



Spanish Fly Racing, Inc.
 attn: Bret Dooley
 4794 W Case Jct
 Prescott, AZ 86305
 Phone (805) 635-5196

Installation instructions for GasGas/OSSA/Vertigo spark arrestor part #GGT-2

- 1) Verify exhaust tube is nominally 32mm in diameter (1.25") & has a minimum of 10mm (0.40") exposed length so that the set screw can find purchase on the tube.
- 2) Check for sharp edges on exhaust tube that may tear O-ring, if present knock down with a file.
- 3) Clean & apply a light coating of grease to the O.D. of the exhaust tube to ease installation.
- 4) Slide spark arrestor onto exhaust tube until it bottoms out against the end of the exhaust tube then tighten set screw with a 2mm allen wrench to fix in place.

SERVICE: To maintain maximum flow characteristics the screen must occasionally be cleaned. Start with 6 hour service intervals & adjust per individual requirements depending on oil brand & mixing ratio. **WARNING: DO NOT USE A TORCH TO BURN THE SCREEN CLEAN, THIS WILL PERMANENTLY DAMAGE THE SCREEN AND DOES NOT REMOVE ALL CARBON DEPOSITS.** To clean the screen: (1) Loosen set screw & remove spark arrestor from exhaust tube (2) Remove O-ring. (3) Remove the screen from the spark arrestor body by pinching the end of the screen to compress it, and then pulling it out in the opposite direction of exhaust flow. (4) Clean the screen with an appropriate solvent (WD40 & a tooth brush work great). (5) Re-install the screen back into the spark arrestor body by again pinching/compressing the screen & sliding it in making sure it is seated in the relief cut in the end of the body. (6) Clean & re-grease and re-install O-ring. (7) Re-install spark arrestor per installation instructions, smile & ride.

PATENT PENDING & USFS APPROVED (REF. FILE#0880-01)

MATERIALS: Body-anodized 6061-T6 aluminum, Sealing- size 24 viton O ring, Screen-stainless steel, Set screw- 4X0.7mm metric 2mm allen head.

WEIGHT: 24 grams (0.85 oz)

APPLICATIONS: Vertigo all models & years (except Nitro-will not fit Nitro without adapter), OSSA 2011-2015 all models, GasGas 2-T 125-300cc years 2002-2009. **GasGas NOTES:** 2010-2022 GG models with plastic end cap shipped with a smaller 30.5mm O.D. metal tip. If you have a 2010-2022 GasGas model with the 30.5mm tip, order the GGT-3 adapter individually or as a kit (Kit Part# GGT-2-GGT-3) with the GGT-2 spark arrestor. Beginning in 2023 GasGas changed the tip again, so 2023 and on models require the new GGT-4 spark arrestor, no adapter required. **Vertigo Nitro NOTES:** 2022 and on Nitro models have a 28.3mm O.D. tip and require the VNSS stainless steel adapter to fit the GGT-2 spark arrestor. The VNSS adapter is available independently or as a kit (Kit Part#GGT-2-VNSS) with the GGT-2 spark arrestor.