



Spanish Fly Racing, Inc.
attn: Bret Dooley
4794 W Case Jct
Prescott, AZ 86305
Phone (805) 635-5196

Installation instructions for GasGas spark arrestor part #GGT-4

- 1) Slide spark arrestor onto exhaust tube until it bottoms out against the end of the exhaust tube then evenly tighten the 3 set screws with a 2mm allen wrench to fix in place.

SERVICE: To maintain maximum flow characteristics the screen must occasionally be cleaned. Start with 6 hour service intervals & adjust per individual requirements depending on oil brand & mixing ratio. **WARNING: DO NOT USE A TORCH TO BURN THE SCREEN CLEAN, THIS WILL PERMINANENTLY DAMAGE THE SCREEN AND DOES NOT REMOVE ALL CARBON DEPOSITS.** To clean the screen: (1) Loosen set screws & remove spark arrestor from exhaust tube (2) Remove O-ring. (3) Remove the screen from the spark arrestor body by pinching the end of the screen to slightly compress it, and then pulling it out in the opposite direction of exhaust flow. (4) Clean the screen with an appropriate solvent (WD40 & a tooth brush work great). (5) Re-install the screen back into the spark arrestor body by again pinching/compressing the screen & sliding it in making sure it is seated in the relief cut in the end of the body. (6) Clean & re-install O-ring. (7) Re-install spark arrestor per installation instructions, smile & ride.

PATENT PENDING & USFS APPROVED (REF. FILE#0880-04)

MATERIALS: Body-anodized 6061-T6 aluminum, Sealing- size 023 viton O ring, Screen-stainless steel, 3X Set screws- 4X0.7mm 6mm length 2mm allen head.

WEIGHT: 19.5 grams (0.7 oz)

APPLICATIONS: 2023-2024 GasGas TXT-GP & TXT-Racing 250cc & 300cc.