



**KRUD KUTTER®
RUST REMOVER GEL**

DESCRIPTION AND USES

Krud Kutter® Rust Remover is a proprietary formulation that penetrates into the voids of a metal surface and dissolves rust and oxidation through chemical action.

Cleaning time will vary according to the severity of the rust. Medium to light rust will be dissolved in 10 minutes or less, while heavier deposits may require a second application. Rust Remover is recommended for cast iron, stainless steel, aluminum, galvanized, chrome and brass.

PRODUCTS

SKU	Description
RG326	32 oz. Trigger Sprayer

PRODUCT APPLICATION

DIRECTIONS

IMPORTANT – READ ENTIRE LABEL BEFORE USE
For best results apply in ambient temperature of 70°F or above. Maintain wet solution on surface to remove rust. Once the rust is dissolved, rinse or wipe the surface, and wait one hour or more before painting. Do not allow remover to dry on painted surfaces.

PRODUCT APPLICATION (cont.)

DIRECTIONS

Remove any oil, grease, or dirt from the surface to be treated. On heavy rusted surfaces, remove any loose rust particles with a wire brush. Rinse the metal with water, to break the surface tension and wash away any loose dirt. Turn sprayer to “**SPRAY**” position, and apply remover liberally to surface. Continue to apply the remover as needed, to keep the surface wet until the rust is dissolved. Disassemble units composed of moveable parts before applying remover. Clean parts and allow to dry before reassembling.

DISSOLVING RUST FROM IRON OR STEEL

Turn sprayer to “**SPRAY**” position, and apply remover liberally to surface. Continue to apply the remover as needed, to keep the surface wet. until the rust is dissolved. Chemical action begins at once. Cleaning time will vary according to the severity of the rust. Medium to light rust will be dissolved in 10 minutes or less, while heavier deposits may require a second application. Once the rust is dissolved, rinse with water, and wipe the surface dry. After one hour or more, the surface is ready to be painted.

ALUMINUM/CHROME

Apply the remover to a wet surface. Allow time to dissolve the rust, then rinse away with clean water and buff dry with a cloth.

GALVANIZED SURFACES

Where the surface is unbroken, treat as suggested for aluminum. Where rust is showing at the surface, treat as for iron or steel.

WARNING! Contains phosphoric acid. Severe eye and skin irritant. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

KRUD KUTTER® RUST REMOVER GEL

PHYSICAL PROPERTIES

	RUST REMOVER GEL
Composition	Phosphoric Acid and other Proprietary Ingredients
Color	Light Yellow
pH	<1.5
VOC	2%
Practical Coverage	32 ounces – 50-75 square feet
Shelf Life	NA
Flash Point	Non-flammable
Warning!	Contains phosphoric acid. Severe eye and skin irritant. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.