

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

SPECIALTY
GLOW IN THE DARK

DESCRIPTION AND USES

Rust-Oleum® Glow in the Dark paint is a luminous latex paint designed to produce a glowing effect for up to 2 hours. It has a light yellow appearance during the day but glows a bright green at night. The painted finish needs to be charged with natural or artificial light for several hours before the surface glows. This product can be applied to wood, metal, drywall, and many other surfaces. It is ideal for use on walls, doors, drawer fronts, storage containers, light switches, toy chests, closets, and other surfaces. Use in bedrooms, play areas, basements, garages, laundry rooms and dorm rooms. Glows for 2 hours after a full charge. For indoor use only.

PRODUCTS

| SKU | Container Size |
|------------|-----------------------|
| 214945 | 7 ounces |

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Painter's Touch or American Accents latex primer enhances adhesion and hiding, and is especially recommended for bare metal and wood surfaces. Recommended primers include 224430T Painters Touch Flat White Primer, 7980502 American Accents Flat White Primer and 249058 Painters Touch White Primer.

APPLICATION

Apply only when air and surface temperatures are above 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Before using, mix thoroughly to ensure any settled pigment is re-dispersed. Thinning is not required. Avoid painting in direct sunlight or on hot surfaces. Use a good quality synthetic brush. Avoid excessive brushing as this will reduce film thickness and protection. Use light even strokes to ensure smooth and uniform flow. Apply two coats 45 minutes apart to achieve maximum glowing effect.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 45 minutes, dries to handle in 4 hours, and can be recoated in 45 minutes.

CLEAN-UP

Clean brush and other application tools immediately with soap and water.

TECHNICAL DATA

SPECIALTY GLOW IN THE DARK

PHYSICAL PROPERTIES

| | | GLOW IN THE DARK |
|--|-------------------|--|
| Resin Type | | Modified Acrylic Copolymer |
| Pigment Type | | Modified Zinc Copper Chloride |
| Solvents | | Propylene Glycol, Water |
| Weight | Per Gallon | 9.34 lbs |
| | Per Liter | 1.12 kg |
| Solids | By Weight | 36.1% |
| | By Volume | 28.4% |
| Volatile Organic Compounds | | 130 g/l (1.08 lbs./gal.) |
| Recommended Dry Film Thickness (DFT) per Coat | | 1.5-2.5 mils (37.5-62.5 μ) |
| Wet Film to Achieve DFT (unthinned material) | | 5.5-9.0 mils (137.5-225 μ) |
| Practical Coverage at Recommended DFT (assumes 15% material loss) | | 25 sq.ft./can (0.6 m ² /can) |
| Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity | Touch | 45 minutes |
| | Handle | 4 hours |
| | Recoat | 45 minutes |
| Shelf Life | | 5 years |
| Flash Point | | 200°F (93°C) |
| Safety Information | | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.