



estimated assembly + installation time



people required



- Put on mood music!
- To prevent damage to product, use the clean side of package carton or rug as working surface.
- In the event of missing or damaged parts, delivery problems etc., please reach out to our team.
  We will be happy to fix the problem!

### care guide

- Clean regularly with a soft and dry cloth.
- To protect finish, avoid use of abrasive cleaners.
- Wipe up spills immediately. Please!

I While assembling the product, tighten the bolts up to 50%. Once all parts are in place, only then fully tighten the bolts.

### product parts





(B) Frame x2

## what's included



(C) - Jcbc (6 x 30mm) x12



(D) - Washer (ø16 xø8) x12



(E) - Lock Washer (Ø8.5) x12



(F) - Allen Key x1



(G)- Screw (4 x 40mm) x2



(H) - Wall Plug x2



While assembling the product, tighten the bolts up to 50%. Once all parts are in place, only then fully tighten the bolts.

### step 1:

Align shelf planks (A) with frames (B) taking this image as reference. Make sure both keyhole slots face upwards for easy mounting.



### step 2:

To secure the shelf parts, tighten all bolts (C), washers (D), lock washers (E) with the help of allen key (F).



# installation instructions



step 1:

Place the shelf on the wall and put a spirit level on it to check alignment. Adjust if needed.



#### step 2:

Once the shelf is straight aligned to the wall, make a line running from its one end the the other using a pencil.



step 3:

Next, measure the distance between the two keyholes using a measuring tool.



#### step 4:

Place the measuring tool against the line marked on the wall and make two marks on it where you want to mount the shelf.



step 5:

Drill holes at the points you just marked.



step 6:

Now, insert the wall plugs (H) using a hammer.



### step 7:

Insert the screws (G) using a screwdriver.



### step 8:

Place the keyhole-slots over the screws.





