



Application Instructions
Peel & Stick Floor Decals

THANK YOU for your purchase of Mirth Studio Floor Decals! Our unique and colorful designs are printed onto resilient, adhesive backed vinyl and laminated so they are durable enough to stand up to high amounts of foot traffic. Our decals are also temporary so they can be removed without damaging the existing floor. It is very important to follow the installation instructions below carefully to ensure that the decals are installed correctly. Once installed, you simply treat them as you would any other floor.

PREPARATION:

Prepping of the surface that you are applying the floor decals to is very important. The floor needs to be clean, dry, and free of any loose debris. First sweep the floors well. Use a mild soap solution to clean the floor. Dry with a towel so that there is no loose debris on the floor and the floors are completely dry. Debris can cause adhesion issues.

Tip: Remove your shoes when you are ready to dry the floor to maintain a clean surface.

VISUALIZATION:

Determine how you would like the design to look once complete. Our designs have a top and bottom and it is important you know which is which before you start. Pick a corner of the floor you are working on as a starting point. No room is exactly square or rectangular so it is important you follow the pattern and tile shape not the the line of the wall.

NOTE: Be careful not to overlap the edges of the decals. Overlapping will allow dirt to become trapped and will cause the decals to peel up with time. Cause the decals to peel up with time.



Mirth Studio

Colorful Patterned Hardwood Floor Tiles


For additional questions please contact Mirth Studio directly:
P: 866-519-7727 | E: info@mirthstudio.com




1. Peel back two inches of the white backing paper along your top edge and fold the backing in place. Butt the edge of the vinyl into the base where the floor meets the wall.



2. Once the decal is in place, tack the two inch edge down working from the middle outwards. You are trying not to trap any air bubbles in the vinyl.



3. With one hand pulling the backing and the other sweeping across the vinyl from left to right, work towards you. Continue until the whole decal is down.



4. Repeat steps 1 through 3 in a straight line until you get to the end of the floor. Then repeat the whole line again using the edges of the tiles as your guide.



5. Work out any air bubble towards the edges of the tile if you can. If not, you can create a pin-hole in the bubble and remove the bubble that way.



6. When the decal folds up along a wall (because walls are never straight) work the vinyl into the base the best you can. At the end you will come back and remove any excess with an exacto knife.