## SD-GLASS DOOR REACH-IN REFRIGERATORS & FREEZERS







USBV-48SDF Freezer USBV-48SD Refrigerator



US REFRIGERATION



USBV-48SDF Freezer USBV-48SD Refrigerator

- Our units are equipped with DIXELL Controls the most efficient in the industry and easy to operate.
- Easy access condenser coil for cleaning.
- All of our reach-in models come standard with casters, stainless steel interiors & exteriors.
- Adjustable heavy duty PVC coated white shelves
- Magnetic gasket with Stainless steel door hinges and a heating element for freezer doors.
- Self-closing and stay open door with door locks.
- A high density, CFC free polyurethane insulation for the entire cabinet and solid door.
- Our equipment is designed using the highest quality materials and components to provide the user with stable product temperatures and lower utility costs at a very competitive price.

 Oversized wiring to prevent heat and damage to electronic components.

 Standard Oversized, high efficient compressor with automatic on-off interior lighting and evaporator fan.



NSF<sub>®</sub>

SD-GLASS DOOR REACH-IN REFRIGERATORS (Bottom mount)											
Model #	Dimensions			Capacity			HP	Electrical		TEMP Range	Weight
6	W	D	Н	Doors	Shelves	Cu. Ft.		Voltage	Amps		
USBV-24SD USBV-48SD	27 58-3/8	31-1 3 31-1	/2 84 /2 84	1 2	4 6	21 46	1/4 1/2	115 115	3.5 5.5	33.8°F – 46.4°F 33.8°F – 46.4°F	264 440
SD-GLASS DOOR REACH-IN FREEZERS (Bottom mount)											
USBV-24SDF USBV-48SDF		31-1 3 31-1	/2 84 /2 84	1 2	4 6	21 46	5/8 1.0	115 115	3.5 5.5	-13.8°F – 1.4°F -13.8°F – 1.4°F -	264 440



