

IM Series

Air Refresh



Air Disinfection



VOC Reduction




Odor Elimination



IM8-N



IM12-N



IM16-N



IM24-N




IM8-S



IM12-S



IM16-S



IM24-S

Specifications

	IM8-N	IM8-S	IM12-N	IM12-S	IM16-N	IM16-S	IM24-N	IM24-S
Voltage	Single-phase 115 V ± 10% 50/60Hz							
Power consumption max.	55 W		82 W		110 W		165 W	
Bentax® Bipolar Ionization tube type VTU-F or VTU-E	8		12		16		24	
Mounting	Stand	Slide In	Stand	Slide In	Stand	Slide In	Stand	Slide In
Air velocity over tubes	up to 3 m/s							
Active Room Air Cleaning Capability*)	up to 32,000 ft ²		up to 48,000 ft ²		up to 64,000 ft ²		up to 96,000 ft ²	
Air Volume In Duct Air Cleaning **)	up to 40,000 CFM		up to 60,000 CFM		up to 80,000 CFM		up to 120,000 CFM	
Weight in lb	15	22	24	32	26	36	38	46

*) Depending on air quality, tube size, air exchange-rate, room ft³, duct-length, and air distribution.

**) Depending on air quality and tube size.

IM Series

Dimensions (mm)

