

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

- **Product (material) name:** Unislick Water Based Tyreshine
- **Other names:**
- **Recommended use:**
- **Supplier:** Sprint Cleaning Products 1/90 Heathcote Rd, Moorebank NSW 2170
- **Tel:** 02 8712 2406 □ **Emergency:** Contact Poisons Info Centre 131 126 or Manufacturer

SECTION 2: HAZARDS IDENTIFICATION

□ **Classification of the substance or mixture:**
 Hazardous according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS)

Hazard Categories: **Flammable Liquids - Category 2**
Serious Eye Damage/Irritation - Category 2A

□ **Pictograms**



- **Signal word:** Danger
- **Hazard statement(s):**
H225: Highly flammable liquid and vapor.
H319: Causes serious eye irritation

□ **Precautionary statement(s):**

Preventio	P233	Keep container tightly closed.
	P240	Ground/bond container and receiving equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P210	Keep away from all sources of ignition. No smoking.
	P264	Wash face, hands and any exposed skin thoroughly after
	P280	Wear protective gloves/protective clothing/eye
Response	P241	Use explosion-proof electrical/ventilating/lighting/equipment.
	P303 + P361 + P353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	P337 + P313	If eye irritation persists: Get medical advice/attention.
	P370 + P378	In case of fire: Alcohol resistant foam is the preferred fire-fighting medium. However, if it is not available, fine water spray or water fog can be used to extinguish.
Storage	P403 + P235	Store in a well-ventilated place. Keep cool.
Disposal	P501	Dispose of contents/container in accordance with local / regional / national / international regulations.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**MIXTURE:**

Chemical name	CAS No.	% product
Ethanol	64-17-5	<50%
Other Non Hazardous		30%
Water		Balance

This is a commercial product and the exact ratio of ingredients may vary slightly and trace quantities of impurities are also possible.

SECTION 4: FIRST AID MEASURES

Swallowed	Rinse mouth with water. Give water to drink provided victim is conscious. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position if possible) to maintain open airway and prevent aspiration. Seek medical attention.
Eye	Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Take care not to rinse contaminated water into the non-affected eye. Seek immediate medical attention.
Skin	Immediately remove all contaminated clothing, including footwear after wetting with water if available. Wash affected areas thoroughly with water. If irritation occurs, seek medical advice.
Inhaled	Remove victim from exposure to fresh air. Allow patient to assume most comfortable position and keep warm and at rest. If patient finds breathing difficult, and develops a bluish discoloration of the skin, ensure airways are clear, and have qualified person give oxygen through a face mask. Seek immediate medical advice. BURNS: Immerse affected area in cold water for 10-15 minutes. Bandage lightly with sterile dressing. Treat for shock if required. Transport to hospital if required.
Advice to Doctor	Treat symptomatically based on individual reactions of patient and judgement of doctor.

SECTION 5: FIRE FIGHTING MEASURES

General Measures	Flame-proof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Remain upwind and notify those downwind of hazard.
Flammability Conditions	Highly flammable. Vapours may form explosive mixtures with air.
Extinguishing Media	In case of fire, appropriate extinguishing media include water fog or foam. Keep containers cool with water spray. If safe to do so, remove containers from path of fire. Earth containers when dispensing fluids.
Fire and Explosion Hazard	Highly flammable- explosive vapour. May ignite from sources including cigarettes, open flames, spark producing switches / tools, heaters, naked lights, pilot lights, mobile phones etc
Hazardous Products of Combustion	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Special Fire Fighting Instructions	Clear fire area of all non-emergency personnel. Stay upwind. Keep out of low areas. Eliminate ignition sources. Move fire exposed containers from fire area if it can be done without risk. Do NOT allow fire fighting water to reach waterways, drains or sewers. Store fire fighting water for treatment.
Personal Protective Equipment	Fire fighters should wear a positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots and gloves) or chemical splash suit. Please note: Structural fire fighters' uniform will provide limited protection.

Flash Point	13 - 18 °C Closed Cup
Lower Explosion Limit	3.3 %
Upper Explosion Limit	19.0 %
Auto Ignition Temperature	No Data Available
Hazchem Code	YE

SECTION 6: ACCIDENTAL RELEASE MEASURES

General Response Procedure	Shut off all possible sources of ignition. Use clean, non-sparking tools and equipment. Avoid accidents, clean up immediately. Increase ventilation.
Clean Up Procedures	Absorb spill with sand or similar, collect and place in sealable containers for disposal according to local authority guidelines.
Containment	Stop leak if safe to do so.

Environmental Precautionary Measures: Do NOT let product reach drains or waterways. If product does enter a waterway, advise the Environmental Protection Authority or your local Waste Management.

Evacuation Criteria: Evacuate all unnecessary personnel.

Personal Precautionary Measures: Personnel involved in the clean up should wear full protective clothing as listed in section 8.

SECTION 7: HANDLING AND STORAGE

Handling	Ensure an eye bath and safety shower are available and ready for use. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling. Take precautionary measures against static discharges by bonding and grounding equipment. Avoid contact with eyes, skin and clothing. Do not inhale product vapours. Avoid prolonged or repeated exposure. Operations should be carried out in an efficient fume hood or equivalent system. Remove contaminated clothing and wash before reuse. Discard contaminated shoes. Keep away from combustible material. Empty containers pose a fire risk, evaporate residue under a fume hood. Chemicals should be used only by those trained in handling potentially hazardous materials.
Storage	Store in a cool, dry, well-ventilated, fire-proof area. Keep containers tightly sealed when not in use. Inspect regularly for deficiencies such as damage or leaks. Protect against physical damage. Ground and bond storage containers. Store away from incompatible materials as listed in section 10. Store away from direct sunlight and other sources of heat. This product has a UN Classification of 1170 and a Dangerous Goods Class 3 (flammable) according to The Australian Code for the Transport of Dangerous Goods By Road and Rail
Container	Container type/packaging must comply with all applicable local legislation. Store in original packaging as approved by manufacturer.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

General The following exposure standard has been established by The Australian Safety and Compensation Council (ASCC); Ethyl Alcohol (ethanol) CAS: 64-17-5
TWA = 1000ppm (1880mg/m³)
Methyl isobutyl ketone CAS: 108-10-1 TWA = 50 ppm (205mg/m³)
STEL = 75 ppm (307mg/m³)

NOTE: The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week.

Exposure Limits No Data Available

Biological Limits No information available on biological limits for this product.

Engineering Measures A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. In poorly ventilated areas, mechanical explosion proof extraction ventilation is recommended. Flammable / explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

Personal Protection Equipment RESPIRATOR: Where an inhalation risk exists, wear a type A (Organic vapour) Respirator, At high levels wear Self Contained Breathing apparatus (SCBA) or an Air-line respirator (AS1715/1716).
EYES: Wear splash proof goggles (AS1336/1337).
HANDS: Nitrile or neoprene gloves are recommended (AS2161).
CLOTHING: Flame-retardant coveralls and anti-static footwear (AS3765/2210).

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn, ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

Work Hygienic Practices No Data Available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Liquid, Free of any foreign matter
Odour	No Data Available
Colour	Clear
pH	No Data Available
Vapour Pressure	5.9 kPa (@ 0 °C)
Relative Vapour Density	No Data Available
Boiling Point	78 °C

Melting Point	No Data Available
Freezing Point	No Data Available
Solubility	Completely soluble
Specific Gravity	0.79 g/ml - 0.80 g/ml
Flash Point	13 - 18 °C Closed Cup
Auto Ignition Temp	No Data Available
Evaporation Rate	No Data Available
Bulk Density	No Data Available
Corrosion Rate	No Data Available Decomposition Temperature
Specific Heat	No Data Available
Molecular Weight	No Data Available
Net Propellant Weight	No Data Available Octanol Water Coefficient
Partition Coefficient	No Data Available Saturated Vapour Concentration No Data Available Vapour Temperature
Viscosity	No Data Available
Volatile Percent	No Data Available
VOC Volume	No Data Available
Additional Characteristics	Methyl Isobutyl Ketone (MIBK)
Potential for Dust Explosion	Product is a flammable liquid.

Fast or Intensely Burning Characteristics	No data
Flame Propagation or Burning Rate of Solid Materials	No data
Non-Flammables That Could Contribute Unusual Hazards to a Fire	No data
Properties That May Initiate or Contribute to Fire Intensity	No data

SECTION 10: STABILITY AND REACTIVITY

General Information	Flammable liquid with explosive vapour.
Chemical Stability	Product is stable under normal conditions of use, storage and temperature.
Conditions to Avoid	Avoid excessive heat, direct sunlight, static discharges, moisture and high temperatures.
Materials to Avoid	Oxidising agents (eg. Hypochlorites, peroxides), acids (sulphuric acid), strong alkalis (eg. Hydroxides), heat and ignitions sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Polymerisation	No Data Available

SECTION 11: TOXICOLOGICAL INFORMATION

General Information	Low to moderate toxicity - irritant. This product has the potential to cause adverse health effects with chronic over exposure. Use safe work practices to avoid eye or shin contact and over exposure via inhalation.
	Ethanol: Inhalation LC50 Rat: 2000 ppm/10h Ingestion LD50 Mouse: 3450 mg/kg

Skin Irritant Skin irritant. Prolonged contact may result in drying and defatting of the

	skin, rash and dermatitis. Toxic effects may result from skin absorption.
Eye Irritant	Irritating to eyes. Exposure may result in lacrimation, irritation, pain and redness.
Ingestion	Chronic ingestion may result in cirrhosis of the liver. Over exposure may cause central nervous system depression. Low toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain, diarrhoea, headache, dizziness and drowsiness with large doses. Liver damage may occur with high level of chronic ingestion.
Inhalation	Inhalation may cause irritation to the respiratory system, nose and throat irritation, coughing and headache. Over exposure may result in nausea, dizziness and drowsiness.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity	Golden ide LC0: >1000 mg/L/48h Daphnia Magna EC50: >1000 mg/L/24h
Mobility	If spilled on solid, ethanol will either evaporate or leach into the ground due to the relatively high vapour pressure and low absorption in soil.
Persistence/Degradability	This product will biodegrade, probably to acetic acid and formaldehyde. Ethanol will volatilise from water and biodegrade, and is not expected to bioconcentrate. It will photodegrade in air with a half-life ranging from hours (polluted air) to days (clean air).
Bioaccumulation Potential	No information available on bioaccumulation for this product.
Environmental Impact	No data

SECTION 13: DISPOSAL CONSIDERATIONS

General Information	Dispose of in accordance with all local, state and federal regulations. All empty packaging should be disposed of in accordance with Local, State and Federal Regulations or recycled/reconditioned at an approved facility. For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved.
Precautions for landfill	Contact a specialist disposal company or the local waste regulator for advice. This material may be suitable for approved landfill.

SECTION 14: TRANSPORT INFORMATION

Sea Transport	IMDG
Proper Shipping Name	ETHANOL
Class	3 Flammable Liquids
Subsidiary Risk(s)	No Data Available
UN Number	1170
Hazchem	2YE
Pack Group	II
Special Provision	No Data Available
EMS	FE,SD
Marine Pollutant	No
Air Transport	IATA

National Transport Commission (Australia)

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Dangerous Goods Classification	Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)
Sea Transport	IMDG
Proper Shipping Name	ETHANOL
Class	3 Flammable Liquids
Subsidiary Risk(s)	No Data Available
UN Number	1170
Hazchem	2YE
Pack Group	II
Special Provision	No Data Available
EMS	FE,SD
Marine Pollutant	No
Air Transport	IATA

National Transport Commission (Australia)

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Dangerous Goods Classification	Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)
---------------------------------------	---

SECTION 15 REGULATORY INFORMATION

The chemicals in formulation are listed on the Australian Inventory of Chemical Substances (AICS).
The chemical is listed in schedule 5 of the SUSMP.

SECTION 16 OTHER INFORMATION

□ **Date of preparation or last revision of the MSDS** **December 2016**

Acryoyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
ASCC	Office of the Australian Safety and Compensation Council
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

Disclaimer:

A) This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. The information is meant to describe Safety Requirements of the product and should not be construed as guaranteeing specific properties. This MSDS is analogous to the data for the principal components of the mixture/compound. No warranty, express or implied, is made as to its accuracy, reliability or completeness.

B) Each user should read this SDS, all product labels, and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

C) We can not accept any liability for any damage or injury caused by the product as it is sold and its use, handling and storage are completely out of our control.