



# Material Safety Data Sheet

---

## SECTION 1 - Product and Company Identification

Product Name: ECOS Paints Filler  
Description: Gypsum-based filler for holes and joints  
Document ID: 10046 R 1.1  
Document Date: 03-30-2013  
Document Version: R1.1  
Manufacturer: Imperial Paints  
Address: PO Box 489, Fairforest, SC, 29336  
Contact: 864.595.3840

## SECTION 2 - Hazards Identification

Noted components appear on the California Prop 65 List

## SECTION 3 - Composition/Information on Ingredients

Chemical nature: Powder.

Ingredients:

Gypsum plaster (more than 70%), limestone (more than 10%). May also contain, as part of these: perlite, fullers earth, talc (zero-asbestos), quartz, mica, polyvinyl alcohol (trace), PVA (trace).

Hazardous components: none.

VOCs/Solvents: none.

## SECTION 4 - First Aid Measures

Eye contact: May cause temporary irritation.  
Irrigate with water for 15 minutes holding eyelid open.  
Seek medical attention if irritation persists.

Skin contact: Prolonged contact may cause dryness. Use moisturizing lotion on dry areas.  
Wash thoroughly with soap and water.

Inhalation of vapor: Remove to fresh air immediately. If breathing difficulty continues, seek medical attention.

## SECTION 5 - Fire Fighting Measures

Product is not combustible when wet or dry.



# Material Safety Data Sheet

---

## SECTION 6 - Accidental Release Measures

Personal protection: Refer to Section 8  
Environmental precautions: Prevent excess product entering drains as it can cause blockages.  
Cleaning and taking up: Spillages should be scooped into a suitable container for reuse or disposal.

## SECTION 7 - Handling and Storage

Handling: No special precautions necessary. Observe good housekeeping practices.  
Storage: Store cool and dry, and away from direct sunlight.

## SECTION 8 - Exposure Controls/Personal Protection

Workplace parameters: none  
Personal protective equipment:  
    Respiratory protection: A NIOSH approved particulate respirator is recommended in poorly ventilated areas. OSHA's 29 CFR 1910.134 (Respiratory Protection Standard) must be followed whenever work conditions require respirator use.  
    Eye protection: Advisory (Safety glasses or goggles).  
    Skin protection: Gloves, protective clothing and/or barrier creams may be utilized if conditions warrant.  
Hygiene measures; None.

## SECTION 9 - Physical and Chemical Properties

Physical form: Powder  
Color: White/off-white  
Odor: Faint – none  
Flash point: Not applicable  
Vapor pressure: Not applicable  
Specific Gravity: 2.4 - 2.6  
Solubility in water: Insoluble  
PH: 7 – 9  
Flammability: Non-flammable

## SECTION 10 - Stability and Reactivity

The product is stable under recommended storage conditions – see Section 7  
Incompatible materials: Contact with strong acids may generate of carbon dioxide.



# Material Safety Data Sheet

---

## **SECTION 11 - Toxicological Information**

Long term experience of this product type indicates no danger to health when properly handled under normal conditions.

## **SECTION 12 - Ecological Information**

Presents no ecological/environmental hazard.

## **SECTION 13 - Disposal Considerations**

Non-hazardous waste. Dispose of according to Local, State, Federal, and Provincial Environmental Regulations.

## **SECTION 14 - Transport Information**

The product is not classified as Dangerous for Carriage. It is:

- ✓ Non-HAZMAT
- ✓ Non-toxic
- ✓ Non-flammable

## **SECTION 15 - Regulatory Information**

### **TSCA**

All components comply with the TSCA regulations and are either exempt or listed therein.

### **California Proposition 65**

Respirable crystalline silica is known to the state of California to cause cancer. If used as directed, no respirable crystalline silica is generated.

## **SECTION 16 - Other Information**

### **HMIS (Hazardous Materials Identification System) Information**

Health	0
Flammability	0
Physical Hazard	0
Personal Protection	A – Safety glasses recommended. (If spraying without local exhaust ventilation, it is recommended that you also wear a normal dust mask.)



# Material Safety Data Sheet

---

## **Note on hazards from lead paint:**

Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

## **Disclaimer**

*At the time of publishing (as per document date in Section 1), all the enclosed data and information was believed to be complete and accurate, and is provided in good faith. It is the responsibility of the reader to ensure that they have all the information they need to ensure the health and safety of them themselves and their employees. Such determination must be in accordance with all applicable local and federal laws and regulations.*