



# Material Safety Data Sheet

---

## SECTION 1 - Product and Company Identification

Product Name: ECOS Paints Plaster Sealer  
Description: Water-borne sealer for new plaster and absorbent walls and ceilings  
Document ID: 10049 R 1.1  
Document Date: 04-03-2013  
Document Version: R1.1  
Manufacturer: Imperial Paints  
Address: PO Box 489, Fairforest, SC, 29336  
Contact: 864.595.3840

## SECTION 2 - Hazards Identification

Noted components appear on the California Prop 65 List

## SECTION 3 - Composition/Information on Ingredients

Chemical nature: Water based paint.

Ingredients:

Water, acrylic dispersion, thickeners – cellulosic and polymeric, dispersing aids (various).

Hazardous components: none.

VOCs/Solvents: none.

## SECTION 4 - First Aid Measures

Eye contact: May cause temporary irritation.  
Irrigate with water for 15 minutes holding eyelid open.  
Seek medical attention if irritation persists.

Skin contact: Prolonged contact may cause irritation.  
Remove contaminated clothing.  
Wash thoroughly with soap and water.

Inhalation of vapor: No hazard.

## SECTION 5 - Fire Fighting Measures

Product is water based and not combustible when wet or dry.

## SECTION 6 - Accidental Release Measures

Personal protection: Refer to Section 8

Environmental precautions: Prevent product entering soil, natural waters, and drains.

Cleaning and taking up: Large spillages should be contained and pumped into a receiving vessel.  
Small spillages should be absorbed on inert absorbent.  
For disposal methods refer to Section 13



# Material Safety Data Sheet

---

## SECTION 7 - Handling and Storage

Handling: No special precautions necessary. Observe good housekeeping practices.

Storage: Store between +5°C and 20°C protected from frost and direct sunlight. Do not use storage vessels or pipe work made of aluminum, copper or their alloys. Detailed advice on storage systems can be provided.

## SECTION 8 - Exposure Controls/Personal Protection

Workplace parameters: None.

Personal protective equipment:

Respiratory protection: None.

Hand protection: None.

Eye protection: Advisory.

Skin protection: In case of severe splashing wear waterproof overalls and boots. Wash with soap and water after handling.

Hygiene measures; None.

## SECTION 9 - Physical and Chemical Properties

Physical form: Liquid

Color: Milky/clear.

Odor: Faint – none

Flash point: Not applicable

Vapor pressure: 23hPa @ 20°C

Relative density: 1.0 – 1.4

Solubility in water: Insoluble but miscible in all proportion

PH: 8 – 11

Viscosity: Variable

Flammability: Non-flammable.

## SECTION 10 - Stability and Reactivity

The product is stable under recommended storage conditions – see Section 7

Incompatible materials: None.

## SECTION 11 - Toxicological Information

Long term experience of this product type indicates no danger to health when properly handled under normal conditions.



# Material Safety Data Sheet

---

## **SECTION 12 - Ecological Information**

Degradation/elimination: The product can be virtually eliminated from water by abiotic processes, e.g. adsorption onto activated sludge.  
Bioaccumulation: No evidence for bioaccumulation.  
Eco-toxic effects: No long term effects expected.

## **SECTION 13 - Disposal Considerations**

Waste product should not be discharged directly into drains or waterways without treatment. Disposal of product and packaging should always comply with local and national regulations. Waste water containing product should be treated in a separation and biological treatment plant.

## **SECTION 14 - Transport Information**

The product is not classified as Dangerous for Carriage. It is:

- ✓ Non-HAZMAT
- ✓ Non-toxic
- ✓ Non-flammable



# Material Safety Data Sheet

---

## SECTION 15 - Regulatory Information

### TSCA

All components comply with the TSCA regulations and are either exempt or listed therein.

### California Proposition 65

Noted components appear on the California Prop 65 List

## SECTION 16 - Other Information

### HMIS (Hazardous Materials Identification System) Information

Health	0
Flammability	0
Physical Hazard	0
Personal Protection	A – Safety glasses recommended. (If spraying without local exhaust ventilation, it is recommended that you also wear a normal dust mask.)

### Note on hazards from lead paint:

Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

### Disclaimer

*At the time of publishing (as per document date in Section 1), all the enclosed data and information was believed to be complete and accurate, and is provided in good faith. It is the responsibility of the reader to ensure that they have all the information they need to ensure the health and safety of them themselves and their employees. Such determination must be in accordance with all applicable local and federal laws and regulations.*