

POLISHED PLASTER CO.

BONDING LIQUID – PRODUCT DATASHEET

PRODUCT DESCRIPTION

- Bonding Liquid is a universal water based bonding aid
- Bonding Liquid is a classical solution polymer based penetrating, bonding and stabilizing liquid, sealer for interior and exterior use on powdery, friable and very porous new and weathered substrates such as Lime Wash, old paint, new friable or porous plaster and fillers. Once the Bonding Liquid has been applied, then these areas can be over coated with a range of Polished Plaster Co's decorative products.

READ ALL THE INSTRUCTIONS THOROUGHLY BEFORE USE

APPLICATION AREAS

- New / weathered plaster, hardboard and fibre cement walls.
- Powdery, friable weathered previously painted areas.
- Lime Wash.
- Rhinolite walls.

PRODUCT FEATURES

- Excellent penetrating and binding properties.
- Excellent adhesion.
- Excellent alkali resistant properties.
- Once sealed can be top coated with a wide range of water and Solvent based products

PRODUCT DATA

- | | |
|----------------------|-------------------------------|
| • Resin Base | Solution polymer based resin. |
| • Drying Time | 1 hour. |
| • Film Thickness | Penetrating liquid. |
| • Spreading Rate | 10m ² /litre. |
| • Surface Appearance | Slight glossy appearance |

MIXING

Always stir well with a flat paddle.

APPLICATION METHOD

Brush or short hair roller

SURFACE PREPARATION

- Remove all dust, foreign material, fungal and algae growth.
- Remove all loose, flaking and bubbling paint.
- Lime Wash coated walls – remove lime wash as far as possible with scraper blades and or soft wire or hard fibre brushes but be careful not to damage the plaster.
- Sand carefully and remove dust.

NOTICE

Polished Plaster Co shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods.