POLISHED PLASTER CO.

METALLIC PAINT - PRODUCT DATASHEET

PRODUCT DESCRIPTION

Metallic Paint is a thermoplastic-acrylic solvent-based paint which can be applied onto concrete or Italian Polished Plaster to provide a metallic effect finish. It is formulated for easy application, by roller, cloth and brush providing a uniform distribution of metallic pigment across the substrate, giving a smooth finish.

READ ALL THE INSTRUCTIONS THROUGHLY BEFORE USE

PRODUCT FEATURES

- · Easy to apply
- · Fast drying
- · Smooth metallic finish

PROPERTIES

Paint type Solvent basedFinishing Gloss Metallic Effect

COMPOSITION

Pigment Mainly Aluminium pigment, carbon black, iron oxide and organic pigment

Binder Thermoplastic Acrylic resin

Thinner Combination of Ketone and Hydrocarbon

TECHNICAL DATA

Drying Time Touch Dry 15 minutes (Dependent on temperature and humidity)
 Hard Dry 45 minutes (Dependent on temperature and humidity)

nara bry 45 minutes (bependent on temperature and namic

Recoating Time 2 hours (Dependent on temperature and humidity)

Dry Film Thickness Around 35 - 40

µm (Actual thickness per coat is based on substrate condition)

• Coverage 50m²/5L

CLEANING

Clean up equipment with solvent-based thinner immediately after use.

SAFETY PRECAUTIONS

- · Keep container tightly closed and keep out of reach children or away from food and drink.
- · Ensure good Ventilation during application and drying.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- · Paint must always be stored in a cool place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose off any paint waste in accordance with the appropriate Environment Quality Regulations.

NOTICE

Polished Plaster Co shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods.