

# POLISHED PLASTER CO.

## UV-STABLE SEALER

### PRODUCT DESCRIPTION

A milky white pure acrylic sealer that dries to a clear sheen finish. Quick drying, good water resistance and washability. Incorporated UV factor for exterior use.

### READ ALL THE INSTRUCTIONS THOROUGHLY BEFORE USE

#### RECOMMENDED USES

Interior and exterior vertical, brick and wall tile areas (porous or semi-porous).

#### TECHNICAL DATA

Spread Approx.	10m <sup>2</sup> /l
Viscosity	90 - 100 Krebb Units
SG	1.04kg/l
pH	8 - 9
Mass Solids	29.50%
Accelerated Stability	60°C Pass
Freeze thaw stability	Pass
Drying time	
Touch dry:	25 min
Hard dry:	4 hours
Fully cured:	1 week
Recommended dry film	100 micron (2 coats)

#### CLEANING

Clean equipment with water.

#### SURFACE PREP

Clean the surface.

#### APPLICATION METHOD

Brush and roller.

#### NOTICE

Polished Plaster Co shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods.