

POLISHED PLASTER CO.

WATERPROOFING SEALER

PRODUCT DESCRIPTION

A low viscosity, clear silicone liquid providing water repellency to the substrate being treated. Product works by means of impregnation and can be used as an injection agent for combatting rising damp. It develops its water repellent effect by reacting with atmospheric humidity and with water absorbed on the walls of the pores and capillaries of the building material. Silicone liquid does not provide a specific finish but retains the natural colour of the substrate being treated.

READ ALL THE INSTRUCTIONS THOROUGHLY BEFORE USE

RECOMMENDED USES

The following surfaces should be treated to provide water repellency and to stop fungal/algae growth: Plaster, brick, aerated concrete, fibre cement and paint. A 2 coat treatment is normally recommended.

TECHNICAL DATA

S.G.	0.8kg/l
Viscosity	< 20 seconds Ford Cup no 4 @ 25°C
Coverage	Depends on the porosity of the building material. Average 4m ² /l
Drying	± 2 hours @ 25°C. Depends on volume used. Once the 'wetness' disappears another coat may be applied.

CLEANING

Clean equipment with Turps

SURFACE PREP

Clean the surface and apply Silicone Liquid when surface is dry

APPLICATION METHOD

Low pressure spray.

NOTICE

Polished Plaster Co shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods.