

Safety Data Sheet

Color Fire Fluid - Green

Section 1. Identification

Product Identifier Color Fire Fluid - Green

Recommended use Product is intended for professional Special Effects use only.

Uses advised against

Use of this material is at the sole risk of the purchaser.

Manufacturer Contact Roger George Special Effects

14525 Bessemer St Van Nuys, CA, 91411

USA

Phone Emergency Phone Fax

(818) 994-3049 (800) 535-5053 #85740 (818) 994-9432

Section 2. Hazards Identification

Classification FLAMMABLE LIQUIDS - Category 2

ACUTE TOXICITY - DERMAL - Category 3 ACUTE TOXICITY - INHALATION - Category 3

EYE IRRITATION - Category 2A

Specific target organ toxicity - single exposure - Category 1 (Eyes,

Central nervous system)

Specific target organ toxicity - single exposure - Category 3 (Central

nervous system)

Signal Word Danger

Pictogram



Hazard Statements Toxic if swallowed, in contact with skin or if inhaled. Causes serious eye irritation.

May cause drowsiness or dizziness

Causes damage to organs.

Suspected of damaging fertility or the unborn child.

Precautionary Statements

PREVENTION

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Take precautionary measures against static discharge. Do not breathe fume/gas/

mist/vapors/spray.

Wash skin throughly after handling.

Do not eat, drink or smoke while using this product.

Use only outdoors or in a well ventilated area.

Wear protective gloves/eye protection/face protection.

RESPONSE

IF SWALLOWED: Immediately call a poison center/doctor. Rinse mouth.

IF ON SKIN: Take off all contaminated clothing immediately. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call poison center/doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF EXPOSED: Call a poison center or doctor.

If eye irritation persists: get medical attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Keep cool

Store locked up.

Dispose of contents/ container to an approved waste disposal plant.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

No Data Available

Section 3. Ingredients

CAS		Ingredient Name	Weight %
67-56-1	Methnanol		90% - 100%

Occupational exposure limits, if available, are listed in Section 8.

This Product contains one or more ingredients where the specific chemical identity and exact percentage of composition has been withheld as a trade secret

Section 4. First-Aid Measures

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Inhalation Move to fresh air.

If unconscious, place in recovery position and seek medical advice.

If symptoms persist, call a physician.

Skin Contact If on skin, rinse well with water.

If on clothes, remove clothes.

Eye Contact Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Ingestion Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Do not induce vomiting without medical advice.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Use dry chemical, alcohol-resistant foam, or carbon dioxide (CO2).

Unsuitable Extinguishing

Media

High volume water jet.

Flammable Properties Carbon oxides, Formaldehyde, Toxic fumes

Precautions Do not allow run-off from fire fighting enter drains or water courses.

Collect contaminated fire extinguishing water separately. This must not be

discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

For safety reasons in case of fire, cans should be stored separately in closed

containments.

Use a water spray to cool fully closed containers.

Special protective

equipment for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

Use personal protective equipment.

Section 6. Accidental Release Measures

Personal Precautions Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-tions. Vapors can

accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

This product may cause damage to trees or vegetation by root absorption.

Spills/Leaks Clean-up Contain spillage, and then collect with non-combustible ab-sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal

according to local / national regulations

Section 7. Handling and Storage

Handling Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-plication area.

Take precautionary measures against static discharges.

Provide sufficient ventilation.

Open container carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national regulations.

Storage No Smoking

Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to

prevent leakage.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TWA	OSHA Z-1	STEL
	Methanol	200 PPM S	200 PPM S	250 PPM

Personal Protective Equipment Respirators Goggles, Gloves, Respirator

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are un-known, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respi-rator if there is any potential for uncontrolled release, expo-sure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection

Eye Protection Eye wash bottle with pure water

Tightly fitting safety goggles

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the product.

Section 9. Physical and Chemical Properties

Dharata at Otata	I described	
Physical State	Liquid	
Color	Water-white	
Odor	Alcohol	
Odor Threshold	160 PPM	
Solubility	Miscible in	
	water	
Partition coefficient Water/n-octanol	- 0.79	
VOC%	N/A	
Viscosity	0.55	
Specific Gravity	0.795	
Density lbs/Gal	0.796	
Pounds per Cubic Foot	N/A	
Flash Point	36.5 F	
FP Method	closed cup	
Ph	N/A	
Melting Point	-144 F	
Boiling Point	148.1 F	
Boiling Range	N/A	
LEL	6	
UEL	36.5	
Evaporation Rate	N/A	
Flammability	Class I B	
Decomposition Temperature	N/A	
Auto-ignition Temperature	867 F	
Vapor Pressure	97.86 mm of	
	HG @20 C	
Vapor Density	1.11 @ 20 C	

General This product has not been tested as a whole

Section 10. Stability and Reactivity

Stability Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Vapors may form explosive mixture with air.

Conditions to Avoid

Keep away from heat, sparks, and flame.

Incompatibilities Incompatible with oxidizing agents and strong acids. Incompatible with strong

reducing agents.

Hazardous Decomposition Burning produces noxious and toxic fumes. Carbon oxides and formmaldehyde.

Possibility of Hazardous Reactions

Precipitate is a weak acid that may cause corrosion of base metals. Reaction with strong reducing agents such as metal hydrides or alkalki metals will generate hydrogen gas which could create an explosive hazard.

Section 11. Toxicological Information

Acute Toxicity

Oral Acute toxicity estimate: 101.01 mg/kg

Inhalation Acute toxicity estimate: 3.03 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The component/mixture is toxic after short term inhalation.

Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry

leaders and the EU Harmonized Classification (Annex VII).

Dermal Acute toxicity estimate: 303.03 mg/kg

Assessment: The component/mixture is toxic after single contact with skin.

Carcinogenicity No evidence of carcinogenicity. Based on the available data, the classification

criteria are not met.

Additional Info Solvents may degrease the skin.

Section 12. Ecological Information

Eco-toxicity No data available

Persistence & No data available Degradability

Bio-accumulative

Potential

No data available

Mobility in soil No data available

Section 13. Disposal

Compliance ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE,

PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT

PROPER AGENCIES.

Contaminated Packaging

Empty remaining contents. Dispose of as unused product. Do not re use

empty containers.

Section 14. Transport Information

UN Number 1230 **UN Proper Shipping Name** Methanol, 3 **DOT Classification** Flammable Liquid

Packing Group

Section 15. Regulatory Information

California Proposition 65 WARNING: This product contains chemical(s) known to the State of California to

cause birth defects or other reproductive harm.

EPA Methanol - CAS 67-56-1 250 ppm is an EPA Hazardous Air Pollutant.

SARA TITLE 311/312 Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)


Specific target organ toxicity (single or repeated exposure) Serious eye damage

or eye irritation

Section 16. Other Information

9/17/2020 **Revision Date**

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 =Extreme, * = Chronic

Company Policy/Disclaimer The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. The supplier nor any of its subsidiaries makes no representations as to its accuracy or sufficiency. This information is furnished without warranty of any kind. Conditions of use are beyond Roger George Special Effects' control and therefore users must determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling and disposal of the product, or from the publications or use of, or reliance upon information contained herein. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process in which user assumes all responsibility.