

Bond It Bath & Kitchen is a high quality, flexible, water-based sealant that forms a watertight seal to most surfaces. It contains a powerful antifungal compound to prevent mold growth. Easy water clean-up. Low VOC content.

### Product Use

For use as a grout repair and for sealing around all types of bathtubs, basins, sinks, toilets, countertops, and backsplash. Adheres to plastics, ceramics, glass, granite, marble, porcelain, vinyl, plaster, and wood. Not suitable for areas constantly submerged in water.


### Application / Instructions

Surfaces must be clean, dry, and dust or grease-free. Remove all existing sealant. When sealing around bathtubs, fill the tub half full of water to position the bath at midpoint of any potential joint movement. Cut the tip of the cartridge without damaging the threaded area. Screw on nozzle and cut at an angle of 45° to an opening slightly larger than the gap to be sealed. Use foam backing rod to fill any deep gaps between the wall and bath to form a backing for sealant. Apply using a standard sealant gun and tool down within 10 minutes of application using the appropriate tool. Protect from water for at least 24 hours after sealing or until a tough skin has formed. Thorough ventilation will aid the curing process. Clean tools with soapy water after use. Regular cleaning of the sealed joint will prevent mold build-up.

### Features & Benefits

- Permanently Flexible
- Water Resistant
- Excellent Adhesion
- Non-shrinking
- Mold & Mildew Resistant
- Solvent-Free
- Sanitary
- 10 Year Lifespan
- Meets ASTM C834

### Available Sizes



### Physical Properties

Fast Cure	Tools within 5 minutes
Skinning Time at 68°F and 50%RH	Skins after 20 minutes
Full Cure	24 hours
Waiting Time Before Painting	1 to 24hrs
Sag	None
Movement Accommodation	7.5%
Water Resistance	Good

### Packaging & Ordering Information

Code	Color	Size	Barcode
SLBAWH	White	10 oz.	810030760245

### Surface Preparation

For best results, surface should be clean, dry and structurally sound.

### Limitations

This product is not a silicone sealant! Not suitable when:

- applied externally during rainy weather.
- applied at temperatures below 41°F (+5°C).
- used in joints constantly immersed in water.
- used in contact with bituminous products.
- used in areas of high abrasion, e.g. floor joints.
- for use with plastic baths - use a sealant with greater flexibility

### Storage & Shelf Life

Store in cool, dry conditions, protect from frost.

Product should be stored in the original, unopened container. Use within 24 months of date of manufacture.

### Cleanup

Clean up excess wet caulk with a damp sponge before it cures. Excess dried caulk must be cut or scraped off.

Wash hands and tools with warm water and soap.

### Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

### Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting [www.bonditusa.com](http://www.bonditusa.com).

### Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

### Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

*Please refer to our website at [www.bonditusa.com](http://www.bonditusa.com) for the most up-to-date Technical Data Sheets and Safety Information.*

*Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite [www.bonditusa.com](http://www.bonditusa.com)*

### Seal It Services, Inc. dba Bond It

[salesUS@bonditgroup.com](mailto:salesUS@bonditgroup.com) | [www.bonditusa.com](http://www.bonditusa.com)  
(800) 587-9940

#### West

13214 Crenshaw Blvd  
Gardena, CA 90249

#### East

3301 Industrial Dr  
Sanford, NC 27332