

Bath & Kitchen Plus

Sanitary Grade Silicone

Technical Data Sheet

Bond It Bath & Kitchen PLUS is a premium sanitary grade silicone, ideal for use in hotels, leisure facilities and domestic installations. Formulated for use in wet and humid areas it contains a powerful fungicide that inhibits mold growth.

Product Use

For waterproofing joints between ceramic tiles, bathtubs, sinks, showers, backsplashes and counters. Can also be used for bedding sinks into kitchen tops and vanity units and for sealing shower trays and shower units. Good adhesion to glass, melamine, laminates, sanitary plastics, anodized aluminum, lacquered metals, painted wood, painted plaster, primed or painted concrete and primed metals, granite. marble, and engineered stones.

Application / Instructions


Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Bath surrounds: Half fill the bath with water to allow sealant to be applied at joint mid point. If needed, masking tape may be applied. If large gaps are to be filled, polythene foam, rod or tape should be used to provide support and reduce sealant wastage. Tool down within 5 minutes using a wet spatula or Sealant Applicator Tool. Any trims should be bedded into the silicone within 5 minutes. For sealing waste outlets in sinks and baths: silicone should be applied so that it will be in compression after tightening of connecting pipes. For metallised plastic trims: test for discoloration by sealant before use.

Features & Benefits

- Permanently Flexible
- Waterproof
- Crack Resistant
- Non Shrinking
- Mold & Mildew Resistant
- Interior Use
- 20 Year Lifespan

bond it

Available Sizes



Filysical Floperties		
Tooling Time	5-10 minutes	
Skinning Time	15 minutes	

Drying Time 1-2mm depth per day

Movement Capability

Packaging & Ordering Information			
Code	Color	Size	Barcode
SLS3CL	Clear	10 oz.	810030760313
SLS3WH	White	10 oz.	810030760306

±20%



Surface Preparation

For best results, surface should be clean, dry and structurally sound.

Limitations

Do not use on bare metal or fresh concrete without priming. Natural stone, particularly marble must be protected by primer/ sealer. Not suitable for mirrors. For fixing mirrors use Bond It MIRROR-PRO Hybrid Adhesive.

Storage & Shelf Life

Store in cool, dry conditions at a temperature between 41°F (5°C) and 77°F (25°C).

Product should be stored in the original, unopened container. Use within 24 months of date of manufacture.

Cleanup

Clean up excess wet caulk with a damp sponge before it cures.

Excess dried caulk must be cut or scraped off. Wash hands and tools with warm water and soap.

Disposal

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com