

Bond It Grab Adhesive SF is high strength, multipurpose, eco-friendly, gap-filling construction adhesive. Water-based and solvent -free with exceptional instant grab properties. Cures to give a tough, durable, permanent bond and reduces squeaks, nail pops and splitting. It has low odor and non-slumping properties; and can be painted.

### Product Use

Ideal for bonding a wide variety of building substrates both porous and non-porous. For interior use only.


### Application / Instructions

Surfaces to be bonded should be clean, dry and dust/grease-free. Carefully cut the tip of the cartridge, taking care not to damage the threaded area. Screw on the supplied nozzle and cut at an angle of 45° to the required bead width. Apply the adhesive using a standard sealant gun, to one side only. For large heavy panels, beads should be between 4-6 inches apart. Bring the components together as soon as possible pressing firmly and support for 24 hours. For non-absorbent surface, use adhesive sparingly to speed drying. Excess material can be removed with water before drying is complete.

### Features & Benefits

- Paintable
- Low VOC Content
- Interior Use
- Non-Slumping
- BONDS: brick, ceramic, metal, plastic, plaster, wood & stone

### Available Sizes



### Physical Properties

Flammability	Non-flammable
Application Temperature	35.6°F to 86°F
Service Temperature	-40°F to + 140°F
Consistency	Thick paste - gun grade
Slump	None
Shrinkage	Approx 16%
Coverage	6mm bead - 10 linear metres
Shear Strength (wood to wood)	6N/mm <sup>2</sup>

### Packaging & Ordering Information

Code	Color	Size	Barcode
SLGASF	White	10 oz.	810030760115

## Surface Preparation

For best results, surface should be clean, dry and structurally sound.

## Limitations

When using externally, in areas of high humidity, protect from water for a minimum of 12 hours. In damp and cold conditions, cure time will be significantly extended. Not for use in conjunction with bitumen or asphalt. Do not attempt to abrade when cured. Do not use around baths or shower trays. We recommend use of Bond It S3 SILICONE. Do not over paint until a surface skin has formed. Over painting is not necessary. Note: this product is flexible. Certain poor quality paints (especially certain vinyl matt)s have very little movement in the dry film. It is possible for the dry paint film to crack if movement is excessive. Should not be used in conditions of continuous water immersion, below ground level, in areas of high abrasion (eg floor joints). This product is not a silicone sealant and is not suitable for joints with very high movement.

## Storage & Shelf Life

Store in cool, dry conditions. Protect from frost. Apply at temperatures above 41°F (5°C)

Product should be stored in the original, unopened container. Use within 12 months from date of manufacture.

## Cleanup

Clean up excess wet caulk with a damp sponge before it cures. Excess dried caulk must be cut or scraped off. Wash hands and tools with warm water and soap.

## Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

## Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting [www.bonditusa.com](http://www.bonditusa.com).

## Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

## Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

*Please refer to our website at [www.bonditusa.com](http://www.bonditusa.com) for the most up-to-date Technical Data Sheets and Safety Information.*

*Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite [www.bonditusa.com](http://www.bonditusa.com)*

## Seal It Services, Inc. dba Bond It

[salesUS@bonditgroup.com](mailto:salesUS@bonditgroup.com) | [www.bonditusa.com](http://www.bonditusa.com)  
(800) 587-9940

### West

13214 Crenshaw Blvd  
Gardena, CA 90249

### East

3301 Industrial Dr  
Sanford, NC 27332