

Bond It Gripbond Pro is a one-part, high-quality, high-modulus sealing and bonding material. Forms a tough, elastic rubber joint or an adhesive with superior bonding strength. Can be painted.

### Product Use

For filling and sealing connecting joints, cracks, holes, bonding metal to metal and as a waterproof adhesive for bonding concrete, mirrors, drywall, polycarbonates, polystyrene, PVCu, plastics, ceramics, copper, lead, zinc, aluminum, stainless steel, wood, and glass. Not for use with expansion joints or where joints are regularly immersed in water. If allowed to cure in low UV light conditions this product may yellow. For internal and external use, the product is solvent-free and odorless.


### Application / Instructions

Check substrates are clean and free of dust and grease. Carefully cut the tip of the cartridge, taking care not to damage the threaded area. Cut off top of nozzle at an angle of approximately 45°. Screw on nozzle and place cartridge in a standard sealant gun. As an adhesive: apply in beads or strips and bond the surfaces together carefully and allow to cure. As a sealant: apply in a continuous bead along the aperture and allow to cure. Smooth the joint by tooling with a spray solution. Remove any excess material and clean tools immediately using white spirit. Porous substrates such as natural stone and marble must be primed prior to application. Gripbond Pro can be painted with water-based paints once dry, however as quality and type of paint can vary, always test compatibility before use.

### Features & Benefits

- Hybrid Technology
- Interior & Exterior Use
- Weatherproof
- Paintable
- Non-Shrinking
- Permanently Flexible
- Solvent-free
- Odorless
- Applicable to Wet Surfaces

### Available Sizes



### Physical Properties

Cure Time	2.5mm
Skin Time	10 min
Hardness Shore A (DIN 53505)	45+/-4
Temperature Resistance	-22°F to +203°F
Application Temperature	41°F to +104°F
Storage Temperature	41°F to +77°F

### Packaging & Ordering Information

Code	Color	Size	Barcode
SLMSPCL	Clear	10 oz.	810030760436
SLMSPWH	White	10 oz.	8100307604443

### Surface Preparation

For best results, surface should be clean, dry and structurally sound.

### Limitations

This product is not a silicone sealant. Not suitable when applied at temperatures below 40°F, used in joints constantly immersed in water, used in contact with asphaltic products, or used in areas of high abrasion (e.g., floor joints). For interior use only. Each user is solely responsible for evaluating and making their own determination as to fitness of use in their particular application.

### Storage & Shelf Life

Keep in a cool, dry area between 41°F

Product should be stored in the original, unopened container. Use within 9 months of date of manufacture.

### Cleanup

Remove any excess material and clean tools immediately with white spirit. Replace plastic cap after use.

### Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

### Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting [www.bonditusa.com](http://www.bonditusa.com).

### Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

### Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

*Please refer to our website at [www.bonditusa.com](http://www.bonditusa.com) for the most up-to-date Technical Data Sheets and Safety Information.*

*Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite [www.bonditusa.com](http://www.bonditusa.com)*

### Seal It Services, Inc. dba Bond It

[salesUS@bonditgroup.com](mailto:salesUS@bonditgroup.com) | [www.bonditusa.com](http://www.bonditusa.com)  
(800) 587-9940

#### West

13214 Crenshaw Blvd  
Gardena, CA 90249

#### East

3301 Industrial Dr  
Sanford, NC 27332