



Technical Data Sheet



Bond It Gutter & Roof is a polymerically reinforced lap jointing sealant used to prevent leaks in gutters and downspouts. It can be used for small repairs on flat and shingle roofs. Forms a flexible seal capable of accommodating 5% movement.

Product Use

For repairing and maintaining general roofing drainage systems and cracked or damaged downspouts, sidings and for pointing around roofing applications. Ideal for use on aluminum/metal, lead, construction-grade plastics, cladding panels, paint, stone, brick, bitumen's and asphalt, concrete, mortar, rubber, and wood.

Application / Instructions

Surfaces must be clean, dry and dust/grease-free. Remove all existing sealant. When sealing deep joints use foam backer rods to minimize wastage. Cut the tip of the cartridge without damaging the threaded area. Screw on nozzle and cut at an angle of 45° to an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun and tool down within 10 minutes of application using the appropriate tool. Clean tools with mineral spirits before the product dries.

Features & Benefits

- · Permanently Flexible
- Excellent Adhesion
- Waterproof
- Weatherproof
- Non-shrinking
- · Mold & Mildew Resistant
- 10 Year Lifespan
- Meets ASTM C834

Available Sizes





Physical Properties

Flammability	Flammable
Solubility in Water	Insoluble
Adhesion	Good to metals and plastics
Movement Value	5%

Packaging & Ordering Information			
Code	Color	Size	Barcode
SLGRBL	Black	10 oz.	810030760252



Surface Preparation

For best results, surface should be clean, dry and structurally sound.

Limitations

For emergency repairs in wet conditions Bond It RAIN-MATE should be used. ROOF & GUTTER MATE maintains a permanently putty-like consistency. It is not suitable for applications where surface contact is likely.

Storage & Shelf Life

Store in cool, dry conditions.

Product should be stored in the original, unopened container. Use within 24 months of date of manufacture.

Cleanup

Clean up excess wet caulk with a damp sponge before it cures. Excess dried caulk must cut or scraped off. Wash hands and tools with warm water and soap.

Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com