

Bond It Gutter & Roof Plus is a premium grade, neutral cure roofing silicone that is compatible with lead and most common building materials. Remains permanently flexible and is tough enough to stand up to the harshest of weather conditions.

Product Use

For use on all types of roofing, roof vents, soffits, downspouts, siding, and gutters and as a lap jointing sealant. Good adhesion to acrylic, glass, GRP and polycarbonate glazing, aluminum, copper, lead, PVCu, steel, timber, industrial roofing panels, slate, and tiles. Also suitable for internal use for sub-roof ducting and for sealing roof lights, mechanical fasteners, and clogging, as well as HVAC and solar energy system installations.


Application / Instructions

Surfaces must be clean, dry and dust/grease free. When sealing deep joints, use foam backer rods to reduce wastage. Prime porous materials prior to use. Cut the tip of the cartridge without damaging the threaded area. Screw on the nozzle and cut at an angle of 45° to an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun and tool down after 2-3 minutes using the appropriate tool. This silicone will stretch up to at least 25%. When using as an adhesive, ensure materials are bedded firmly into position. After use, clean tools with mineral spirits before product dries.

Features & Benefits

- Fast Skinning
- Weatherproof
- Interior & Exterior Use
- Permanently Flexible
- UV, Heat & Ozone Resistant

Available Sizes



Physical Properties

Flammability	Non-flammable
Solubility in Water	Insoluble
Tooling Time	5-10 minutes
Skinning Time	15-25 minutes
Rate Of Cure	1-2mm per day
Joint Movement Capability	25% by ISO methods
Application Temperature	41°F to + 86°F
Service Temperature	-58°F to + 248°F

Packaging & Ordering Information

Code	Color	Size	Barcode
SLLEAD	Gray	10 oz.	810030760320

Surface Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. Priming may be necessary on porous surfaces.

Limitations

Porous surfaces should be primed first. Do not use on surfaces where water can penetrate through porous materials to the bond interface without first carrying out remedial work. Not suitable for use on natural stone.

Storage & Shelf Life

Store in cool, dry conditions at a temperature between 41°F (5°C) and 77°F (25°C).

Product should be stored in the original, unopened container. Use within 12 months from date of manufacture.

Cleanup

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com

Seal It Services, Inc. dba Bond It

salesUS@bonditgroup.com | www.bonditusa.com
(800) 587-9940

West

13214 Crenshaw Blvd
Gardena, CA 90249

East

3301 Industrial Dr
Sanford, NC 27332