

Bond It Painter's Caulk is a quick-drying interior acrylic latex caulk that can be smoothed and painted within 1-2 hours. Good adhesion to most surfaces and moderate flexibility to prevent cracks. Easy water clean-up.

Product Use

For filling gaps and cracks in most common building materials including plaster, brick, concrete, wood, and drywall with low movement, such as baseboards, crown molding, ceilings, light fixtures, shelves, and built-in furniture. Applies and finishes smoothly and easily. For interior use only.


Application / Instructions

Surfaces must be clean, dry and dust/grease free. Remove all existing sealant. Cut the tip of the cartridge without damaging the threaded area. Screw on the nozzle and cut at an angle of 45° to an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun and tool down within 10 minutes of application (before the sealant starts to skin) using the appropriate tool. Can be painted with emulsion paint as soon as skin forms (approx. 1 hour). For oil-based paints allow 24-48 hours before painting. Clean tools with soapy water after use.

Features & Benefits

- Quick Drying
- Paintable in 1 hour
- Easy to apply and finish
- Easy water clean-up
- 25 Year Lifespan
- Meets ASTM C834

Available Sizes



Physical Properties

Cure Time	Tools within 5 min
Skin Time	20 min
Full Cure	24 hrs
Wait Time before Painting	1 hr
Sag	0%, None
Movement Accommodation	7%, Moderate

Packaging & Ordering Information

Code	Color	Size	Barcode
SLPCWH	White	10 oz.	810030760276

Surface Preparation

For best results, surface should be clean, dry and structurally sound.

Limitations

This product is not a silicone sealant. Not suitable when applied at temperatures below 40 F, used in joints constantly immersed in water, used in contact with asphaltic products, or used in areas of high abrasion (e.g., floor joints). For interior use only. Each user is solely responsible for evaluating and making their own determination as to fitness of use in their particular application.

Storage & Shelf Life

Store in cool, dry conditions, protect from extreme heat or extreme cold. Product should be stored in the original, unopened container. Use within 24 months of date of manufacture.

Cleanup

Clean up excess wet caulk with a damp sponge before it cures. Excess dried caulk must be cut or scraped off. Wash hands and tools with warm water and soap.

Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com

Seal It Services, Inc. dba Bond It

salesUS@bonditgroup.com | www.bonditusa.com
(800) 587-9940

West

13214 Crenshaw Blvd
Gardena, CA 90249

East

3301 Industrial Dr
Sanford, NC 27332