

Bond It Power Pro is the ultimate grab adhesive for a long-lasting bond. Power Pro typically has double the initial grab of other adhesives and is rapid-curing, omitting the need for mechanical support in most common applications, even on ceilings.

Product Use

Superb adhesion even on wet surfaces, Power Pro is suitable for all weather conditions. Fast-curing, isocyanate, solvent, and acid-free; it's ideal for use with metal, wood, glass, stone, insulation board ceramics, plastics, Plexiglas, Lexan, polyester, MDF, OSB, chipboard, and wood paneling. It can be painted, applied to wet surfaces, and has a usual bond strength of 50 PSF; for interior and exterior use.


Application / Instructions

Check substrates are clean and free from dirt and dust. Carefully cut the tip of the cartridge, without damaging the threaded area. Screw on the notched nozzle attached and use a standard sealant gun. Apply in beads or strips to one surface only, bond the surfaces together carefully and allow to cure. Remove uncured adhesive with white spirit. Note: this product is not recommended for installations where joints are permanently immersed in water or on surfaces that bleed oils or plasticizers. If used on overhead applications, always use in conjunction with mechanical fixings. For large and/or heavy items, provide temporary support (eg. tape) until full cure is achieved.

Features & Benefits

- Hybrid Technology
- Interior & Exterior Use
- Weather Proof
- Can Be Painted Over
- Non Shrinking
- Quick Curing
- Solvent-Free
- Odorless
- Applicable to Wet Surfaces

Available Sizes



Physical Properties

Curing in 24 hours	2.5mm
Bond Strength	250Kg/m ²
Shrinkage	0
Skinning Time	approx 10 minutes
Shore A Hardness (DIN 53505)	40+/-4
Temperature Resistance	-22°F to +203°F
Application Temperature	41°F to +104°F
Storage Temperature	41°F to +77°F
Elongation To Break	60%
Density	1.5
Tensile Strength	275.6 PSI
UFI	6030-10UD-K008-7VHD

Packaging & Ordering Information

Code	Color	Size	Barcode
SLGBMWH	White	10 oz.	810030760481

Surface Preparation

For best results, surface should be clean, dry and structurally sound.

Limitations

Not suitable for use on polypropylene or Teflon. Paintable, however, always test compatibility in an inconspicuous area before application. Natural stone can vary, so always test for staining before use. Yellowing can occur in predominantly dark conditions.

Storage & Shelf Life

Store in cool, dry conditions between 41°F (5°C) and 77°F (25°C).

Product should be stored in the original, unopened container. Use within 9 months of date of manufacture.

Cleanup

Clean up excess wet caulk with a damp sponge before it cures. Excess dried caulk must be cut or scraped off. Wash hands and tools with warm water and soap.

Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com

Seal It Services, Inc. dba Bond It

salesUS@bonditgroup.com | www.bonditusa.com
(800) 587-9940

West

13214 Crenshaw Blvd
Gardena, CA 90249

East

3301 Industrial Dr
Sanford, NC 27332