

Water Based Sealant

Technical Data Sheet



Bond It Window & Door is a high-quality, water-resistant, water-based frame sealant with excellent adhesion to most building materials. A flexible joint filler that can be painted, stained or varnished for color matching purposes. Easy water clean-up.

Product Use

For sealing window and door frames or soffit boards with limited movement. Suitable for use with brick, stone, concrete, wood, pressboard, aluminum and preformed panels. Ideal for sealing, waterproofing and draught-proofing applications.


Application / Instructions

Surfaces must be clean, dry and dust or grease-free. Remove all existing sealant. Cut the tip of the cartridge without damaging the threaded area. Screw on the nozzle and cut at an angle of 45° to an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun and tool down within 10 minutes of application (before the sealant starts to skin) using the appropriate tool. Can be painted with water-based paint as soon as skin forms (approx. 1 hour). For oil-based paints, allow 24-48 hours before painting. Clean tools with soapy water after use.

Features & Benefits

- Permanently Flexible
- Excellent Adhesion
- Water Resistant
- Weatherproof
- Durability
- Mildew Resistant
- 25 Year Lifespan
- Paintable
- Easy Water Cleanup
- Meets ASTM C834

Available Sizes





Physical Properties	
Tooling Time	Tool within 5 minutes
Skinning Time at 68°F	After 20 minutes
Full Cure Time	24 hours
Movement Value	12.5%
Wait Time before Painting	1-24hrs
Sag	None
UV and Weather Resistance	Good
Water Resistance	Good
Polluted Environments	Good

Packaging & Ordering Information			
Code	Color	Size	Barcode
SLFMWH	White	10 oz.	810030760269



Surface Preparation

For best results, surface should be clean, dry and structurally sound.

Limitations

This product is not a silicone sealant! Not suitable when:

- applied externally during rainy weather.
- applied at temperatures below 41°F (+5°C).
- used in joints constantly immersed in water.
- used in contact with bituminous products.
- used in areas of high abrasion, e.g. floor joints.
- for use with plastic baths use a sealant with greater flexibility.

Storage & Shelf Life

Store in cool, dry conditions. Protect from frost.

Product should be stored in the original, unopened container. Use within 24 months of date of manufacture.

Cleanup

Use Bond It WHITE SPIRIT or MULTI-WIPES.

Disposal

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

Safety

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting www.bonditusa.com.

Warranty

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

Disclaimer

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

Please refer to our website at www.bonditusa.com for the most up-to-date Technical Data Sheets and Safety Information.

Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite www.bonditusa.com