

Bond It Wood Pro is a permanently flexible, one-part, ready to use interior wood flooring adhesive. Moisture cure and free from silicone, solvent, isocyanates, and water.

### Product Use

Wood Pro is moisture and solvent-free and so reduces the risk of warping or deforming wood flooring. Ideal for the internal bonding of parquet, mosaic, oak, woodblock, laminated, exotic hard and softwoods, and many other wood floor types to porous or non-porous substrates such as concrete, screeds, chipboard, plywood, and anhydrite. For interior use, Wood Pro is permanently elastic, quick-curing and produces a rapid bond strength. Also compatible with under-floor heating systems.


### Application / Instructions

Loose or cracked areas should be repaired before application. Installations and subfloor preparations must be carried out in line with manufacturer recommendations. Ensure that moisture content does not exceed that recommended by the flooring recommendation. Note: Underfloor heating systems should be turned off 48 hours before and 48 hours after application. Application temperature should be between 50°F (10°C) and 86°F (30°C), materials should be acclimatized to ambient temperature on site prior to installation.

### Features & Benefits

- Hybrid Technology
- Gap-Filling
- Non-Shrinking
- Permanently Flexible
- Solvent-Free
- Odorless
- Works with underfloor heating

### Available Sizes



### Physical Properties

Density	1.49g/cc
Open Time	20 minutes
Shore A Hardness	40 +/- 5
Tensile Strength	290 PSI

### Packaging & Ordering Information

Code	Color	Size	Barcode
SLWPROTN	TAN	10 oz.	810030760498

**Surface Preparation**

All surfaces must be clean, dry and free from grease, polish, old adhesive or contaminants that may hinder adhesion.

**Limitations**

WOOD PRO will take at least 24 hours to cure assuming a temperature of 73.4°F at 50% RH. Cooler and / or less humid conditions will extend drying times. Wait until the adhesive has fully cured before sanding or finishing the flooring. Depending upon substrate condition and porosity the approximate coverage rates will be approximately 1m<sup>2</sup> per cartridge.

**Storage & Shelf Life**

Store in cool, dry conditions between 41°F (5°C) and 77°F (25°C).  
Product should be stored in the original, unopened container. Use within 12 months of date of manufacture.

**Cleanup**

Uncured WOOD PRO can be removed using Bond It WHITE SPIRIT. Cured adhesive must be removed mechanically.

**Disposal**

Empty containers must be disposed of in accordance with local, state, and federal regulations. Do not leave empty or partially used containers where residue could be harmful to children, animals, or the environment.

**Safety**

KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Wear skin and eye protection. In case of contact with eyes, flush eyes with water. Wash hands thoroughly after use. For emergencies, contact your local poison center. Refer to Safety Data Sheet (SDS) for complete information, available from your supplier or by visiting [www.bonditusa.com](http://www.bonditusa.com).

**Warranty**

Manufacturer warrants the product to be free of defects in material and performance when used as directed for one year from date of purchase. Call (877) 587-9940 with your sales receipt and product container available for replacement product or sales price refund. Manufacturer nor reseller will be held liable for incidental or consequential damages.

**Disclaimer**

All values presented in this document are approximate and subject to change without notice. Product is provided without warranty, expressed or implied, of fitness for any specific purpose. Because conditions and usage are beyond the manufacturer's control, neither manufacturer nor seller will assume responsibility for the use or misuse of this product. Each user is solely responsible and liable for making its own determination as to the suitability of this product for its own particular use and application. We assume no responsibility for coverage, performance or injuries resulting from the use of this product. Liability, if any, is limited to replacement cost of product.

*Please refer to our website at [www.bonditusa.com](http://www.bonditusa.com) for the most up-to-date Technical Data Sheets and Safety Information.*

*Para obtener instrucciones o garantía en español, llame al (800) 587-9940 o visite [www.bonditusa.com](http://www.bonditusa.com)*

**Seal It Services, Inc. dba Bond It**

[salesUS@bonditgroup.com](mailto:salesUS@bonditgroup.com) | [www.bonditusa.com](http://www.bonditusa.com)  
(800) 587-9940

**West**

13214 Crenshaw Blvd  
Gardena, CA 90249

**East**

3301 Industrial Dr  
Sanford, NC 27332