ALPINE SERIES



DISCONTINUED

PLEASE NOTE: The Alpine has now been replaced by our Trimax Fixture. For more information, click here

Description

The **Alpine** series is a high performance low profile LED flood light designed for a wide variety of applications and mounting heights. Multiple optics and color temperature options make the Alpine ideal for exterior area lighting, retail, sports fields and ski hills.

Extruded aluminum heat sinks with driver thermally isolated from the LEDs. Edge-to-edge high impact glass lens with no bezel prevents dirt and ice build-up on the optics.

Lumileds or Cree LED chips. Optics can deliver light up to 7 times the mounting height uniformly from the pole to the target. Low profile, wide optic design ensures minimal exposure to the elements. Visor protects the optics and redirects potentially wasted light back to the target plane, minimizing sky glow and blocking unwanted glare. Unique optic venting system allows air to flow freely in and out of the optics while blocking water, condensation and contaminants. Optics stay clean, efficient and long lasting.

Moons driver is rear mounted and easily accessible for maintenance. 100-277V or 347-480V operation. 0-10V dimming standard. Suitable for operation in -40°C to +50°C (-40°F to 122°F) ambient environments.

Alpine EPA

Front = 1.3427 ft2; Side = 0.3197 ft2; Top = 1.2206 ft2;

Certifications and Warranty

cETLus and DLC with 3 year warranty



120-277V 347-480V





ALPINE 200W

Product Information 200W

Installation: Yoke
Material: Extruded Aluminum

Finish: Powder coat

 System power (W):
 200

 Fixture lumen output (Im):
 24000

 System efficiency (Im/W):
 120

LED engine: Lumileds/Cree

Packaging

 Net weight lamp (kg/lb):
 14.80 / 24.29

 Gross weight carton (kg/lb):
 16.00 / 35.27


Master carton dimensions (mm/in): 732x297x315 / 28.8x11.7x12.4


Quantity per carton:

Code composition


Series		Model		Mounting		Wattage-Lun	Optics			
FL	Flood Light	ALP	Alpine	YK	Yoke	200W-240L	200W-24000lm	6X3	6x3D	







CCT	CT CRI		Voltage		Dimming		Finish		Accessories		
30K	3000K	70	70+	UNV	120-277V	D	0-10V	вк	Black	NA	No Accessories
40K	4000K		(Standard)	CHV	347-480V		Dimming	GR	Grey	VS	Visor
50K	5000K	80	80+							SPD	SPD



200W-6X3D-3000K-CRI70

