

LUNA1

WATTAGE SELECTABLE



Description

The **Luna1** is a **WATTAGE SELECTABLE** LED post top fixture. It provides a great outdoor lighting solution for a variety of applications, such as schools, streets, gardens, yards, and commercial areas. The Luna 1 is designed to provide efficient, long-lasting lighting with an ultra-thin, aesthetically pleasing design, and an IP66 rating ensures that the LED light is protected against dust and moisture, making it ideal for use in areas where water resistance is essential.

Features

Wattage selectable options include 30/40/50W and 100/120/150W, with CCT options for 3000K / 4000K / 5000K / 5700K.
 IP Rating: IP66
 IK Rating: IK08
 Beam Angle: 90° / 120° / T2 / T3 / T4 / T5(140x140°)
 Arm Diameter: 60 - 80mm / 2.4 - 3.1"
 EPA: 0.528
 T2/T3 BUG: B4-U1-G4
 T5 BUG: B3-U0-G2


Electrical Specifications

Wattage Selectable Options: 30/40/50W | 100/120/150W
 CCT: 3000K / 4000K / 5000K / 5700K
 Efficacy: 140-160 LM/W
 CRI: >70Ra
 Power Factor: >0.9
 0-10V Dimming
 Surge Protection: 10KV / 20KV (Optional)
 Operating Temperature: -40 ~ 55° C / -40 ~ 131°F
 Available Voltages: 120-347VAC (CUNV)
 6KVA Surge Protection Standard

Certifications and Warranty

DLC Premium, ETL listed, and CE with 5 year warranty

Wattage Selectable



LUNA1


WATTAGE SELECTABLE



Product Information	50WS (Selectable)	150WS (Selectable)
Installation:	Slip Fitter (Standard)	
Material:	Die-cast aluminum	
Finish:	Powder coat	
System power (W):	30/40/50W	100/120/150W
Fixture lumen output (lm):	4800/6400/8000	14000/16800/21000
System efficiency (lm/W):	160	140
LED driver:	Becky	
LED engine:	Lumiled 2835	


Packaging

New weight lamp (kg/lb):	
Gross weight carton (kg/lb):	8 / 17.64
Master carton dimensions (mm/in):	540 x 480 x 200 / 21.26 x 18.9 x 7.87
Quantity per carton:	1







Code composition

Series	Model	Mounting	Wattage-Lumens	Beam Angle
DPT	Decorative Luna 1 Post Top	SF	Slip Fitter (for 3" Tenon)	90 90 Degrees 120 120 Degrees T2 Type 2 T3 Type 3 T4 Type 4 T5 Type 5
			50WS-80L 50WS-8000lm 150WS-210L 150WS-21000lm	



CCT	CRI	Voltage	Dimming	Finish	Accessories
30K 3000K 40K 4000K 50K 5000K 57K 5700K	70 Ra70	CUNV 120-347V	D 0-10V Dimming	BK Black	NA No Accessories SPD20 20KV Surge Protection Device





LUNA1 WATTAGE SELECTABLE

Accessories

Surge Protection Device 10KV / 20KV



Dimensions



430.0±0.0 (16.93in)

78.0±0.0 (3.07in)

