

MINI 2

(WATTAGE & CCT SELECTABLE)



Description

The **Mini 2 wall pack** is low profile, light weight, and designed for long life usage with no maintenance and great performance. This wall pack features 3 CCT and Wattage Selectable technology, and is designed to quickly and easily upgrade traditional wall mount fixtures.

The housing is made of aluminum and PC materials for outdoor applications.

Available finishes are Dark Bronze (RAL 8019 Standard) Black is also available.

Cover is a frosted striped lens for a modern design. Photocell included.

Electrical Specifications

Available Wattages: 25W Selectable
(select between 25W, 18.75W, 12.5W)

CCT Selectable: 3000K / 4000K / 5000K

Efficacy: 120 LM/W

Lumen Maintenance (hrs): >50,000 hours

CRI: >70Ra

Power Factor: ≥ 0.90

IP Rating: IP54

0-10V Dimming

Operating Temperature: -30°C to 45°C / -22°F to 113°F

Available Voltages: 120-277VAC (UNV)

Certifications and Warranty

cETL and DLC with 6 year warranty

MINI 2

25W Wattage and CCT Selectable



Product Information	25W Selectable
Installation:	Wall mounted
Material:	Die-cast aluminum
Finish:	Powder coat
System power (W):	25W (100%) / 18.75W (75%) / 12.5W (50%)
Fixture lumen output (lm):	3000 (100%) / 2250 (75%) / 1500 (50%)
System efficiency (lm/W):	120
LED driver:	
LED engine:	

Packaging	
New weight lamp (kg/lb):	0.85 / 1.87
Gross weight carton (kg/lb):	7.4 / 16.31
Master carton dimensions (mm/in):	415 x 300 x 235 / 16.34 x 11.81 x 9.25
Quantity per carton:	8

Code composition

Series	Model	Mounting	Wattage-Lumens	Optics
WP Wall Pack	MIN2 Mini 2	WM Wall Mount	25WS-30L 25WS-3000lm	140x38 140x38°

CCT	CRI	Voltage	Dimming	Finish	Accessories
CCTS 3000K / 4000K / 5000K Selectable	70 70+	UNV 120-277V	D 0-10V Dimming	DB Dark Bronze (Standard) BK Black	PC Photocell (Standard)

