

## SUPERIOR GEN 3 SERIES

### CCT SELECTABLE AND WATTAGE SELECTABLE

150 LM/W



#### Description

The **Superior Area Light Gen 3 (SAL3)** is a sleek and modern high-performance, low profile LED area light. The product range has been upgraded to reach higher efficiency up to 150lm/W. It has been designed to handle any environment. It has a beautiful slim line design along with one of the highest lumen packages on the market today. This versatile fixture can be used as a flood light or an area light. It includes a multitude of mounting options, surge protection devices, photocell and occupancy sensor capabilities, and the most technologically advanced LED's on the market. The SAL 3 is ready to dominate the lighting area landscape. 0-10V dimming standard.

#### Features

The uniform PC lens is easy to maintain and replace. The integrated cooling fins provides excellent thermal dissipation. This superior design allows the fixture to have extremely long life hours. SAL 3 is IP66 rated, operates at -40 to 55 degrees Celsius (-40 to 131 degrees Fahrenheit).

#### Electrical Specifications

LED Type: Philips Lumileds 3030

Available Wattages:

100W Selectable: 50/75/100W

200W Selectable: 100/150/200W

CCT Selectable: 3000K/4000K/5000K

Available Voltages: 100-347Vac

Lumen Maintenance @L70: >100,000 hours

CRI: >70

THD: <15 %; Power Factor: >0.95

Surge Protection: 6kVA

Ambient Temperature: -40 to 55° C / -40 to 131°F

IP Rating: IP66/Wet Location

Standard finish: RAL8019 Dark Bronze

The length of the standard cord is 1m/3ft.

A Zhaga socket for either photocell or Occupancy sensor is included.

#### Available Wattages



#### Certifications and Warranty

ETL, cETL, DLC with 6 year warranty

**LuxLogic Inc reserves the right to accept and/or cancel orders without notice at its discretion.**