

4.ONL
3647
1747R opt.
1747G opt.
1747P opt.

3771
3771A opt.
3776A opt.
5576R opt.

3654

3186
3x12WM

3139
62MM

3186
3x12WM

1834

1914

3x10WST

1834

1914

3x10WST

2362

F-2458A
2458P opt.
R-3757X
3757P opt.

8361
8361

1765
E
3768
E

Limter,
Rear only

F-1664
1664T opt.

R-2656
2656T opt.

F-3765A
R-3766A

3768
3769

Use #1666 silicone
shock oil

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3288
3x15WST

3642
3x12x5SS

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3186
3x12WM

2742

2537
28MM
Threaded rod

2675
3x10RST

3290
3x8WST

3768

2362

1942
2742X

2649
3x12CST



2530A
(Shown for Clarity)

1985
5x8x0.5TW

3736
3636X opt.
3636A opt.
3636G opt.
3636P opt.

2754

3642
3x12x5SS

3641A
69MM

3631
3631A opt.
3631G opt.
3631L opt.
3631R opt.
3631T opt.
3631X opt.

3639

3288
3x15WST

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3187
3x15WM

2742

2056
2075 opt.

3290
3x8WST

1942
2742X

2649
3x12CST

1675
5x11x40B
5116 opt.

3637

2746
3x6MW

3632
3632A opt.
3632X opt.
3632G opt.
3632P opt.

3740
31.5MM

3739
24MM

3631
3631A opt.
3631G opt.
3631L opt.
3631R opt.
3631T opt.
3631X opt.

3639

3288
3x15WST

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3290
3x8WST

2056
2075 opt.

3290
3x8WST

1942
2742X

2649
3x12CST

2563
3x15RM

3637

2746
3x6MW

3632
3632A opt.
3632X opt.
3632G opt.
3632P opt.

3740
31.5MM

3739
24MM

3631
3631A opt.
3631G opt.
3631L opt.
3631R opt.
3631T opt.
3631X opt.

3639

3288
3x15WST

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3290
3x8WST

2056
2075 opt.

3290
3x8WST

1942
2742X

2649
3x12CST

2735
2735P

2548
4x12CM

3739
24MM

2530A
2530 opt.

3631
3631A opt.
3631G opt.
3631L opt.
3631R opt.
3631T opt.
3631X opt.

3639

3288
3x15WST

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3290
3x8WST

2056
2075 opt.

3290
3x8WST

1985
5x8x0.5TW

3723A
3723 opt.

2545
5x8x2.5PB
5114 opt.

3743
3743X opt.
3743A opt.
3743P opt.
6845X opt.

3167
4x15CM

2548
4x12CM

3739
24MM

2530A
2530 opt.

3631
3631A opt.
3631G opt.
3631L opt.
3631R opt.
3631T opt.
3631X opt.

3639

3288
3x15WST

2593
3x14 BCS

8361

3760A
2660 opt.

2742

3290
3x8WST

2056
2075 opt.

3290
3x8WST

1985
5x8x0.5TW

3723A
3723 opt.

2545
5x8x2.5PB
5114 opt.

3743
3743X opt.
3743A opt.
3743P opt.
6845X opt.

3167
4x15CM

3654

2742

3186
3x12WM

3740
31.5MM

1675
5x11x40B
5116 opt.

1985
5x8x0.5TW

3742
3x30
SS

2746
3x6MW

2545
5x8x2.5PB
5114 opt.

3743
3743X opt.
3743A opt.
3743P opt.
6845X opt.

3186
3x12WM

2742

3186
3x12WM

2742

2548
4x12CM

3722R
3722X opt.



5576
5576A opt.
3673 opt.
3675 opt.



5563



5563
5578 opt.

4.ONL
3647
1747R opt.
1747G opt.
1747P opt.

See Parts List for a complete
listing of optional accessories.



REV 200116-R04
Specifications on this page are subject to change without notice. Every attempt has been made to ensure the accuracy of this drawing; however, Traxxas cannot be held responsible for typographical or other errors.

Front Assembly

