

T-Maxx (Model 49077-3) Parts List

	Air Filters	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4 axles (2)/ rubber tires (2)
5262	Air filter and pre-filter inserts, foam (high-volume) (3) (pre-oiled, assembled) (TRX 2.5, 2.5R, 3.3)	5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4). axles (2)/ rubber tires (2)
5267	Air filter body (high-volume)/ filter support/ cap/ foam filter, pre-filter/ T-Maxx® filter base (angled)/ wire mount/ hardware (1 each) (Fits		Chassis & Attachments
	Maxx® trucks) (TRX® 2.5, 2.5R, 3.3)	3170X	Battery holder, 4-cell/ on-off switch
263	Oil, air filter Bearings & Bushings	4925X	Box, battery (grey)/ adhesive foam chassis pad/charge jack plug (rubber)
044		5159	Box, receiver (upper and lower halves)/ clip (1)/ foam pad
611 728	Ball bearings (5x11x4mm) (2)	4963	Chassis braces, lower (black) (for long wheelbase chassis) (2)
119	Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)	5122X	Chassis, T-Maxx®, long wheelbase (extended 30mm) (6061-T6
116	Ball bearings, blue rubber sealed (10x15x4mm) (2)		aluminum, 4.0mm) (blue anodized)
114	Ball bearings, blue rubber sealed (5x11x4riiii) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	5167	Slide carb linkage bellcrank post/ 5x8x2.5 plastic bushing (2)/
117	Ball bearings, blue rubber sealed (5x6x2.3mm) (2)	=40=	bellcrank/ 5x8x0.5 fiber washer (2)/ 3x10 WM
180	Ball bearings, blue rubber sealed (6x13x5mm) (2)	5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)
118	Ball bearings, blue rubber sealed (8x16x5mm) (2)	4974 4977	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)
545	Bellcrank bushings (plastic) (5x8x2.5mm) (4)	4977 4975	Wheelie bar mount (1) Wheelie bar, assembled (fits all T-Maxx® and E-Maxx® trucks)
		4976	Wheels (4)/ axles (2), for Maxx® wheelie bar
	Body & Accessories	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4
926	Antenna caps, vinyl (2)/ antenna spool	3100A	axles (2)/ rubber tires (2)
526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools	5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4).
526R	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools		axles (2)/ rubber tires (2)
726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)		Clutch & Related Parts
170X	Battery holder, 4-cell/ on-off switch		
935	Body clip (mounting clip), angled, 90-degrees (10)	4611	Ball bearings (5x11x4mm) (2)
935A	Body clip (mounting clip), angled, 90-degrees (black) (10)	4120	Clutch bell, (20-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip
834	Body clips (12) (standard size)	4400	(requires #4611-ball bearings, 5x11x4mm (2)
934	Body clips, heavy duty (12)	4122	Clutch bell, (22-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip
914R	Body mount posts, front (2)/ body mount, rear/ body mount screw	4404	(requires #4611-ball bearings, 5x11x4mm (2))
045	pins (4)	4124	Clutch bell, (24-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip (requires #4611-ball bearings, 5x11x4mm (2))
815 915	Body washers (8)	4146X	Clutch shoes (2)/ spring (T-Maxx®/Revo®/Jato®/Nitro 4-Tec®)
915 921	Body washers, foam adhesive (10) Body, T-Maxx® (long wheelbase) (clear, requires painting)/	3281	Cone, split beveled
32 I	window, lights decal sheet	1633	E-clips/ C-rings
921X	Body, T-Maxx®, ProGraphix® (long wheelbase) (replacement for	6542X	Flywheel (large, knurled for use with starter boxes)
0217	painted body. Graphics are painted, requires paint and final	5244	Flywheel nut (TRX® 2.5, 2.5R, 3.3)
	color application)/ window, grille, lights decal sheet	6542	Flywheel with magnet (35mm)
2514	Decal sheet, racing sponsors	1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)
920X	Decal sheets, T-Maxx® 3.3 (long wheelbase) (model 4908)		Differential Components
950	Official Team Traxxas® racing decal set (flag logo/ 6-color)		
185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
974	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
977	Wheelie bar mount (1)	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
975	Wheelie bar, assembled (fits all T-Maxx® and E-Maxx® trucks)	5381 5136X	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 T
976	Wheels (4)/ axles (2), for Maxx® wheelie bar	5382X	Differential oil kit (1 each: 10K, 30K, 50K weights)
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)		Gear set, differential (output gears (2)/ spider gears (2)/ spider gear shaft/ diff carrier support)
186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/	3979 5130	Housings, differential (left & right)/ pinion collar (1) Oil, differential (100K weight) (.7 oz (20cc))
	axles (2)/ rubber tires (2)		Oil, differential (100K weight) (.7 62 (2000))
	Brake Components	5135 5136	Oil, differential (30K weight)
966	Brake adapter, hex aluminum (blue)	5039	Oil, differential (50K weight)
967	Brake cam (blue)/ cam lever/ 3mm set screw	5137	Oil, differential (500K weight)
364	Brake disc (40mm steel)	5379X	Ring gear, differential/ pinion gear, differential
364X	Brake disc (high performance, vented)	5379R	Ring gear, differential/ pinion gear, differential (machined, spir
365	Brake pad set (inner and outer calipers with bonded friction material)	337310	cut) (front)
978	Screws, 3x21mm button-head machine (hex drive) (partially threaded,	3965	Screws, 2.5x8mm cap-head machine (6)
	Revo brake bolts) (6)	0000	
	Bumpers & Skidplates		Driveline Components
000		5334	Axle carriers, left & right (1 each)
930 936	Bulkhead cross braces (2)/ 3x25mm CS screws (8) Bumper mounts, front (l&r)/ bumper mounts, rear (l&r)/ 3x12mm RHM	5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm bal bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ du
935X	screws (8) Rumpers 6061-T6 brushed aluminum (f&r)	E 4 5 0	boot retainers (4)
935 935	Bumpers, 6061-T6, brushed aluminum (f&r) Bumpers, satin finished (f&r)	5459 545 3	Boots, driveshaft (rubber) (2)
579	Screws, 3x15mm button-head machine (hex drive) (6)	5153	Drive cups, inner (2) Revo®/Maxx® (steel constant-velocity driveshafts)/screw pin, M4/15 (2)
937	Skidplate, front plastic/ stainless steel plate (black)	5451X	Driveshaft assembly (1), left or right (fully assembled, ready to inst
937A	Skidplate, front plastic (grey)/ stainless steel plate	070 IA	4x15mm screw pin (1)
937A	Skidplate, rear plastic/ stainless steel plate (black)	5154	Driveshaft, steel constant-velocity, Revo®/Maxx® (shaft only,
938A	Skidplate, rear plastic (grey)/ stainless steel plate	0.07	128.5mm)/ drive cup pin (1)
~~~	Skidplate, transmission, nylon (grey) (for long wheelbase chassis)	5451R	Driveshafts, Revo®/Maxx® (steel constant-velocity) (assemble
	, , , , , , , , , , , , , , , , , , , ,		w/inner & outer dust boots) (for models w/sealed pivot ball
969			suspension & 3.8" wheels) (4)
969 <b>185</b>	Tires, rubber (2) (fits Traxxas® wheelie bar wheels) Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)		Suspension a c.o wheels) (4)
1969 <b>5185</b> 1974	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	5150	E-clips, 1.5mm (24)
1969 <b>5185</b> 1974 1977	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4) Wheelie bar mount (1)	5150 5456	E-clips, 1.5mm (24) Half shafts, center front (Revo 3.3) (internal splined (1)/ external
1969 5 <b>185</b> 1974 1977 1975	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)		E-clips, 1.5mm (24)

Page 2	T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxx	as Link	Wireless Module, & TSM (Model 49077-3) Parts List
4955 <b>5129</b>	Pins, axle (2.5x12mm) (4) Rebuild kit (for Revo®/Maxx® steel constant-velocity	5275	Housing set (inner, outer)/ 3x12mmBCS (5)/ 3x20BCS (1)/ motor bushing (EZ-Start® 2)
5145	driveshafts) (includes pins, dustboots, & lube for 2 driveshafts assemblies) Screw pin, 4x15mm (6)	4581 <b>4581X</b>	Lead wire, glow plug (blue) (EZ-Start® and EZ-Start® 2)  Lead wire, glow plug (blue) (EZ-Start® and EZ-Start® 2)/ molex pin extractor (use where glow plug wire does not have bullet
5189	Screw pins, 4x13mm (with threadlock) (4)		connector)
5454	Stub axle (steel) (2)	5279	Motor (hi-torque)/ pinion gear/ motor bushing (EZ Start 2)
5166	Stub axle, (1)/ axle sleeve (1) Revo®/Maxx® (steel constant- velocity driveshaft)	5211R	Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3)
5452	U-joints, driveshaft (carrier (4)/ 4.5mm cross pin (4)/ 3mm cross pin (4)/ e-clips (20)) (metal parts for 2 driveshafts)	5169 5282	Screws, 2.6x8mm countersunk machine (6) Screws, 3.72mm button-head machine (6) (starter attachment screws
4954 <b>4954R</b>	Wheel hubs, hex (2)/ axle pins (2.5x12mm) (2) Wheel hubs, hex (steel)	2578	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6)
4954X 4954X	Wheel hubs, hex, (steer) Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins (2.5x10mm) (4)	5277	Shaft, starter (TRX® 2.5, 2.5R, 3.3)
5353X	Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts,	4934X	Front Suspension & Steering Aluminum caps, pivot ball (blue-anodized) (4)
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)	5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust
5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts, splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with	0700	boot retainers (4)
5050D	threadlock) (4)	<b>2728</b> 4944	Ball bearings (5x8x2.5mm) (2) Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts, splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with		long rod ends (2)
5050	threadlock) (4)	3930 4930R	Bulkhead cross braces (2)/ 3x25mm CS screws (8) Bulkheads (I & r) (front) (grey)
5353 5353A	Wheel nuts, splined, 17mm (blue-anodized) (4) Wheel nuts, splined, 17mm (green-anodized) (4)	4930X	Bulkheads, front (machined 6061-T6 aluminum) (blue) (l&r)
5457	Yoke, brake (1)/ torque pins (2)/ 4x15mm screw pin		(requires use of 4939X suspension pins)
5458X	Yokes, differential and transmission (2)/ 4x15mm screw pins (2)	5134	Caster spacers (4)/ shims (4)
5453	Yokes, stub axle (2)/ pins (2)	5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)
	Engine & Servo Mounts	5378X	Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust
5160	Engine mount, aluminum/ 3x10 CS with washers (8)	4022	boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)
4960X	Engine mount, machined 6061-T6 aluminum (blue) (w/ screws) (Maxx® Series)	4933 <b>4933X</b>	Pivot balls (4)/ pivot ball cap bushings (4)  Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap
3159	Screws, 3x10mm cap-head machine (hex drive) (6)/ lock washers (6)/ hex wrench	5347	bushings (4) Rod ends, Revo® (large) with hollow balls (12)
4918	Servo mounts, steering/ shift (f&r) (black)	2742X	Rod ends, short (6)/ hollow balls (6)
4918X	Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/	4859	Screws, 3x10 flathead machine (hex drive) (4)
40404	machine screws (8)	5345R	Servo horns, steering, long (2), short (2)/ linkage, steering (3x20mm
4918A <b>4919</b>	Servo mounts, steering/shift (f&r)(grey) Servo mounts, throttle/ brake (1) (black)	2070	turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4) Servo, digital high-torque (ball bearing)
4919X	Servo mounts, throttle/ brake (machined aluminum) (blue) (f&r)/	4917R	Shock tower (for rectangular body posts)
40404	machine screws (8)	4945	Steering bellcranks/ servo saver/ servo saver spring/ servo spring
4919A	Servo mounts, throttle/brake (1) (grey)	E122D	retainer (requires 5x11mm BB (2))
5000D	Engine Components	5132R 5131R	Suspension arms (lower) (2) (fits all Maxx® series) Suspension arms (upper) (2) (fits all Maxx® series)
5238R	Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5)	5161	Suspension screw pin set, hardened steel (hex drive)
3232X	Glow plug, super-duty (long-medium)/gasket	5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/
5228	Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3)		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
5290 5211R	Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5,	54.44D	suspension & 3.8' wheels)
02	2.5R, 3.3)	5141R	Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/
4859	Screws, 3x10mm flat-head machine (hex drive) (4)		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
3932 5277	Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3)	E4.44	suspension & 3.8" wheels)
5170	Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3)	5141	Turnbuckles, toe links (5.0mm steel) (front) (2)
	Exhaust	3147	Fuel Tank & Line
3155	Cable ties, medium (black) (6)	3147 3147X	Fuel line (1 foot) Fuel line (610mm or 2ft)
3296	Fittings, inlet (nipple) for fuel or water cooling (2)	4948	Fuel Tank (125cc)
4961	Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip	4958	Fuel tank rebuild kit (contains cap, foam washer, o-ring, upper/lower
5140	Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX	3149A	retainers, screw, spring and screw pin) Heat shield tubing, fiberglass (2) (black)
5256	2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3)		Fuel, Lubricants & Supplies
5246	Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R)	5001	Bottle, fuel filler (500cc)
2577	(TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6)	3232X 5148	Glow plug, super-duty (long-medium)/gasket Grease, white lithium
5142	Screws, 3x15mm cap-head machine (hex drive) (with split and flat	5263	Oil, air filter
	washers) (6)	5001R	Rebuild kit, fuel filler bottle (includes bottle lid (1) and dispensing tube
5487	Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines)	5070	caps, rubber (2) (fits 8mm or 5/16" dispensing tube))  Top Fuel®, 20% nitro (gallon)
	EZ Start 2 & Related parts	5020	Top Fuel®, 20% nitro (quart)
4579	Connector, wiring harness (EZ-Start® and EZ-Start® 2)	5080	Top Fuel®, 33% nitro (gallon)
5280	Control box (complete) (EZ-Start® 2)	5030	Top Fuel®, 33% nitro (quart)
5281	Control box battery cover w/ belt clip (EZ-Start® 2)		Hardware
5273	Cush-drive elements (4) (EZ-Start® 2)	5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools
5270R	EZ-Start® 2, complete system with controller, drive unit, wiring harness	<b>5526R</b> 3935	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools Body clip (mounting clip), angled, 90-degrees (10)
5276	Gear set (complete) (EZ-Start® 2)	3935A	Body clip (mounting clip), angled, 90-degrees (black) (10)
5148	Grease, white lithium	1834	Body clips (12) (standard size)
		3934	Body clips, heavy duty (12)

Page 3	T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxx	as Link V	Nireless Module, & TSM (Model 49077-3) Parts List
3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
5150	E-clips, 1.5mm (24)	6552	Seal kit, expander box (includes o-ring, seals, and silicone
1633	E-clips/ C-rings		grease)
5477	Flat wrench, 5mm (blue-anodized aluminum)	6526	Sensor, auto-detectable, temperature
5478	Flat wrench, 8mm (blue-anodized aluminum)	<b>6527</b>	Sensor, auto-detectable, voltage
3980	Glow plug wrench (universal wrench)	6520 6521	Sensor, RPM (long)/ 3x4mm BCS (2)/ 3x4 GS (1) Sensor, temperature and voltage (long)
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)	2071	Servo case (for 2070 servo)
2586	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)	2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)
5476X	Hex wrenches; 1.5mm, 2mm, 2.5mm, 3mm, 2.5mm ball	2070	Servo, digital high-torque (ball bearing)
5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	2075	Servo, digital high-torque (ball bearing), waterproof
	adjustment shims; 3.5mm (2), 1.17mm (2)	6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
5475	Multi-tool (plastic)	6550X	Telemetry expander 2.0, TQi radio system (compatible only with
2745 <b>4147X</b>	Nuts, 3mm nylon locking (12)  Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4)	CEEO	#6551X GPS module)
5147X	Nuts, 5mm flanged hylon locking (steel, serrated) (8)	6550 6551X	Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only
4147	Nuts, 5mm nylon locking (8)	000170	with #6550X telemetry expander)
3982	PTFE-coated 6x8x0.5 (10)	6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)		Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
5347	Rod ends, Revo® (large) with hollow balls (12)	0500	receiver)
2742X	Rod ends, short (6)/ hollow balls (6)	6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)
3215	Screws, 2.5x6mm cap-head machine (hex drive) (6)	6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-
3965 5169	Screws, 2.5x8mm cap-head machine (6) Screws, 2.6x8mm countersunk machine (6)		channel (transmitter only)
2562	Screws, 2.6x8mm roundhead machine (6)	6511	Traxxas Link™ Wireless Module
3161	Screws, 2x8mm countersunk machine (6)	3034	Wiring harness for RX Power Pack, Traxxas® nitro vehicles
2577	Screws, 3x10mm button-head machine (hex drive) (6)		(includes on/off switch and charge jack)
3159	Screws, 3x10mm cap-head machine (hex drive) (6)/ lock washers (6)/		Ready-To-Race Model
	hex wrench	49077-3	T-Maxx® 3.3: 1/10 Scale Nitro-Powered 4WD Maxx® Monster Truck
2551	Screws, 3x10mm countersunk machine (6) (hex drive)		with TQi 2.4GHz Radio System, Traxxas Link™ Wireless Module,
4859 5282	Screws, 3x10 flat-head machine (hex head) (4) Screws, 3x12mm button-head machine (6) (starter attachment screws		and Traxxas Stability Management (TSM)®
3202	with threadlock)		<b>Rear Suspension</b>
2578	Screws, 3x12mm button-head machine (hex drive) (6)	4934X	Aluminum caps, pivot ball (blue-anodized) (4)
2552	Screws, 3x12mm countersunk machine (6) (hex drive)	5334	Axle carriers, left & right (1 each)
2579	Screws, 3x15mm button-head machine (hex drive) (6)	5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball
5142	Screws, 3x15mm cap-head machine (hex drive) (with split and flat		bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust boot retainers (4)
2552	washers) (6) Serous 2x15mm counterpunk machine (6) (hox drive)	4914R	Body mount posts, front (2)/ body mount, rear/ body mount screw
2553 2580	Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x20mm button-head machine (hex drive) (6)		pins (4)
4978	Screws, 3x21mm button-head machine (hex drive) (partially	3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)
	threaded, Revo brake bolts) (6)	4929R	Bulkheads (I & r) (rear) (grey)
2554	Screws, 3x6mm cap-head machine (hex drive) (6)	4929X	Bulkheads, rear (machined 6061-T6 aluminum) (blue)(l&r) (requires use of 4939X suspension pins)
3932	Screws, 3x6mm flat-head machine (hex drive) (6)	5134	Caster spacers (4)/ shims (4)
2576	Screws, 3x8mm button-head machine (hex drive) (6)	5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer
2550 4897	Screws, 3x8mm countersunk machine (6) (hex drive) Screws, set (grub) 4mm (6) (with threadlock)		adjustment shims; 3.5mm (2), 1.17mm (2)
2743	Set (grub) screws, 3mm hardened (12)	5378X	Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)	4000	boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)
3981	Washer, PTFE-coated 6x9.5x.5 (10)	4933 <b>4933X</b>	Pivot balls (4)/ pivot ball cap bushings (4)
2746	Washers, 3x6mm metal (12)	4333A	Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap bushings (4)
	Manuals	5347	Rod ends, Revo® (large) with hollow balls (12)
5299R	Engine Manual, TRX® 2.5, 2.5R, 3.3	5348	Rod ends, Revo® (large, for rear toe link only) (4)
020011	Radio System, Batteries & Chargers	4917R	Shock tower (for rectangular body posts)
4700		5132R	Suspension arms (lower) (2) (fits all Maxx® series)
1726 6548	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	5131R	Suspension arms (upper) (2) (fits all Maxx® series)
0340	6530 transmitters)	5161 4956	Suspension screw pin set, hardened steel (hex drive) Tie bar, rear (1) /3x18mm BCS (2) (fits all Maxx® trucks)
2914	Battery, Power Cell AA Alkaline (4)	5143A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
3037	Battery, RX Power Pack (5-cell hump style, NiMH, 1200mAh)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
2919	Battery, Series 1 Power Cell 1800mAh (NiMH, 6-C flat, 7.2V, Sub-C)		wrench (1) (For Maxx® models w/sealed pivot ball suspension &
2734	Cable ties (small) (10)		3.8' wheels)
2977	Charger, DC, 2 amp (Molex) (5 - 6 cell, 6.0 - 7.2 volt, NiMH)  Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery	5143R	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
2972	Identification		wrench (1) (For Maxx® models w/sealed pivot ball suspension &
2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto		3.8" wheels)
	Battery Identification	5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery		Recoil Starter
0070	Identification	5277	Shaft, starter (TRX® 2.5, 2.5R, 3.3)
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification	5170	Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3)
6525	Communication link, telemetry expander		Shocks (Pro-level Aluminum)
2978	Fuse, charger, 5A (2) (for #2974, 2975, 2977)	2666	Big Bore shock cylinder (XX-long) (1)
2010	Gear set (for 2018 servos)	2662	Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6
2072A	Gear set (for 2070, 2075 servos)		aluminum) (assembled with TiN shafts) w/o springs (rear) (2)
6556	Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all	4962	Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6
	Maxx® trucks, Revo® 3.3, Slayer Pro 4X4) (*requires rear chassis brace #5632)		aluminum) (assembled) w/ red springs, TiN shafts (8 pack)
6536	Mounts, RPM sensor (nitro engines)/ 3x10mm CS with split and flat	2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings
0000	washers (2)	2362	& washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	2002	

Page 4	T-Maxx: TRX 3.3	, TQi 2.4GHz Radio S	ystem, 1	Traxxas Link Wireless Module	, & TSM	(Model 49077-3)	Parts List
--------	-----------------	----------------------	----------	------------------------------	---------	-----------------	------------

Page 4	T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxx		(
1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2)		Suspension Linkage
2742X	Rod ends, short (6)/ hollow balls (6)	1633	E-clips/ C-rings
3962	Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8)	5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer
2667	Shock caps, aluminum (Big Bore Shocks) (2)	50.47	adjustment shims; 3.5mm (2), 1.17mm (2)
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	5347 2742X	Rod ends, Revo® (large) with hollow balls (12) Rod ends, short (6)/ hollow balls (6)
0050	(2)	3744	Servo saver w/adapters
2656 1765	Shock shafts, steel, chrome finish (xx-long) (2)	3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
1666	Silicone diaphragms (4) Silicone shock oil (30 wt)	5161	Suspension screw pin set, hardened steel (hex drive)
2668	Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks)	5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball
4649R	Springs, red (for big bore shocks) (2.5 rate) (2)	5143A	suspension & 3.8' wheels) Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	Shocks (Ultra Shocks)	01407	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
3766A	Body, Ultra Shock(s) (XXL) (grey) (2)		wrench (1) (For Maxx® models w/sealed pivot ball suspension 8
2362	Rebuild kit, Ultra shocks (for 2 shocks)	5141R	3.8' wheels) Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum,
2742X 3767	Rod ends, short (6)/ hollow balls (6)	31411	stronger than titanium) (112mm, front) (2)/ rod ends (4)/
3767A	Shock caps (2)/ shock bottoms (2)  Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
3767G	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks)		suspension & 3.8" wheels)
	(3	5143R	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum,
3767P	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8
3767X	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)		3.8" wheels)
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	5141	Turnbuckles, toe links (5.0mm steel) (front) (2)
2656	(2) Shock shafts, steel, chrome finish (xx-long) (2)	5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)		<b>Team Traxxas Items</b>
1765	Silicone diaphragms (4)	2514	Decal sheet, racing sponsors
1666	Silicone shock oil (30 wt)	6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)
3769	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)	9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)
3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole	9909	Traxxas® racing banner, red & black (3x7 feet)
4957R	(2)) Springs, progressive rate (for Ultra-Shocks only) (progressive		Throttle & Brake Linkage
433710	rate) (f/r) (4)	4967	Brake cam (blue)/ cam lever/ 3mm set screw
3757R	Springs, rear (red) (2.9 rate) (2)	3182	Collars, screw (2)/ set screws, 3mm (2)
4957	Springs, red (for Ultra Shocks only) (2.5 rate) (f/r) (2)	3147X	Fuel line (610mm or 2ft)
3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load	3180	Rod guides (2)/ 3mm nylon locknuts (2)
27624	spacers & springs) (rear) (2)	4182 5167	Servo horn, throttle-brake/ shift (1) Slide carb linkage bellcrank post/ 5x8x2.5 plastic bushing (2)/
3762A	Ultra shocks (grey) (xx-long) (complete w/ spring pre-load spacers & springs) (2)	3107	bellcrank/ 5x8x0.5 fiber washer (2)/ 3x10 WM
	Slipper Clutch Components	5168	Slide carb linkage set (throttle link, brake link, and hardware)
5440		4056	Spring, throttle return (2) (Jato®, T-Maxx® 2.5R, 3.3)
5116 <b>5478</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2)  Flat wrench, 8mm (blue-anodized aluminum)	3184	Springs: throttle/brake/shift (3)
5366	Input shaft, transmission (slipper shaft)		Tires & Wheels
5352R	Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum	4147X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4)
	friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm	5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
50501/	pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	4955	Pins, axle (2.5x12mm) (4)
5352X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/	5666	Sidewall protector, beadlock style (blue) (2)/ 2.5x8mm CS (24)
2554	2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Screws, 3x6mm cap-head machine (hex drive) (6)	5664	(for use with Geode wheels) Sidewall protector, beadlock style (green) (2)/ 2.5x8mm CS (24)
5351	Slipper pressure plate and hub (alloy)	0004	(for use with Geode wheels)
	Spur Gears	5667	Sidewall protector, beadlock style (red) (2)/ 2.5x8mm CS (24) (fo
2056	Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch)		use with Geode wheels)
3956 3957	Spur gear, 56-tooth (0.8 metric pitch, compatible with 32-pitch)	5665	Sidewall protector, beadlock style (yellow) (2)/ 2.5x8mm CS (24)
3958	Spur gear, 58-tooth (0.8 metric pitch, compatible with 32-pitch)	5374X	(for use with Geode wheels)  Tires & wheels, assembled, glued (Gemini black chrome wheels
3959	Spur gear, 62-tooth (0.8 metric pitch, compatible with 32-pitch)	JJ14A	Talon tires, foam inserts) (2) (use with 17mm splined wheel hub
	Steering Components		& nuts, part #5353X) (TSM rated)
2728	Ball bearings (5x8x2.5mm) (2)	5374	Tires & wheels, assembled, glued (Gemini chrome wheels, Talo
5116	Ball bearings (5x6x2.5mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)		tires, foam inserts) (2) (fits Maxx/Revo series)
4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/	5674	Tires & wheels, assembled, glued (Geode chrome wheels, Maxx® tires (6.3" outer diameter), foam inserts) (2) (use with
	long rod ends (2)		17mm splined wheel hubs & nuts, part #5353X & beadlock-style
2072A	Gear set (for 2070, 2075 servos)		sidewall protectors, part #5665, 5666, 5667)
5347	Rod ends, Revo® (large) with hollow balls (12)	5672	Tires & wheels, assembled, glued (Geode chrome wheels,
2579 <b>5345X</b>	Screws, 3x15mm button-head machine (hex drive) (6) Servo horns, steering and throttle (for non-Traxxas® servos		paddle tires, foam inserts) (2) (use with 17mm splined wheel
JJ45A	(Hitec, JR, KO, Airtronics))	4973R	hubs & nuts, part # 5353X) (TSM rated) Tires & wheels, assembled, glued (Hurricane chrome wheels, Maxx®
	Servo horns, steering, long (2), short (2)/ linkage, steering (3x20mm	TO I OF	tires (6.3" outer diameter), foam inserts) (2) (fits Revo®/Maxx®
5345R	turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)		series)
5345R	turnbuckie) (2)/ rod erius (short) (4)/ riollow balls (4)	5174A	Tires & wheels, assembled, glued (Split-Spoke satin-finish
4918	Servo mounts, steering/ shift (f&r) (black)		
	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/		wheels, Talon tires, foam inserts) (2) (fits Maxx® w/sealed pivot
4918 4918X	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8)		ball suspension & Revo®)
<b>4918</b> <b>4918X</b> 4918A	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8) Servo mounts, steering/shift (f&r)(grey)	4983A	ball suspension & Revo®) Tires & wheels, assembled, glued (SS (Split Spoke) black
<b>4918</b> <b>4918X</b> 4918A 2070	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8) Servo mounts, steering/shift (f&r)(grey) Servo, digital high-torque (ball bearing)		ball suspension & Revo®)
<b>4918</b> <b>4918X</b> 4918A 2070 <b>2075</b>	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8) Servo mounts, steering/shift (f&r)(grey) Servo, digital high-torque (ball bearing) Servo, digital high-torque (ball bearing), waterproof		ball suspension & Revo®)  Tires & wheels, assembled, glued (SS (Split Spoke) black chrome wheels, Maxx® tires (6.3" outer diameter), foam inserts) (2) (fits Maxx®/Revo® series) (TSM rated)  Tires & wheels, assembled, glued (SS (Split Spoke) chrome
<b>4918</b> <b>4918X</b> 4918A 2070	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8) Servo mounts, steering/shift (f&r)(grey) Servo, digital high-torque (ball bearing)	4983A	ball suspension & Revo®) Tires & wheels, assembled, glued (SS (Split Spoke) black chrome wheels, Maxx® tires (6.3" outer diameter), foam inserts) (2) (fits Maxx®/Revo® series) (TSM rated) Tires & wheels, assembled, glued (SS (Split Spoke) chrome wheels, Maxx® Chevron tires, foam inserts) (2) (fits
4918 4918X 4918A 2070 2075	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/ machine screws (8) Servo mounts, steering/shift (f&r)(grey) Servo, digital high-torque (ball bearing) Servo, digital high-torque (ball bearing), waterproof Steering bellcranks/ servo saver/ servo saver spring/ servo spring	4983A	ball suspension & Revo®)  Tires & wheels, assembled, glued (SS (Split Spoke) black chrome wheels, Maxx® tires (6.3" outer diameter), foam inserts) (2) (fits Maxx®/Revo® series) (TSM rated)  Tires & wheels, assembled, glued (SS (Split Spoke) chrome

	Tires & wheels, assembled, glued (SS (Split Spoke) chrome wheels, Talon tires, foam inserts) (2) (use w/17mm splined wheel		Traxxas Tools
	hubs & nuts, part #5353X)	3433X	Body reamer (aluminum handle)
375R	Tires & wheels, assembled, glued (white dished 3.8" wheels,	3433	Body reamer (plastic handle)
	Response Pro tires, foam inserts) (2) (use with 17mm splined	3436	Cap, body reamer
5670	wheel hubs and wheel nuts, part #5353X)	3432 3431	Scissors, curved tip Scissors, straight tip
<b>5670</b> 4973	Tires, Canyon AT 3.8" (2)/ foam inserts (2) Tires, Maxx® 3.8" (6.3" outer diameter (160mm)) (2) (fits	3431 8712	Scissors, straight tip  Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
1973	Revo®/Maxx® series)	07 12	premium handle (medium), travel pouch, hex drivers (straight:
5171	Tires, Maxx® Chevron 3.8" (2) (fits Revo®/Maxx® series)		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
5375	Tires, Response Pro 3.8" (soft-compound, narrow profile, short		and 8.0mm), 1/4" drive
	knobby design)/ foam inserts (2)	8722	Speed bit handle, premium, medium (rubber overmold)
5471	Tires, Response racing 3.8" (soft-compound, narrow profile,	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
	short knobby design)/ foam inserts (2)		premium handle (medium), travel pouch, hex drivers (straight:
5470	Tires, SportTraxx racing 3.8" (soft compound, directional and		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,
F070	asymmetrical tread design)/ foam inserts (2)		7.00mm, 8.00mm),
<b>5370</b> 4954	Tires, Talon 3.8" (2)/ foam inserts (2)	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
4954R	Wheel hubs, hex (2)/ axle pins (2.5x12mm) (2) Wheel hubs, hex (steel)		includes premium handle (medium), travel pouch, hex drivers
1954X	Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins		(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
10017	(2.5x10mm) (4)		2.5mm, 3.0mm), 1/4" drive
5353X	Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts,	8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with		handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
	threadlock) (4)	8716	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts,	07 10	drive
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
	threadlock) (4)		3.0mm), 1/4" drive
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts,	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
	splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)		2.5mm), 1/4" drive
5353	Wheel nuts, splined, 17mm (blue-anodized) (4)	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
5353A	Wheel nuts, splined, 17mm (green-anodized) (4)		2.5mm, 3.0mm), 1/4" drive
5480X	Wheel wrench, splined, 17mm	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
5371	Wheels, dished 3.8" (white) (2) (use with 17mm splined wheel		3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
	hubs and wheel nuts, part #5353X)		drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench
5372A	Wheels, Gemini 3.8" (black chrome) (2)		driver handle
5372X	Wheels, Gemini 3.8" (black chrome) (2) (use with 17mm splined		Turnbuckles & Threaded Rods
	wheel hubs & nuts, part #5353X)	10.11	
5372	Wheels, Gemini 3.8" (chrome) (2)	4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/
5671	Wheels, Geode 3.8" (chrome) (2) (use with 17mm splined wheel	5355	long rod ends (2) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer
	hubs & nuts, part #5353X & beadlock-style sidewall protectors, part #5665, 5666, 5667)	3333	adjustment shims; 3.5mm (2), 1.17mm (2)
5373	Wheels, Hurricane 3.8" (chrome) (2)	5347	Rod ends, Revo® (large) with hollow balls (12)
5172A	Wheels, SS (split spoke) 3.8" (black chrome) (2) (use with 17mm	2742X	Rod ends, short (6)/ hollow balls (6)
	splined wheel hubs & nuts, part #5353X) (fits Revo®/Maxx®	5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	series)		stronger than titanium) (112mm, front) (2)/ rod ends (4)/
5172X	Wheels, SS (split spoke) 3.8" (chrome) (2) (fits Revo®/Maxx®		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
	series)		suspension & 3.8' wheels)
5172R	Wheels, SS (split spoke) 3.8" (chrome) (2) (use with 17mm	5143A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	splined wheel hubs & nuts, part #5353X) (fits Revo®/Maxx® series)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
5172			wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8' wheels)
3172	Wheels, SS (split spoke) 3.8" (satin) (2) (fits Revo®/Maxx® series)	5141R	Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum,
	,	014110	stronger than titanium) (112mm, front) (2)/ rod ends (4)/
	Transmission Components		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
4611	Ball bearings (5x11x4mm) (2)		suspension & 3.8" wheels)
		5143R	Too links Marry® (Tubes and spedied 7075 TC sluminum
	Ball bearings, blue rubber sealed (10x15x4mm) (2)	3143K	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum,
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	5143K	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur
5116 5117	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2)	5143K	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8
5116 5117 5394X	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)
5116 5117 5394X 5394	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®)	5141	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels) Turnbuckles, toe links (5.0mm steel) (front) (2)
5116 5117 5394X 5394	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)
5116 5117 5394X 5394 <b>5383</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)	5141 5143	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)
5116 5117 5394X 5394 <b>5383</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T	5141 5143 5119	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  TWO-SIGGIFOIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
5116 5117 5394X 5394 <b>5383</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)	5141 5143 5119 5116	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  TWO-SIGHIFOIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
5116 5117 5394X 5394 <b>5383</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)	5141 5143 5119 5116 5117	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  TWO-SIGHI COMPLES  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)
5116 5117 5394X 5394 <b>5383</b> <b>5385</b>	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input	5141 5143 5119 5116 5117 5394X	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)
5116 5117 5394X 5394 <b>5383</b> <b>5385</b> 5384	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/	5141 5143 5119 5116 5117	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  **IWO**SIRGET** **Lower Foundation**  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input
5116 5117 5394X 5394 <b>5383</b> <b>5385</b> 5384 5386 5181	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued	5141 5143 5119 5116 5117 5394X <b>5383</b>	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T inpurgears, hardware)
5116 5117 5394X 5394 5383 5385 5385 5386 5181	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft)	5141 5143 5119 5116 5117 5394X	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T inpurgears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)	5141 5143 5119 5116 5117 5394X 5383 5385	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminur wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T inpur gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm	5141 5143 5119 5116 5117 5394X <b>5383</b>	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input
5116 5117 5394X 5394 <b>5383</b> <b>5385</b> 5384 5386 5181 5366 5390 5393	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued lnput shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  **TWO-SIGGI COIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
5116 5117 5394X 5394 <b>5383</b> <b>5385</b> 5384 5386 5181 5366 5390 5393	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390 5393	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390 5393	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386 5390	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Turnbuckles, toe links (5.0mm steel) (rear) (2)  **Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T  Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)
5119 5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390 5393 5352R	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386 5390	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T  Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)  Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm
5116 5117 5394X 5394 <b>5383</b> <b>5385</b> 5384 5386 5181 5366 5390 5393	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386 5390	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T  Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)  Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390 5393 5352R	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued Input shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Reverse installation kit (includes all components to add mechanical reverse (no Optidrive) to T-Maxx® 3.3) (includes	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386 5390	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T  Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)  Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm
5116 5117 5394X 5394 5383 5385 5384 5386 5181 5366 5390 5393 5352R	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse) Forward only shaft, steel (Revo®) Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware) Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware) Gear, 1st speed, 43T Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued liput shaft, transmission (slipper shaft) Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1) Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Reverse installation kit (includes all components to add	5141 5143 5119 5116 5117 5394X <b>5383</b> <b>5385</b> 5384 5386 5390	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension 8 3.8" wheels)  Turnbuckles, toe links (5.0mm steel) (front) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Turnbuckles, toe links (5.0mm steel) (rear) (2)  Ball bearings, blue rubber sealed (10x15x4mm) (2)  Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Forward only conversion kit (eliminates reverse)  Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)  Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)  Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)  Gear, 1st speed, 43T  Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)  Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm