

Sledge™ (Model 95076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	9528	Tie bars, rear, 6061-T6 aluminum (blue-anodized)
4889X	Ball bearings, black rubber sealed (10x19x5mm) (2)	9626	Tray, battery
5114A	Ball bearings, black rubber sealed (5x8x2.5mm) (2)	9576 9518	Wheelie bar, black (assembled) Wing mount
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)	9517X	Wing/ wing washer (blue)/ 4x12mm FCS (2)
5118A	Ball bearings, black rubber sealed (8x16x5mm) (2)	9517G	Wing/ wing washer (green)/ 4x12mm FCS (2)
5105	Ball bearings, blue rubber sealed (6x10x3mm) (2)	9517T	Wing/ wing washer (orange)/ 4x12mm FCS (2)
	Body & Accessories	9517R	Wing/ wing washer (red)/ 4x12mm FCS (2)
1926	Antenna caps, vinyl (2)/ antenna spool	9517A	Wing/ wing washer (white)/ 4x12mm FCS (2)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	9517	Wing/ wing washer/ 4x12mm FCS (2)
9510	Body reinforcement set, black/ skid pads (roof) (fits #9511 body)		Differential Components
9510X	Body reinforcement set, blue/ skid pads (roof) (fits #9511 body)	4889X	Ball bearings, black rubber sealed (10x19x5mm) (2)
9510G 9510T	Body reinforcement set, green/ skid pads (roof) (fits #9511 body) Body reinforcement set, orange/ skid pads (roof) (fits #9511	9581	Carrier, differential/ differential bushing (metal)/ o-rings (2)/ ring gear gasket
9510R	body) Body reinforcement set, red/ skid pads (roof) (fits #9511 body)	8680	Differential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/ 12.2x18x0.5 PTFE-coated washer (1)
9513X	Body support (assembled with front mount & rear latch)/ skid pads	5136X	Differential oil kit (50cc of 1 each: 10K, 30K, 50K weights)
0540	(roof) (left & right)	9583	Differential output cup, front or rear (hardened steel)/ 2.5x12mm pin
9513	Body support, center/ 3x16 CS (8)	9586	Differential output cup, center (hardened steel)/ 2.5x12mm pin
9511	Body, Sledge™ (clear, requires painting)/window, grille, lights decal sheet	9585	Differential, center (complete) (fits Sledge™)
9511A	Body , Sledge™, blue/ window, grille, lights decal sheet (assembled	9580	Differential, front or rear, complete (fits Sledge™)
	with front & rear body mounts and rear body support for clipless mounting)	9587	Drive cup, front or rear (hardened steel) (for differential pinion gear)/ driveshaft boots (2)/ boot retainers (2)
9511G	Body , Sledge™, green/ window, grille, lights decal sheet (assembled	9582	Gear set, differential (output gears (2)/ spider gears (4)/ spider gear
000	with front & rear body mounts and rear body support for clipless	0504	shafts (2)/ spacers (4))
	mounting)	9584	Mount, center differential
9511T	Body , Sledge™, orange/ window, grille, lights decal sheet (assembled	5130 5135	Oil, differential (100K wt) (0.7 oz (20cc))
	with front & rear body mounts and rear body support for clipless mounting)	5040	Oil, differential (10K wt, 50cc) Oil, differential (20M wt) (standard)
9511X	Body, Sledge™, ProGraphix® (graphics are printed, requires	5136	Oil, differential (30K wt, 50cc)
001170	paint & final color application)/ window, grille, lights decal sheet	5137	Oil, differential (50K wt, 50cc)
9511R	Body, Sledge™, red/ window, grille, lights decal sheet (assembled	9579	Ring gear, differential/ pinion gear, differential
	with front & rear body mounts and rear body support for clipless mounting)	9579R	Ring gear, differential/ pinion gear, differential (machined) (front or rear)
2514	Decal sheet, racing sponsors		Driveline Components
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	9559	Boots, driv eshaft (2)/ retainer (assembled) (2)
	Bumpers & Skidplates	9552	Carriers, stub axle (left and right)
9535	Bumper, front/ skidplate, front/ tie bar mount, front/ 3x25 CS (2)	9555	Driv eshaft, center, front (shaft only, 4mm x 88mm) (1)
9536	Bumper, rear/ skidplate, rear/ tie bar mount, rear/ 3x25 CS (2)	9556	Driv eshaft, center, rear (shaft only, 4mm x 146.5mm) (1)
	Chassis & Attachments	9558	Driv eshaft, front, steel constant-velocity (shaft only, 5mm x 133.5mm)
9514	Body mount, front	9557	(1) Driv eshaft, rear (shaft only , 5mm x 131mm) (1) (for use only with
9515	Body mount, rear/ shock guard (body retainer), front	9551	#9554 stub axle)
9624	Box, receiver (sealed) w/ ESC mount/ receiver box cover/ access	9550	Driv eshaft, steel constant-v elocity (assembled), front (1)
	plug/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x10 BCS (1)	9680	O-rings (6)
9523	Chassis brace (T-Bar), 6061-T6 aluminum (black-anodized)/ 3x16 SS (2)	9551	Rebuild kit, steel constant-velocity driveshaft (includes pins for 2
9523X	Chassis brace (T-Bar), 6061-T6 aluminum (blue-anodized)/ 3x16 SS		driv eshaft assemblies) (for #9550 front or #9654X rear steel CV driv eshafts)
	(2)	9553	Stub axle, front
9523A	Chassis brace (T-Bar), 6061-T6 aluminum (gray-anodized)/ 3x16	9554	Stub axle, rear (for use only with #9557 rear driveshaft)
9523G	SS (2) Chassis brace (T-Bar), 6061-T6 aluminum (green-anodized)/ 3x16	8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
0500-	SS (2)	8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/
9523T	Chassis brace (T-Bar), 6061-T6 aluminum (orange-anodized)/ 3x16 SS (2)	8654A	3x14mm pin (4) Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4)/
9523R	Chassis brace (T-Bar), 6061-T6 aluminum (red-anodized)/ 3x16 SS (2)	8654R	3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/
9520	Chassis brace, front/ 4x15 CCS (2)	000411	3x14mm pin (4)
9521	Chassis braces (rear (1), rear tower (2))/ 4x15 CCS (2)	7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
9522	Chassis, aluminum (blue-anodized)	7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
9627 9516	Hold down, battery Latch, body mount, rear	7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
9628	Retainer, battery hold-down (front and rear) (1 each)	7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
9625	Seal kit, receiver box (includes o-ring, seals, and silicone grease)	7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
9539	Shock tower, front, 6061-T6 aluminum (blue-anodized)		Front Suspension
9539A	Shock tower, front, 6061-T6 aluminum (gray-anodized)	9547	Camber links, front (2) (assembled with hollow balls)
9539G	Shock tower, front, 6061-T6 aluminum (green-anodized)	9532	Caster blocks (c-hub), left & right/ kingpin bushings (4)
9539T	Shock tower, front, 6061-T6 aluminum (orange-anodized)	9683	Hollow balls, steel (8)
9539R 9538	Shock tower, front, 6061-T6 aluminum (red-anodized) Shock tower, rear, 6061-T6 aluminum (blue-anodized)	9598 9597	Linkage, sway bar (front or rear) Mounts, sway bar/ collars (front and rear)
9538A	Shock tower, rear, 6061-T6 aluminum (gray-anodized)	9597 9539	Shock tower, front, 6061-T6 aluminum (blue-anodized)
9538G	Shock tower, rear, 6061-16 aluminum (gray-anodized) Shock tower, rear, 6061-T6 aluminum (green-anodized)	9539A	Shock tower, front, 6061-T6 aluminum (gray-anodized)
9538T	Shock tower, rear, 6061-76 aluminum (green-anodized)	9539G	Shock tower, front, 6061-T6 aluminum (green-anodized)
9538R	Shock tower, rear, 6061-T6 aluminum (red-anodized)	9539T	Shock tower, front, 6061-T6 aluminum (orange-anodized)
9524	Side guards, chassis (left and right)/ 3x8 CCS (10)	9539R	Shock tower, front, 6061-T6 aluminum (red-anodized)
9527	Tie bars, front, 6061-T6 aluminum (blue-anodized)		

Page 2	Sledge™: TQi Traxxas	Link Enabled 2.4GHz	Radio & TSM (Mod	del 95076-4) Parts List
--------	----------------------	---------------------	------------------	-------------------------

Page 2	Sledge™: TQi Traxxas Link Enabled 2.4GHz Radio	& TSM (Model 95076-4) Parts List
9637X	Steering block arms (aluminum, blue-anodized) (2)/ steering		Motors & Electronics
9637G	blocks, left or right Steering block arms (aluminum, green-anodized) (2)/ steering	3475 9590	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear adapter, fixed (A)/ motor mount spacer
9637T	blocks, left or right Steering block arms (aluminum, orange-anodized) (2)/ steering	2277	Gear set, metal (for 2275 servo)
9637R	blocks, left or right Steering block arms (aluminum, red-anodized) (2)/ steering	9591 9589	Hardware, motor mount, Sledge™ Motor mount, aluminum (upper and lower)/ motor mount spacer/ hardware
9537	blocks, left or right Steering blocks, left & right/ M4x0.7 NL (4)	3483	Motor, 2000Kv 77mm, brushless (with 6.5mm gold-plated connectors
9637A	Steering blocks, left & right/ steering block arms (aluminum, dark titanium-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2)	2278	& high-efficiency heatsink) Servo case, aluminum (black-anodized) (middle) (for 2275 servo)
9526 9633	Steering link (30mm) (1)/ hollow balls (2) Suspension arm covers, black, front (left and right)/ 2.5x8 CCS (12)	2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2275 servo)
9633X	Suspension arm covers, blue, front (left and right)/ 2.5x8 CCS (12)	2255	Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof
9633G	Suspension arm covers, green, front (left and right)/ 2.5x8 CCS (12)	2275 3485T	Servo, digital high-torque, metal gear (ball bearing), waterproof Velineon® VXL-6s Electronic Speed Control, waterproof (brushless)
9633T	Suspension arm covers, orange, front (left and right)/ 2.5x8 CCS (12)		(fwd/rev/brake) Radio System, Batteries & Chargers
9633R 9531	Suspension arm covers, red, front (left and right)/ 2.5x8 CCS (12) Suspension arm, front (left), black	2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
9531X	Suspension arm, front (left), blue	2842X	5000mAh 7.4v 2-Cell 25C LiPo Battery
9531G	Suspension arm, front (left), green	2843X	5800mAh 7.4v 2-Cell 25C LiPo Battery
9531T	Suspension arm, front (left), orange	2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery
9531R	Suspension arm, front (left), red	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
9530	Suspension arm, front (right), black	2943	Battery charge indicators (green (4), blue (4), gray (4))
9530X	Suspension arm, front (right), blue	6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
9530G	Suspension arm, front (right), green	2914	Battery, Power Cell AA Alkaline (4)
9530T	Suspension arm, front (right), orange	2914	Battery/charger completer pack (includes #2972 Dual iD®
9530R 9540	Suspension arm, front (right), red Suspension pin set, front & rear (hardened steel), 4x67mm (4),		charger (1), #2869X 7600mAh 7.4V 2-cell 25C LiPo battery (2))
9541	3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2) Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2)	2990	Battery/charger completer pack (includes #2972 Dual iD® charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
9542	Suspension pins, infection and the suspension pins, outer, front, 3.5x48.2mm (hardened steel) (2)/ M3x0.5mm NL, flanged (2)	2998	Battery/charger completer pack (includes #2981 iD® charger (1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (1))
9595	Sway bar kit, Sledge™ (front and rear) (includes front and rear	2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification
9596 9527	sway bars and linkage) Sway bar set, Sledge (includes 1 each of all 6 sway bars)	2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification
9321	Tie bars, front, 6061-T6 aluminum (blue-anodized)	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification
1552	Backplate screws (3x8mm cap-head machine) (6)/washers (6)/weench	2981	Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification
2585 9591	Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5) Hardware, motor mount, Sledge™	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5, 2.5R, 3.3)	6525 6566	Communication link, telemetry expander Data Link cable, telemetry expander (connects #6550X telemetry
2586 9564	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5) Mount, shock (steel) (2)		expander 2.0 to the #3485 VXL-6s or #3496 VXL-8s electronic speed control)
2745X	Nuts, 3mm ny lon locking, black (8)	2277	Gear set, metal (for 2275 servo)
2744X	Nuts, 3mm ny lon locking, flanged, black (8)	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for
3229 2577	Screws, 2.5x10mm cap-head machine (hex drive) (6) Screws, 3x10mm button-head machine (hex drive) (6)	2968	Traxxas® iD® batteries) LiPo cell voltage checker/balancer (requires #2938X adapter for
4859	Screws, 3x10mm flat-head machine (hex drive) (4)	6535	Traxxas® iD® batteries) Mount, temperature sensor (electric motors)/ wire tie/ thermal
2579 2553	Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive)	6533	pad Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
2583X 2581	Screws, 3x18mm cap-head machine (hex driv e) (6) Screws, 3x25mm button-head machine (hex driv e) (6)	6552	Seal kit, expander box (includes o-ring, seals, and silicone grease)
2581X	Screws, 3x25mm cap-head machine (hex drive) (6)	6526	Sensor, auto-detectable, temperature
4858	Screws, 3x25mm countersunk machine (hex drive) (6)	6527	Sensor, auto-detectable, voltage
9682	Screws, 3x45mm cap-head machine (hex drive) (6)	6521	Sensor, temperature and voltage (long)
2550	Screws, 3x8mm countersunk machine (6) (hex drive)	2278	Servo case, aluminum (black-anodized) (middle) (for 2275 servo)
3937	Screws, 4x12mm button-head machine (hex drive) (6)	2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for
2542	Screws, 4x12mm countersunk machine (hex drive) (6)		2275 servo)
2546	Screws, 4x15mm countersunk machine (hex drive) (6)	2275	Serv o, digital high-torque, metal gear (ball bearing), waterproof
3933	Screws, 4x16mm button-head machine (hex drive) (6)	6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
2589	Screws, 4x20mm button-head machine (hex drive) (6)	6550X	Telemetry expander 2.0, TQi radio system (for use only with
2596	Screws, 4x25mm button-head machine (hex drive) (6)		#6551X GPS module)
2595 3939	Screws, 4x35mm button-head machine (hex drive) (6) Screws, 4x6mm button-head machine (hex drive) (with threadlock) (6)	6551X 6509R	Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™
1548	Set (grub) screws, 3x4mm (8)/ 4x4mm (stainless) (4)	JOUSIN	enabled, TSM (2-ch transmitter, 5-ch micro receiver)
9588	Shoulder screws, 3x16mm (2)	6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4), 3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2)	6528	receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-
9541 9542	Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2) Suspension pins, outer, front, 3.5x48.2mm (hardened steel) (2)/		channel (transmitter only)
9543	M3x0.5mm NL, flanged (2) Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/	6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)
	M3x0.5mm NL, flanged (2)	6530 6511	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module
		6511	Traxxas Link™ Wireless Module

Page 3 Sledge™: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 95076-4) Parts List

05070.4	Ready-To-Race Model	9664T	Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4) spacers (4) (for Sledge™)
95076-4	Sledge™: 1/8 Scale 4WD Brushless Electric Monster Truck with TQi 2.4GHz Traxxas Link™ Enabled Radio System and Traxxas Stability Management (TSM)®	9664R	Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)/ spacers (4) (for Sledge™)
	Rear Suspension	9664	Shock caps, GT-Maxx® shocks (2)/ spring perch/ adjusters (2) (for 2 shocks) (for Sledge™)
9529 9548	Bulkhead, front or rear Camber links, rear (2) (assembled with hollow balls)	8963	Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends (2)/ hollow balls (2)
9683	Hollow balls, steel (8)	8963T	Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with
9598	Linkage, sway bar (front or rear)	9662	rod ends and steel hollow balls) Shock shaft, 80mm (GT-Maxx®) (steel, chrome finish) (2) (assemble
9597	Mounts, sway bar/ collars (front and rear)	9002	with rod ends and steel hollow balls)
9519 9519X	Mud guards, rear (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2) Mud guards, rear, blue (left and right)/ 3x15 CCS (2)/ 3x25 CCS	9662T	Shock shaft, 80mm (GT-Maxx®) (TiN-coated) (2) (assembled with
	(2)	9660	rod ends and steel hollow balls) Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o
9519G	Mud guards, rear, green (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2)	9661	springs) (2) Shocks, GT-Maxx®, long, aluminum (blue-anodized) (fully assemble
9519T	Mud guards, rear, orange (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2)		w/o springs) (2)
9519R 9538	Mud guards, rear, red (left and right)/ 3x15 CCS (2)/ 3x25 CCS (2) Shock tower, rear, 6061-T6 aluminum (blue-anodized)	8968X	Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
9538A	Shock tower, rear, 6061-T6 aluminum (gray-anodized)	8968G	Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
9538G	Shock tower, rear, 6061-T6 aluminum (green-anodized)	8968A	Spring retainer (adjuster), orange-anodized aluminum, GT-
9538T 9538R	Shock tower, rear, 6061-T6 aluminum (orange-anodized)		Maxx® shocks (4) (assembled with o-ring)
9634	Shock tower, rear, 6061-T6 aluminum (red-anodized) Suspension arm covers, black, rear (left and right)/ 2.5x8 CCS (12)	8968R	Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
9634X	Suspension arm covers, blue, rear (left and right)/ 2.5x8 CCS (12)	8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)
9634G	Suspension arm covers, green, rear (left and right)/ 2.5x8 CCS (12)	8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)
9634T	Suspension arm covers, orange, rear (left and right)/ 2.5x8 CCS	9659 9658	Springs, shock (natural finish) (GT-Maxx®) (1.487 rate) (85mm) (2) Springs, shock (natural finish) (GT-Maxx®) (1.569 rate) (85mm)
	(12)	0000	(2)
9634R 9534	Suspension arm covers, red, rear (left and right)/ 2.5x8 CCS (12) Suspension arm, rear (left), black	9657	Springs, shock (natural finish) (GT-Maxx®) (1.671 rate) (85mm) (2)
9534X	Suspension arm, rear (left), blue	8969	Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)
9534G 9534T	Suspension arm, rear (left), green		Springs
9534R	Suspension arm, rear (left), orange Suspension arm, rear (left), red	8966	Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)
9533	Suspension arm, rear (right), black	8967	Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)
9533X	Suspension arm, rear (right), blue	9659 9658	Springs, shock (natural finish) (GT-Maxx®) (1.487 rate) (85mm) (2) Springs, shock (natural finish) (GT-Maxx®) (1.569 rate) (85mm)
9533G 9533T	Suspension arm, rear (right), green	3030	(2)
9533R	Suspension arm, rear (right), orange Suspension arm, rear (right), red	9657	Springs, shock (natural finish) (GT-Maxx®) (1.671 rate) (85mm)
9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4),	8969	(2) Springs shock (noticed finish) (CT Mayy®) (4.725 rate) (2)
9541	3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2) Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2)	0909	Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)
9543	Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/	9590	Spur Gears & Pinion Gears Gear adapter, fixed (A)/ motor mount spacer
	M3x0.5mm NL, flanged (2)	6482X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
9595	Sway bar kit, Sledge™ (front and rear) (includes front and rear	6483X	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
9596	sway bars and linkage) Sway bar set, Sledge™ (includes 1 each of all 6 sway bars)	6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
9528	Tie bars, rear, 6061-T6 aluminum (blue-anodized)	6491R	Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/ set screw
	Shock Oil	9651	Spur gear, 46-tooth, steel (1.0 metric pitch)
5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)	9652	Spur gear, 52-tooth, steel (1.0 metric pitch)
5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)		Steering Components
5033 5034	Oil, shock (40 wt, 500 cSt, 60cc) (silicone) Oil, shock (50 wt, 600 cSt, 60cc) (silicone)	9525	Bellcrank posts, steering (aluminum, blue-anodized)
5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)	9546 2277	Draglink, steering/ 3x14mm SS (2) Gear set, metal (for 2275 servo)
5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)	9683	Hollow balls, steel (8)
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)	2278	Servo case, aluminum (black-anodized) (middle) (for 2275 servo
5029 5038X	Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &	2276	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for
	80 wt premium shock oils with spinning carousel rack)	9544	2275 servo) Serv o horn, steering, metal
5038	Spinning carousel rack	9545	Serv o sav er/ serv o sav er spring/ serv o horn, steering (assembled)
	Shocks (GT-Maxx®)	2255	Servo, digital high-torque 400 brushless, metal gear (ball
8965X	Body, GT-Maxx® shock (aluminum, blue-anodized) (1)	2275	bearing), waterproof Serv o, digital high-torque, metal gear (ball bearing), waterproof
9665X 8965G	Body, GT-Maxx® shock (aluminum, blue-anodized) (long) (1) Body, GT-Maxx® shock (aluminum, green-anodized) (1)	9637X	Steering block arms (aluminum, blue-anodized) (2)/ steering
9665G	Body, GT-Maxx® shock (aluminum, green-anodized) (long) (1)	00070	blocks, left or right
3965T	Body, GT-Maxx® shock (aluminum, orange-anodized) (1)	9637G	Steering block arms (aluminum, green-anodized) (2)/ steering blocks, left or right
9665T	Body, GT-Maxx® shock (aluminum, orange-anodized) (long) (1)	9637T	Steering block arms (aluminum, orange-anodized) (2)/ steering
3965R 9665R	Body, GT-Maxx® shock (aluminum, red-anodized) (1) Body, GT-Maxx® shock (aluminum, red-anodized) (long) (1)		blocks, left or right
3962	Rebuild kit, GT-Maxx® shocks (lower cartridge, assembled, pistons,	9637R	Steering block arms (aluminum, red-anodized) (2)/ steering blocks, left or right
9664A	piston nuts, bladders) (renews 2 shocks) Shock caps, aluminum (black-anodized), GT-Maxx® shocks (4)/	9537 9637A	Steering blocks, left & right/ M4x0.7 NL (4) Steering blocks, left & right/ steering block arms (aluminum,
	spacers (4) (for Sledge™) Shock caps, aluminum (blue-anodized), GT-Maxx® shocks (4)/		dark titanium-anodized) (2)/ 3x18mm CS (2)/ M3x0.5mm NL (2) Steering link (30mm) (1)/ hollow balls (2)
9664X	Shock caps, aluminum (blue-anouized), G1-waxx® shocks (4)/		
9664X 9664G	spacers (4) (for Sledge™) Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)/	9526 9549	Toe links, front (2) (assembled with hollow balls)

Parts List

Page 4	Sledge™: TQi Traxxas Link Enabled 2.4GHz Radio	& 15W	i (Model 95076-4) i
	Suspension Linkage	8711	Speed Bit Master S
9547	Camber links, front (2) (assembled with hollow balls)		includes premium (straight: 1.5mm, 2
9548	Camber links, rear (2) (assembled with hollow balls)		2.5mm, 3.0mm), 1/4
9546	Draglink, steering/ 3x14mm SS (2)	8719	Speed Bit Master S
9683	Hollow balls, steel (8)		handle (medium), t
9544	Serv o horn, steering, metal		5.0mm, 5.5mm, 7.0
9540	Suspension pin set, front & rear (hardened steel), 4x67mm (4),	8716	Speed Bit Set, hex
9541	3.5x48.2mm (2), 3.5x56.7mm (2)/ M3x0.5mm NL, flanged (2) Suspension pins, inner, front or rear, 4x67mm (hardened steel) (2)	0746	drive
9541 9542	Suspension pins, inner, front of rear, 4xo7mm (hardened steel) (2)/	8716X	Speed Bit Set, hex 3.0mm), 1/4" drive
3042	M3x0.5mm NL, flanged (2)	8715	Speed Bit Set, hex
9543	Suspension pins, outer, rear, 3.5x56.7mm (hardened steel) (2)/	07.10	2.5mm), 1/4" drive
	M3x0.5mm NL, flanged (2)	8715X	Speed Bit Set, hex
9549	Toe links, front (2) (assembled with hollow balls)		2.5mm, 3.0mm), 1/-
	Team Traxxas Items	2748R	Tool set (includes
2514	Decal sheet, racing sponsors		2.5mm hex wrench
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)	3415	wrench) Tool set with pouc
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	3415	3.5mm, 4mm drive
9909	Traxxas® racing banner, red & black (3x7 feet)		drivers/ 2mm, 4mm
	Tires & Wheels		#0 Phillips, and #1
2074			driver handle
8674	Tires & wheels, assembled, glued (black 3.8" wheels, paddle		Turnbuck
8672	tires, foam inserts) (2) (TSM rated) Tires & wheels, assembled, glued (black wheels, Talon EXT tires,	9547	Camber links, front
0012	foam inserts) (2) (17mm splined) (TSM rated)	9548	Camber links, rear (
8672G	Tires & wheels, assembled, glued (green wheels, Talon EXT	9683	Hollow balls, steel (8
	tires, foam inserts) (2) (17mm splined) (TSM rated)	9549	Toe links, front (2) (a
8672A	Tires & wheels, assembled, glued (orange wheels, Talon EXT		
	tires, foam inserts) (2) (17mm splined) (TSM rated)		
9672	Tires and wheels, assembled, glued (3.8" black wheels,		
F070	Sledgehammer® tires, foam inserts) (2)		
5670 4973	Tires, Canyon AT 3.8" (2)/ foam inserts (2)		
49/3	Tires, Maxx® 3.8" (6.3" outer diameter (160mm)) (2) (fits Revo®/T-Maxx®/E-Maxx)		
5171	Tires, Maxx® Chevron 3.8" (2) (fits Revo®/T-Maxx®/E-Maxx)		
8673	Tires, paddle 3.8" (2)/ foam inserts (2)		W
5375	Tires, Response Pro 3.8" (soft-compound, narrow profile, short		If you have questions or
	knobby design)/ foam inserts (2)		1-888
5471	Tires, Response racing 3.8" (soft-compound, narrow profile,		(1-888-
9670	short knobby design)/ foam inserts (2)		•
5470	Tires, Sledgehammer® (2)/ foam inserts (2)		For orders, calls outside the or fax to 972-549-301
3470	Tires, SportTraxx racing 3.8" (soft compound, directional and asymmetrical tread design)/ foam inserts (2)		TR
8670	Tires, Talon EXT 3.8" (2)/ foam inserts (2)		1107
8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm		
	pin (4)		
8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/		
	3x14mm pin (4)		
8654A	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4)/		
8654R	wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/		
0034K	3x14mm pin (4)		
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)		
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)		
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)		
7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)		
7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)		
8671	Wheels, 3.8" (black) (2) (17mm splined)		
9671	Wheels, 3.8" (black) (2) (17mm splined)		
8671G	Wheels, 3.8" (green) (2) (17mm splined)		
8671A	Wheels, 3.8" (orange) (2) (17mm splined)		
	Traxxas Tools		
3433X	Body reamer (aluminum handle)		
3433	Body reamer (plastic handle)		
3436	Cap, body reamer		
3432	Scissors, curved tip		
3431	Scissors, straight tip		
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes		
	premium handle (medium), travel pouch, hex drivers (straight:		
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,		
8721	and 8.0mm), 1/4" drive Speed bit handle, medium (one piece)		
8720	Speed bit handle, premium, large (rubber overmold)		
8722	Speed bit handle, premium, medium (rubber overmold)		
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes		
-	premium handle (medium), travel pouch, hex drivers (straight:		
	1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,		

1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm),

Set, hex driver, 7-piece straight and ball end, n handle (medium), travel pouch, hex drivers 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 4" drive Set, nut driver, 6-piece, includes premium travel pouch, and nut drivers (4.0mm, 4.5mm, 0mm, 8.0mm), 1/4" drive x driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" x driver, 3-piece ball-end (2.0mm, 2.5mm, x driver, 3-piece straight (1.5mm, 2.0mm, x driver, 4-piece straight (1.5mm, 2.0mm, 4" drive 1.5mm hex wrench / 2.0mm hex wrench / h/ 4-way wrench/ 8mm & 4mm wrench/ U-joint ch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, ers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut m, and 5mm slotted screwdrivers/ #00 Phillips,

1 Phillips screwdrivers/ 4mm and 8mm wrench/

kles & Threaded Rods

(2) (assembled with hollow balls) (2) (assembled with hollow balls) (assembled with hollow balls)

need technical assistance, call Traxxas at:

3-TRAXXAS

-872-9927) (U.S. residents only)

he U.S., and other information, call 972-549-3000, 011 e-mail Traxxas at support@Traxxas.com

AXXAS.COM