

## QL-900

Print with Confidence  
Experience Unmatched Productivity with this  
Versatile Label Printer



Featuring a flat, easily accessible media path, the **QL-900** boasts superior inkjet performance, producing crisp, clean results. The adjustable media sensor allows printing on various label shapes. With a bright, easy-to-use 7" touchscreen display for seamless printer operation and monitoring, 1600 dpi, and full-color printing, the **QL-900** is versatile and delivers superior results job after job.

- **Operator friendly 7" Touchscreen Display**
- **Sharp print resolution up to 1600 dpi**
- **Print Width up to 8.5"**
- **High productivity label printer**

# Technical Specifications

## Operation

<b>Print Technology</b>	Thermal Inkjet
<b>Ink Type</b>	High-Performance Dye ink, (5) individual CMYKK Cartridges
<b>Print Resolution</b>	1600 dpi x 1600 dpi / 1600 x 800 dpi
<b>Print Speed</b>	6 ips (152 mm/sec) @ 1600 x 1600 dpi 12 ips (305 mm/sec) @ 1600 x 800 dpi*
<b>Label Size/Print Area</b>	Width: 2.0" (50.8 mm) - 8.6" (220.8 mm) Length: 2.5" (63.5 mm) - 75" (1904 mm)
<b>Media Sensors</b>	Gap, Reflective (bottom-only), Continuous
<b>Cutter</b>	Approximately 400,000 cuts on paper liner
<b>User Interface</b>	7" Touchscreen Display, Power Button/LED
<b>Connectivity</b>	USB 2.0; 10/100 BaseT Ethernet, RJ-45 connection
<b>Software</b>	Microsoft Windows® 11, 10, 64/32-bit Driver CQL Pro® advanced label creation and print management software (one free license included)
<b>Color Matching</b>	ICC Color profile support for qualified media

## Supplies

<b>Ink Cartridges</b>	QuickLabel QL-900 CMYKK Natura Dye cartridges, 250mL each
<b>Wiper Module</b>	Approximately 10,000 wipes

## Media

<b>Width</b>	2.125" (54 mm) - 9.0" (228.6 mm)
<b>Length</b>	Length: 2.5" (63.5 mm) - 75" (1904 mm)
<b>Thickness</b>	3.9 - 11.8 mil (0.1 mm - 0.3 mm)
<b>Roll Size</b>	10" OD (254 mm), 3" ID (76 mm) core

## Environmental & Physical

<b>Printer Operating</b>	59° F to 95° F (15° C to 35° C), 30% to 90% Relative Humidity (non-condensing)
<b>Printer Storage</b>	23° F to 113° F (-5° C to 50° C), 30% to 90% Relative Humidity (non-condensing)
<b>Ink Storage</b>	32° F to 95° F (0° C to 35° C), 35% to 85% Relative Humidity (non-condensing)
<b>Atmospheric Pressure</b>	1060hPa (795mmHg) - 700hPa (525mmHg)
<b>Power Requirements</b>	100 - 240 VAC 50/60Hz, 2.5A
<b>Power Consumption</b>	Operating: 60W (max) Idle: 30W (max)
<b>Dimensions</b>	Print Unit (only): 22.5" L x 20.3" W x 13.5" H (514 mm x 565 mm x 343 mm) With HP Unwind: 35.75" L x 23.75" W x 14.25" H (908 mm x 603 mm x 362 mm) With HP Unwind & Rewind: 52.5" L x 23.75" W x 14.25" H (1334 mm x 603 mm x 362 mm)
<b>Weight</b>	Print Unit (only): 75 lbs. (34 Kg) High Performance Unwind: 19 lbs. (8.6 Kg) High Performance Rewind: 20 lbs. (9.1 Kg)
<b>Optional Accessories</b>	RW-900-STD Standard Label Rewinder 10" (254 mm) OD Roll, 6 ips only  UW-900-STD Standard Label Unwinder 10" (254 mm) OD Roll, 6 ips only (required for roll printing operation)  RW-900-HP High Performance Label Rewinder 10" (254 mm) OD Roll, 6 ips or 12 ips*  UW-900-HP High Performance Label Unwinder 10" (254 mm) OD Roll, 6 ips or 12 ips* (required for roll printing operation)

## Warranty

One-Year Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)

## What's Included

QuickLabel QL-900 printer, AC power cord, USB Cable, Installation Guide, CQL Pro® advanced label creation and print management software (one free license included)

Manufacturer-Direct Sales. Warranty and Service | Unlimited Telephone Web and E-mail Technical Support

Optional Remote and On-Site Setup & Training, Extended Warranty Support and QuickSwap™ programs available

 **QuickLabel®** *The Labels You Want When You Need Them.®*

Toll-free: 877-757-7978 | Tel: 401-828-4000 | [info@astronovaproductid.com](mailto:info@astronovaproductid.com) | [www.astronovaproductid.com](http://www.astronovaproductid.com)