

10,1"

Resolution:

1366×768

—

Brightness:

200 cd/m²

—

1 x RJ-45 10/100/1000

Base-T Ethernet Port

—

—

Intel® Celeron J1900

Quadcore bis zu 2,4GHz

Intel® Baytrail Chipsatz

Intel® HD Graphics (Baytrail)

—

Monitor output:

1x VGA

—

Interfaces:

2 x COM RS-232,

1 x RS-232/422/485

—

Power supply:

19 V DC

—

Power adapter: 65W, 19V, 6,3A, AC/DC adapter kit

—

Fanless

—

Measures WxHxD (in mm):

263 x 170 x 38

—

Weight: 1,5 kg

15,6"

Resolution:

1366*768

—

Brightness:

220 cd/m²

—

2 x RJ-45 10/100/1000

Base-T Ethernet Port

—

1 x Mic-IN,

1 x Line-OUT

—

Intel® Core i5 4570TE,

2,7GHz

Intel® Q87 (AMT 9.0) Chip

Intel® HD Graphics 4600

—

Monitor output:

1 x VGA, 1 x DVI-D

—

Interfaces:

2 x COM RS-232,

2 x RS-232/422/485

—

Power supply:

19 V DC

—

Power adapter: 120 W, 19 V, 6,3 A, AC/DC adapter kit

—

Fan

—

Measures WxHxD (in mm):

396 x 245x 48

—

Weight: 4,5 kg

18,5"

Resolution:

1366*768

—

Brightness:

250 cd/m²

—

2 x RJ-45 10/100/1000

Base-T Ethernet Port

—

1 x Mic-IN,

1 x Line-OUT

—

Intel® Core i5 4570TE,

2,7GHz

Intel® Q87 (AMT 9.0) Chip

Intel® HD Graphics 4600

—

Monitor output:

1 x VGA, 1 x DVI-D

—

Interfaces:

2 x COM RS-232,

2 x RS-232/422/485

—

Power supply:

19 V DC

—

Power adapter: 120 W, 19 V, 6,3 A, AC/DC adapter kit

—

Fan

—

Measures WxHxD (in mm):

464 x 284 x 48

—

Weight: 6,8 kg

21,5"

Resolution:

1920*1080

—

Brightness:

250 cd/m²

—

2 x RJ-45 10/100/1000

Base-T Ethernet Port

—

1 x Line-IN,

1 x Line-OUT

—

Intel® Core i5 4570TE,

2,7GHz

Intel® Q87 (AMT 9.0) Chip

Intel® HD Graphics 4600

—

Monitor output:

1 x VGA, 1 x DVI-D

—

Interfaces:

4 x COM RS-232

—

Power supply:

19 V DC

—

Power adapter: 120W, 19V, 6,3 A, AC/DC adapter kit

—

2 Fans

—

Measures WxHxD (in mm):

536 x 328 x 48

—

Weight: 8 kg
