

acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

SECTION 1: Identification

1.1 Product identifier

Trade name Adam's Anti-Fog Solution

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Anti-fog treatment

HS code 3402.13.50.

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc. 8225 North Valley Hwy. Thornton CO 80221 720-484-5059

tips@adamspolishes.com www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500

24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07



- Hazard statements

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

United States: en Page: 1 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Propan-2-ol

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS

Tidzardous ingredients doe	Trazaradas migrodismo adol to dire						
Name of substance	Identifier	Wt%	Classification acc. to GHS				
Propan-2-ol	CAS No 67-63-0	70 - < 85	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225				
dipropylene glycol monomethyl ether	CAS No 34590-94-8	20-<40	Flam. Liq. 4 / H227				
Poly(oxy-1,2-ethanediyl), .alpha [3-[1,3,3,3-tetramethyl-1-[(tri- methylsilyl)oxy]disiloxanyl]propyl]- .omegahydroxy	CAS No 67674-67-3	3-<12	Eye Irrit. 2A / H319				

For full text of abbreviations: see SECTION 16.

United States: en Page: 2 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

none In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

United States: en Page: 3 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

United States: en Page: 4 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	(2-methoxy- methylethoxy)pro- panol	34590- 94-8	TLV®	100		150					AC- GIH® 2019
US	dipropylene glycol methyl ether	34590- 94-8	PEL (CA)	100	600	150	900				Cal/ OSHA PEL
US	dipropylene glycol methyl ether	34590- 94-8	REL	100 (10 h)	600 (10 h)	150	900				NIOS H REL
US	dipropylene glycol methyl ether	34590- 94-8	PEL	100	600						29 CFR 1910.1 000
US	2-propanol	67-63-0	TLV®	200		400					AC- GIH® 2019
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/ OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOS H REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1 000

Notation

TWA

Ceiling-C

ceiling value is a limit value above which exposure should not occur short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless STEL

otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH® 2019

United States: en Page: 5 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	950 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	404 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub-	CAS No	End-	Threshold	Organism	Environmental	Exposure time
stance		point	level		compartment	
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	160 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	water	intermittent release
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _I	microorganisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	19 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	1.9 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	2.2 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	192 ^{mg} / _l	aquatic organisms	water	intermittent release

United States: en Page: 6 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless and clear
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	82 °C
Flash point	12 °C at 101 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

United States: en Page: 7 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

Explosive limits

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	3 vol%
Vapor pressure	4.3 kPa at 20 °C
Density	0.79 – 0.8 ^g / _{cm³} at 25 °C 6.6 – 6.7 ^{lb} / _{gal} at 77 °F
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available	
Auto-ignition temperature	270 °C	
Viscosity	not determined	
Explosive properties	none	
Oxidizing properties	none	

Temperature class (USA, acc. to NEC 500)	$T2B$ (maximum permissible surface temperature on the equipment: $260^{\circ}\text{C})$
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

United States: en Page: 8 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Propan-2-ol	67-63-0	3	

Legend

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United States: en Page: 9 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propan-2-ol	67-63-0	LC50	10,000 ^{mg} / _l	fish	96 h
dipropylene glycol monomethyl ether	34590-94-8	LC50	>150 ^{mg} / _l	fish	72 h
dipropylene glycol monomethyl ether	34590-94-8	ErC50	>969 ^{mg} / _I	algae	72 h
Poly(oxy-1,2- ethanediyl), .alpha[3- [1,3,3,3-tetramethyl-1- [(trimethylsilyl)oxy]dis- iloxanyl]propyl]omega hydroxy	67674-67-3	EC50	68 ^{mg} / _I	daphnia magna	48 h
Poly(oxy-1,2- ethanediyl), .alpha[3- [1,3,3,3-tetramethyl-1- [(trimethylsilyl)oxy]dis- iloxanyl]propyl]omega hydroxy	67674-67-3	EC50	>1,000 ^{mg} / _I	microorganisms	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propan-2-ol	67-63-0	LC50	>10,000 ^{mg} / _I	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

United States: en Page: 10 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	ι	J	Ν	ทเ	ım	bei	r
------	---	---	---	----	----	-----	---

DOT UN 1993 IMDG-Code UN 1993 ICAO-TI UN 1993

14.2 UN proper shipping name

DOT Flammable liquid, n.o.s.

IMDG-Code FLAMMABLE LIQUID, N.O.S.

ICAO-TI Flammable liquid, n.o.s.

Technical name (hazardous ingredients) Propan-2-ol, Poly(oxy-1,2-ethanediyl), .alpha.-[3-

[1,3,3,3-tetramethyl-1-

[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy

14.3 Transport hazard class(es)

DOT 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

DOT II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous

goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

United States: en Page: 11 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1993, Flammable liquid, n.o.s., (contains: Propan-

2-ol, Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tet-ramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-

.omega.-hydroxy), 3, II

Danger label(s)



Special provisions (SP) IB2, T7, TP1, TP8, TP28

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Danger label(s) 3



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-E

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E2

Limited quantities (LQ)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

United States: en Page: 12 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings Name of substance **CAS No** Effective date Remarks Propan-2-ol 67-63-0 1986-12-31 only persons who manufacture by the strong acid process are subject, supplier notification not required

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)				
Name of substance CAS No Functionality Authoritative Lists			Authoritative Lists	
Propan-2-ol	67-63-0	alcohols	OEHHA RELs	
dipropylene glycol monomethyl ether	34590-94-8	surfactant		

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
Propan-2-ol	67-63-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
dipropylene glycol monomethyl ether	34590-94-8	A, O	
Propan-2-ol	67-63-0	A, N, O	

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer

Ν

Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, 0 subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

United States: en Page: 13 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
dipropylene glycol monomethyl ether	34590-94-8		F2
Propan-2-ol	67-63-0		F3

Legend

F2 Flammable - Second Degree F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANOL, (2-METHOXYMETHYLETH-OXY)-	34590-94-8	
2-PROPANOL	67-63-0	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
dipropylene glycol monomethyl ether	34590-94-8	Т
Propan-2-ol	67-63-0	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

Regulated Volatile Organic Compounds (VOC-EPA)Regulated Volatile Organic Compounds (VOC-Cal ARB)100 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

 $\label{thm:local_equation} \mbox{Hazardous Materials Identification System. American Coatings Association.}$

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard

United States: en Page: 14 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

Flammability: flammability hazards Health: health hazard

personal protective equipment (PPE) for normal use Personal protection:

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed
AU	AICS	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

Australian Inventory of Chemical Substances
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISLA ENCS) AICS CICR CSCL-ENCS DSL

ECSI

IECSC

INSQ

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NZIoC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. TCSI **REACH** registered substances Taiwan Chemical Substance Inventory **TSCA** Toxic Substance Control Act

United States: en Page: 15 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book"). Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance

United States: en Page: 16 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

	<u> </u>
Abbr.	Descriptions of used abbreviations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

 $Transport\ of\ dangerous\ goods\ by\ road\ or\ rail\ (49\ CFR\ US\ DOT).\ International\ Maritime\ Dangerous\ Goods\ Code\ (IMDG).\ Dangerous\ Goods\ Regulations\ (DGR)\ for\ the\ air\ transport\ (IATA).$

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United States: en Page: 17 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Anti-Fog Solution

Version number: GHS 1.0 Date of compilation: 2022-01-14

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 18 / 18