



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

SECTION 1: Identification

1.1 Product identifier

Trade name

Adam's Glass Sealant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Glass coating

Uses advised against

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). For professional users only.

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc.
8225 North Valley Hwy.
Thornton CO 80221
720-484-5059

tips@adamspolishes.com
www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS05,
GHS07





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

- Hazard statements

H225 Highly flammable liquid and vapor.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

- Additional statements

This product is for professional use only.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling Propan-2-ol, aminoethylaminopropylmethylsiloxane

2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS			
Name of substance	Identifier	Wt%	Classification acc. to GHS
Propan-2-ol	CAS No 67-63-0	≥ 85	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Hazardous ingredients acc. to GHS

Name of substance	Identifier	Wt%	Classification acc. to GHS
aminoethylaminopropylmethylsiloxane	CAS No 71750-79-3	1 - <3	Acute Tox. 4 / H312 Skin Corr. 1 / H314 Eye Dam. 1 / H318

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	2-propanol	67-63-0	TLV®	200		400					ACGIH® 2019
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1000

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH® 2019



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	benthic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	pelagic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	160 mg/kg	(top) predators	water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	water	intermittent re-lease

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Particulate filter device (EN 143).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless
Odor	like alcohols

Other safety parameters

pH (value)	7 – 8 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	12 °C at 101.3 kPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	4.3 kPa at 20 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	241 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Temperature class (USA, acc. to NEC 500)

T2C (maximum permissible surface temperature on the equipment:
230°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
aminoethylaminopropylmethylsiloxane	71750-79-3	dermal	2,000 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Propan-2-ol	67-63-0	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propan-2-ol	67-63-0	LC50	10,000 mg/l	fish	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propan-2-ol	67-63-0	LC50	>10,000 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	1987
14.2	UN proper shipping name	Alcohols, n.o.s.
14.3	Transport hazard class(es)	
	Class	3 (flammable liquids)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	hazardous to the aquatic environment
	Environmentally hazardous substance (aquatic environment)	1,1,1,3,5,5,5-Heptamethyl-3-octyltrisiloxane
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1987
Proper shipping name	Alcohols, n.o.s.
- Particulars in the shipper's declaration	UN1987, Alcohols, n.o.s., 3, II, environmentally hazardous
Class	3
Packing group	II
Danger label(s)	3, fish and tree



Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	172, IB2, T7, TP1, TP8, TP28
ERG No	127

International Maritime Dangerous Goods Code (IMDG)

UN number	1987
Proper shipping name	ALCOHOLS, N.O.S.
Class	3
Marine pollutant	YES (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3, fish and tree



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1987
Proper shipping name	Alcohols, n.o.s.
Class	3
Environmental hazards	YES (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3



Special provisions (SP)	A3, A180
Excepted quantities (EQ)	E2



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Limited quantities (LQ)

1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings				
Name acc. to inventory	CAS No	Conc.	Remarks	Effective date
isopropyl alcohol	67-63-0	89.95 wt%	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Propan-2-ol	67-63-0	alcohols	OEHHA RELs
polydimethylsiloxane	63148-62-9	shine agent	
1,1,1,3,5,5,5-Heptamethyl-3-octyltrisiloxane	17955-88-3	shine agent	
aminoethylaminopropylmethylsiloxane	71750-79-3	shine agent	
Perfluorooctyl Triethoxysilane	51851-37-7	shine agent	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Propan-2-ol	67-63-0				1.0 %



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Propan-2-ol	67-63-0	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Propan-2-ol	67-63-0		F3

Legend

- F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	CAS No	Classification
Propan-2-ol	67-63-0	E

Legend

- E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Propan-2-ol	67-63-0	T, F

Legend

- F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

Regulated Volatile Organic Compounds (VOC-EPA): 89.95 %
Regulated Volatile Organic Compounds (VOC-Cal ARB): 89.95 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Category	Rating	Description
Chronic	/	none
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazard
Health: health hazard
Personal protection: personal protective equipment (PPE) for normal use
Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
NDSL Non-domestic Substances List (NDSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: Adam's Glass Sealant 2.0	Trade name: Adam's Glass Sealant	yes
14.5	Environmentally hazardous substance (aquatic environment): caprylyl methicone	Environmentally hazardous substance (aquatic environment): 1,1,1,3,5,5,5-Heptamethyl-3-octyltrisiloxane	yes
15.1	New Jersey Worker and Community Right to Know Act		yes
15.1		Right to Know Hazardous Substance List: change in the listing (table)	yes
15.1		Right to Know Hazardous Substance List	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK)	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA): change in the listing (table)	yes
15.1		Hazardous Substances List (MN-ERTK)	yes
15.1		Hazardous Substances List (MN-ERTK): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1	VOC content: Regulated Volatile Organic Compounds (VOC-EPA): 89.96 % Regulated Volatile Organic Compounds (VOC-Cal ARB): 89.96 %	VOC content: Regulated Volatile Organic Compounds (VOC-EPA): 89.95 % Regulated Volatile Organic Compounds (VOC-Cal ARB): 89.95 %	yes
15.1		National inventories: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Glass Sealant

Version number: GHS 2.0
Replaces version of: 2019-10-22 (GHS 1)

Revision: 2019-12-05

Abbr.	Descriptions of used abbreviations
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.