

acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

SECTION 1: Identification

1.1 Product identifier

Trade name Adam's Graphene Ceramic Glass Coating

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Glass coating

Professional use Industrial use

HS code 3208.90.00.

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc. 8225 North Valley Hwy. Thornton CO 80221 720-484-5059

tips@adamspolishes.com www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500

24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

Additional information

Containing a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07



United States: en Page: 1 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

- Hazard statements

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

propan-2-ol

2.3 Other hazards

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS										
Name of substance	Identifier	Wt%	Classification acc. to GHS							
propan-2-ol	CAS No 67-63-0	≥20	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225							
decamethylcyclopentasiloxane	CAS No 541-02-6	< 100	Flam. Liq. 4 / H227							
decamethyltetrasiloxane	CAS No 141-62-8	< 100	Flam. Liq. 3 / H226							

For full text of abbreviations: see SECTION 16.

United States: en Page: 2 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

none In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

United States: en Page: 3 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

United States: en Page: 4 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	lden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	2-propanol	67-63-0	TLV®	200		400					AC- GIH® 2019
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/ OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOS H REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1 000

Notation

Ceiling-C STEL

ceiling value is a limit value above which exposure should not occur short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless

otherwise specified) TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH® 2019

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
propan-2-ol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

United States: en Page: 5 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24 mg/m³	human, inhalatory	worker (industry)	chronic - local ef- fects
decamethyltetrasilox- ane	141-62-8	DNEL	102 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethyltetrasilox- ane	141-62-8	DNEL	102 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
decamethyltetrasilox- ane	141-62-8	DNEL	1,449 mg/ kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
decamethyltetrasilox- ane	141-62-8	DNEL	1,449 mg/ kg bw/day	human, dermal	worker (industry)	acute - systemic ef- fects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
propan-2-ol	67-63-0	PNEC	2,251 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
propan-2-ol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	13 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.2 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	0.12 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)

United States: en Page: 6 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	2.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
decamethyltetrasilox- ane	141-62-8	PNEC	1 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethyltetrasilox- ane	141-62-8	PNEC	6.1 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
decamethyltetrasilox- ane	141-62-8	PNEC	3.8 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
decamethyltetrasilox- ane	141-62-8	PNEC	0.61 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance

United States: en Page: 7 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

number: GHS 1.0	Date of compilation: 2022-08-02
Physical state	liquid
Color	smoke
Particle	not relevant (liquid)
Odor	like alcohols
Other safety parameters	
pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	18 °C at 101 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	73 Pa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	241 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2C (maximum permissible surface temperature on the equipment:

United States: en Page: 8 / 18

230°C)



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

United States: en Page: 9 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
propan-2-ol	67-63-0	3	

Legend

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
propan-2-ol	67-63-0	LC50	10,000 ^{mg} / _l	fish	96 h
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _I	fish	96 h
decamethylcyclopentas- iloxane	541-02-6	EC50	>2.9 ^{µg} / _I	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _I	fish	14 d
decamethylcyclopentas- iloxane	541-02-6	EC50	>15 ^{µg} / _I	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

United States: en Page: 10 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN	num	ber
------	----	-----	-----

DOT	UN 1987
IMDG-Code	UN 1987
ICAO-TI	UN 1987

14.2 UN proper shipping name

DOT	Alcohols, n.o.s.
IMDG-Code	ALCOHOLS, N.O.S.
ICAO-TI	Alcohols n.o.s

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards hazardous to the aquatic environment

United States: en Page: 11 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Environmentally hazardous substance (aquatic environment)

decamethylcyclopentasiloxane

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Particulars in the shipper's declaration UN1987, Alcohols, n.o.s., 3, II, environmentally haz-

ardous

Reportable quantity (RQ) 6,472,492 lbs (2,938,511 kg) (acetic acid, glacial) (methanol)

Danger label(s) 3, fish and tree





Environmental hazards yes (hazardous to the aquatic environment)
Special provisions (SP) 172, IB2, T7, TP1, TP8, TP28

ERG No 127

International Maritime Dangerous Goods Code (IMDG)

Marine pollutant yes (hazardous to the aquatic environment) (decamethylcyclopentas-

iloxane)

Danger label(s) 3, fish and tree





Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR)

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP) A3, A180

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

United States: en Page: 12 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
propan-2-ol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not re- quired	1986-12-31

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
propan-2-ol	67-63-0	alcohols	OEHHA RELs
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
polydimethylsiloxane	63148-62-9	surface modifier	
alkylmethyl silicone	17955-88-3	shine agent	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	trade secret	refractory resin	
acetic acid, glacial	64-19-7	pH adjusting agent	
Alkyl Polysilicates	Trade Secret	resin	
Graphene	7782-42-5	surface modifier	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
propan-2-ol	67-63-0				1.0 %

United States: en Page: 13 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
propan-2-ol	67-63-0	A, N, O	

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational 0 Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
propan-2-ol	67-63-0		F3

Legend

Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
2-PROPANOL	67-63-0	E

Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
propan-2-ol	67-63-0	T, F

Legend

Flammability (NFPA®) Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and **Toxic Enforcement Act of 1987**

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
methanol	67-56-1	0.00073		developmental

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 70 % - Regulated Volatile Organic Compounds (VOC-Cal ARB) 70 %

Industry or sector specific available guidance(s)

United States: en Page: 14 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard Flammability: flammability hazards health hazard

Personal protection: personal protective equipment (PPE) for normal use

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed

United States: en Page: 15 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Country	Inventory	Status
TW	TCSI	not all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI IECSC EC Substance Inventory (EINECS, ELINCS, NLP)

Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory

NZIoC PICCS New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances **TCSI** Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book"). Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

United States: en Page: 16 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

	Date of compilation: 2022-08-02
Abbr.	Descriptions of used abbreviations
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds

United States: en Page: 17 / 18



acc. to 29 CFR 1910.1200 App D

Adam's Graphene Ceramic Glass Coating

Version number: GHS 1.0 Date of compilation: 2022-08-02

Abbr.	Descriptions of used abbreviations
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 18 / 18