

acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

SECTION 1: Identification

1.1 Product identifier

Trade name Adam's Tire Armor

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Tire coating

Professional use Industrial use

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc. 8225 North Valley Hwy. Thornton CO 80221 720-484-5059

tips@adamspolishes.com www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Hazard class and cat- egory	Hazard state- ment
B.6	flammable liquid	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

Additional information

Contains a PBT-/vPvB-substance at a concentration of \geq 0.1%.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word warningPictograms not required

- Hazard statements

H227 Combustible liquid.

United States: en Page: 1 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of \geq 0.1%. Contains a vPvB-substance at a concentration of \geq 0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of ≥ 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	1-<3	Eye Irrit. 2 / H319
dipropylene glycol monomethyl ether	CAS No 34590-94-8	1-<3	Flam. Liq. 4 / H227
2-(2H-benzotriazol-2-yl)-4,6-ditert- pentylphenol CAS No 25973-55-1		0.1 - < 1	Acute Tox. 4 / H312 Acute Tox. 2 / H330 STOT RE 2 / H373

Remarks

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

United States: en Page: 2 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

none In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

not required

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United States: en Page: 3 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Occup	pational exposure	limit value	s (Worl	kplace Ex	cposure L	_imits)
Coup	Name of agent	CACNO	ldon	T\\/ \	T\\/ A	CTEL

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	AC- GIH® 2019
US	(2-methoxy- methylethoxy)pro- panol	34590- 94-8	TLV®	100		150					AC- GIH® 2019

United States: en Page: 4 / 16





acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	dipropylene glycol methyl ether	34590- 94-8	PEL (CA)	100	600	150	900				Cal/ OSHA PEL
US	dipropylene glycol methyl ether	34590- 94-8	REL	100 (10 h)	600 (10 h)	150	900				NIOS H REL
US	dipropylene glycol methyl ether	34590- 94-8	PEL	100	600						29 CFR 1910.1 000

Notation

Ceiling-C

iv STEL

ceiling value is a limit value above which exposure should not occur inhalable fraction and vapor short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless

otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

Relevant DNELs of components

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
2-(2- butoxyethoxy)ethanol	112-34-5	DNEL	68 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2- butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2- butoxyethoxy)ethanol	112-34-5	DNEL	68 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
2-(2- butoxyethoxy)ethanol	112-34-5	DNEL	101 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	950 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	404 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	DNEL	0.7 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	DNEL	0.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

United States: en Page: 5 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Relevant PNECs of components

Relevant PINEUS 0	Components					
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	200 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	4 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	56 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	3.9 ^{mg} / _I	aquatic organisms	water	intermittent release
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	0.4 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	200 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	1.1 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	0.11 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	4.4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	0.44 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
2-(2- butoxyethoxy)ethanol	112-34-5	PNEC	0.32 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	19 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	1.9 ^{mg} / _I	aquatic organisms	marine water	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	2.2 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	192 ^{mg} / _l	aquatic organisms	water	intermittent release
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	0.01 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	0.001 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	1 ^{mg} /	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

United States: en Page: 6 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	451 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	45 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
2-(2H-benzotriazol-2- yl)-4,6-ditertpentyl- phenol	25973-55-1	PNEC	90 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	white
Particle	not relevant (liquid)
Odor	characteristic

United States: en Page: 7 / 16





acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version r

number: GHS 1.0	Date of compilation: 2024-03-14			
Other safety parameters				
pH (value)	7-8 (25 °C)			
Melting point/freezing point	not determined			
Initial boiling point and boiling range	100 °C			
Flash point	86 °C at 101 kPa			
Evaporation rate	Not determined			
Flammability (solid, gas)	not relevant, (fluid)			
Explosive limits				
- Lower explosion limit (LEL)	1.1 vol%			
- Upper explosion limit (UEL)	3 vol%			
Vapor pressure	32 hPa at 25 °C			
Density	1 ^g / _{ml}			
Vapor density	this information is not available			
Solubility(ies)				
- Water solubility	miscible in any proportion			
Partition coefficient				
- n-octanol/water (log KOW)	this information is not available			
Auto-ignition temperature	210 °C (auto-ignition temperature (liquids and gases))			
Viscosity	not determined			
Explosive properties	none			
Oxidizing properties	none			
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment:			

United States: en Page: 8 / 16

200°C)



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1	dermal	>1,100 ^{mg} / _{kg}
2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1	inhalation: dust/mist	>0.4 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

United States: en Page: 9 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of \geq 0.1%. Contains a vPvB-substance at a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

United States: en Page: 10 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous

goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

 Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

United States: en Page: 11 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
acrylic copolymer	not available	polymer	
water	7732-18-5	solvent	
2-(2-butoxyethoxy)ethanol		co-solvent	CA TACs
dipropylene glycol monomethyl ether	34590-94-8	surfactant	
hydroxypropylheptamethyltrisiloxane,eth- oxylated, hydroxy-terminated	67674-67-3	surface modifier	
2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1		EC PBTs
Alcohols, C9-11 ethoxylated	68439-46-3	surfactant	
Polyethylene glycol	25322-68-3	surfactant	
polydimethylsiloxane	63148-62-9	surface modifier	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
2-(2-butoxyethoxy)ethanol		1022			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
dipropylene glycol monomethyl ether	34590-94-8	A, O	

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division 0

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
2-(2-butoxyethoxy)ethanol			
dipropylene glycol monomethyl ether	34590-94-8		F2

Legend

Flammable - Second Degree

United States: en Page: 12 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
GLYCOL ETHERS		Е
PROPANOL, (2-METHOXYMETHYLETH-OXY)-	34590-94-8	

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
dipropylene glycol monomethyl ether	34590-94-8	Т

Legend

Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

Regulated Volatile Organic Compounds (VOC-EPA)Regulated Volatile Organic Compounds (VOC-Cal ARB)1 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	0	no significant risk to health
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazards
Health: health hazard

Personal protection: personal protective equipment (PPE) for normal use

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

United States: en Page: 13 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	not all ingredients are listed

Legend

AllC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP) **ECSI**

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

National Inventory of Chemical Substances INSQ

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NCI NZIoC

PICCS

National Chemical Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances
Taiwan Chemical Substance Inventory REACH Reg. **TCSI** TSCA Toxic Substance Control Act

Chemical Safety Assessment 15.2

Chemical safety assessments for substances in this mixture were not carried out.

United States: en Page: 14 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book"). Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)

United States: en Page: 15 / 16



acc. to 29 CFR 1910.1200 App D

Adam's Tire Armor

Version number: GHS 1.0 Date of compilation: 2024-03-14

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 16 / 16