



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

SECTION 1: Identification

1.1 Product identifier

Trade name

Heavy Cutting Compound

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Vehicle polishing compound
Professional use
Industrial use

HS code

3405.30.00.

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc.
8225 North Valley Hwy.
Thornton CO 80221
720-484-5059

tips@adamspolishes.com
www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

not required

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Description of the mixture

Hazardous ingredients acc. to GHS			
Name of substance	Identifier	Wt%	Classification acc. to GHS
White mineral oil (petroleum)	CAS No 8042-47-5	3 - < 12	Asp. Tox. 1 / H304
Solvent naphtha(petroleum), heavy aromatic, Naphthalene Depleted	CAS No 64742-94-5	3 - < 12	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 4 / H227
Distillates (petroleum), hydro-treated heavy naphthenic	CAS No 64742-52-5	1 - < 3	Acute Tox. 4 / H332 Asp. Tox. 1 / H304
distillates (petroleum) hydrotreated, light	CAS No 64742-47-8	1 - < 3	Asp. Tox. 1 / H304
Solvent naphtha (petroleum), heavy aliph.	CAS No 64742-96-7	1 - < 3	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226

Hazardous ingredients

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

not required

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as
frost

7.3 Specific end use(s)

See section 16 for a general overview.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	alpha-Alumina	1344-28-1	REL							appx-D	NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15					i, dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r, dust	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	ACGIH® 2019
US	aluminium oxide	1344-28-1	PEL (CA)		10					dust	Cal/OSHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5					r	Cal/OSHA PEL
US	glycerine	56-81-5	REL							mist, appx-D	NIOSH REL
US	glycerol	56-81-5	PEL		15					mist, i	29 CFR 1910.1000
US	glycerol	56-81-5	PEL		5					mist, r	29 CFR 1910.1000
US	mineral oil	8042-47-5	TLV®		5					i, ex-Met-Work-Fl	ACGIH® 2019

Notation

appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
exMetWorkFl	excluding metal working fluids
i	inhalable fraction
mist	as mists
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
White mineral oil (petroleum)	8042-47-5	DNEL	165 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
White mineral oil (petroleum)	8042-47-5	DNEL	217 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Distillates (petroleum), hydro-treated heavy naphthenic	64742-52-5	PNEC	9.3 mg/kg	(top) predators	water	short-term (single instance)
Distillates (petroleum), hydro-treated heavy naphthenic	64742-52-5	PNEC	9.3 mg/kg	aquatic organisms	water	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	baby blue
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	8 – 9 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	19 vol%

Vapor pressure	32 hPa at 25 °C
Density	1.2 g/cm ³ 9.94lbs/US Gal
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
---------------------------	--

Viscosity



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

- Kinematic viscosity	10,084 mm ² /s at 25 °C
- Dynamic viscosity	12,000 cP at 25 °C
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Solvent naphtha(petroleum), heavy aromatic, Naphthalene Depleted	64742-94-5	inhalation: vapor	>5.3 mg/l/4h
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	inhalation: vapor	11 mg/l/4h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	inhalation: dust/mist	2.2 mg/l/4h
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	inhalation: vapor	>5.3 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | | |
|------|---|---|
| 14.1 | UN number | not subject to transport regulations |
| 14.2 | UN proper shipping name | not relevant |
| 14.3 | Transport hazard class(es) | none |
| 14.4 | Packing group | not assigned |
| 14.5 | Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 | Special precautions for user | There is no additional information. |
| 14.7 | Transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

- 15.1 **Safety, health and environmental regulations specific for the product in question**
- National regulations (United States)**
- Toxic Substance Control Act (TSCA)** all ingredients are listed
- Superfund Amendment and Reauthorization Act (SARA TITLE III)**



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)			
Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
aluminium oxide	1344-28-1	abrasive	
White mineral oil (petroleum)	8042-47-5	lubricant	
Solvent naphtha(petroleum), heavy aromatic, Naphthalene Depleted	64742-94-5	solvents	
Glycerine	56-81-5	humectant	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	solvents	EC Annex VI CMRs - Cat. 1B
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	solvents	
polyoxyethylene sorbitan monooleate	9005-65-6	surfactant	
acrylic polymer	75760-37-1	viscosity modifier	
triethanolamine	102-71-6	pH adjusting agent	
2-methylpentane-2,4-diol	107-41-5	humectant	

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
diethanolamine	111-42-2	0.0008		cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 4 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 4 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazards
Health: health hazard
Personal protection: personal protective equipment (PPE) for normal use
Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AiIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Abbr.	Descriptions of used abbreviations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Heavy Cutting Compound

Version number: GHS 1.0

Date of compilation: 2023-06-14

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.