


Fitting instructions

These instructions demonstrate how to fit all connector types across the Hoselink range. Please follow the instructions to match the connectors you have purchased.

 To watch video fitting instructions, please visit: www.hoselink.com.au/help/how-to-videos

For further assistance, please email hello@hoselink.com.au or call 1300 900 617 (Monday to Friday 9am - 5pm AEST)

CONNECTOR TYPES

Hose End Connectors



Proceed to **Step 1**

Universal Tap Connector



Proceed to **Step 2**

Accessory Connectors



Proceed to **Step 3**

Adapters



Proceed to **Step 5**

STEP 1 Fit the Hose End Connectors

a. Prepare half a cup of boiling water.



b. Ensure the hose is cut square.



c. Slide grey nut on to hose & put white split ring flush with hose end.



d. **IMPORTANT!** Submerge the hose end 2cm deep into boiled water for approx. 10 seconds to soften.

e. 1. **Hose End Connector:** Place the body of the fitting on a hard flat surface & push the hose down firmly, ALL the way to the bottom.



2. **Hose Connector with Flow Control:** Pull stem out of connector body, place the stem on a hard flat surface & push the hose down firmly, ALL the way to the bottom. Put back into connector body.




Tip: If the hose is not going all the way down, try spraying silicone lubricant onto the stem of the Hose End Connector and inside the hose.

f. Tighten the grey nut.



STEP 2 Fit Tap Connector

Screw tightly on to the tap. If connector appears too small, unscrew size reducer and screw the main connector body on to the tap.




STEP 3 Fit Accessory Connector

Screw directly into the Hoselink sprayer.



STEP 4 Connecting it all together

Line up the white markers on each fitting then point and twist together until firmly locked.



Line markers and join together

Twist to lock until you hear a 'click'

Finished product



TIPS ON USING HOSELINK

Don't lose o-rings

Hoselink fittings feature an o-ring to o-ring seal between each connector, which is how they remain watertight. They can be lost if you disconnect fittings under water pressure, so always turn off the water supply and release pressure before disconnecting. Be sure to keep spare o-rings handy, just in case.



How to join hoses

This is easy, just connect one hose end to the other with a point and twist!



Troubleshooting

Please refer to our website for manuals and how-to videos: www.hoselink.com.au/troubleshooting

STEP 5 How to use Hoselink with an Adapter or convert them to Hoselink

To connect to your existing watering accessories, for best results, **DON'T** use an adapter!

Unscrew the click-on fitting and replace it with an appropriate Hoselink Connector.

If you need further help, please watch our how-to videos:



www.hoselink.com.au/help/how-to-videos



Use a **Universal Tap Connector** (2320) with most pressure washers.



Use an **Accessory Connector** (2470) with watering accessories. You may find some products have a moulded or glued click-on fitting. If this is the case, you'll need a **Click-on Adapter** (2490).



This adapter allows you to connect to a click-on type fitting on one end and to a Hoselink **Accessory Connector** on the

For more information on how you can adapt to Hoselink, please visit: www.hoselink.com.au/adapt-to-hoselink

My hose is skinny

If the wall of your hose is very thin and you are experiencing leaking, use secateurs to cut a further 2mm off the white split ring. This ensures the split ring can grip tightly around the hose.



How to remove a connector

Follow these steps: Unscrew the grey nut. Use a small screwdriver in the gap of the white split ring to wedge it back up the hose. Submerge the hose & fitting in boiling water for 10-15 seconds. Remove and drain off the water. Place the fitting between your feet and pull firmly upwards to release the hose from the barbed stem.

