

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 1 of 17

## SECTION 1. IDENTIFICATION

Product name : **1436333**  
GSLA\_ULTRA Black Paste 50g

Material number : **1436333**

### Manufacturer or supplier's details

Company name of supplier : Ferro Corporation

Address : 6060 Parkland Blvd. Suite 250  
Mayfield Heights OH 44124-4185

Telephone : (216) 875-5600

### Emergency telephone number

In-Country Number : (800)424-9300

CHEMTREC Global Number : +(1)-703-527-3887 (Call Collect)

### Recommended use of the chemical and restrictions on use

Recommended use : Consult the technical guidelines for the use of this  
substance/mixture.

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable liquids : Category 2

Eye irritation : Category 2A

### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open  
flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 2 of 17</b>

- P241 receiving equipment.  
Use explosion-proof electrical/ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash skin thoroughly after handling.
- P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/ attention.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

- P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

- P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

- Substance / Mixture : Mixture
- Chemical nature : organic solvent, inorganic pigment, inorganic metal-nonmetal compound, silicon/siloxane, silicatic material, metal/metal compound, glycol ether/-acetate, carbonic acid/ester/anhydride

**Hazardous components**

Chemical Name	CAS-No.	Concentration (%)
ethanol	64-17-5	>= 30 - < 50
Molybdenum(VI) oxide	1313-27-5	>= 5 - < 10
mica	12001-26-2	>= 5 - < 10
silicon	7440-21-3	>= 5 - < 10
manganese	7439-96-5	>= 1 - < 5

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 3 of 17</b>

2-butoxyethanol	111-76-2	>= 1 - < 5
ethyl acetate	141-78-6	>= 1 - < 5
Silica, amorphous	112945-52-5	>= 1 - < 5

## SECTION 4. FIRST AID MEASURES

- General advice : Consult a physician.
- If inhaled : Remove to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water and seek medical advice.
- If swallowed : If accidentally swallowed obtain immediate medical attention.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
- Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal. Clean contaminated floors and objects thoroughly while observing environmental regulations.

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 4 of 17</b>

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			1,900 mg/m3	
Molybdenum(VI) oxide	1313-27-5	TWA	1,000 ppm	OSHA P0
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
		TWA	5 mg/m3 (Molybdenum)	OSHA Z-1
			0.5 mg/m3 (Molybdenum)	ACGIH
mica	12001-26-2	TWA	5 mg/m3 (Molybdenum)	OSHA P0
			3 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
			3 mg/m3	OSHA P0
silicon	7440-21-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total)	15 mg/m3	OSHA Z-1

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GS LA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 5 of 17</b>

		dust)		
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
manganese	7439-96-5	C (Fumes)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	1 mg/m3 (Manganese)	NIOSH REL
		ST (Fumes)	3 mg/m3 (Manganese)	NIOSH REL
		TWA (Fumes)	1 mg/m3 (Manganese)	OSHA P0
		STEL (Fumes)	3 mg/m3 (Manganese)	OSHA P0
		TWA (Inhalable fraction)	0.1 mg/m3 (Manganese)	ACGIH
		TWA (Respirable fraction)	0.02 mg/m3 (Manganese)	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
ethyl acetate	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m3	NIOSH REL
		TWA	400 ppm 1,400 mg/m3	OSHA Z-1
		TWA	400 ppm 1,400 mg/m3	OSHA P0
Silica, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

### Hazardous components without workplace control parameters

Components	CAS-No.
------------	---------

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>	<b>GSLA_ULTRA Black Paste 50g</b>		
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 6 of 17

| boron orthophosphate | 13308-51-5 |

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

**Engineering measures** : Apply technical measures to comply with the occupational exposure limits.  
Provide adequate ventilation.

## Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Protective measures : Wear suitable protective equipment.  
Avoid contact with skin.  
When using do not eat, drink or smoke.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : green, yellow

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 14 °C  
Method: calculated

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 7 of 17</b>

---

Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Relative vapour density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble  soluble
Auto-ignition temperature	:	Not determined
Oxidizing properties	:	No data available
Refractive index	:	No data available
Volatile organic compounds (VOC) content	:	This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.  47.75 %  The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489):

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	Extremes of temperature and direct sunlight.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

inhalation (dust/mist/fume)

Skin

Eye contact

Skin Absorption

### Acute toxicity

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 8 of 17</b>

## **Components:**

### ***ethanol:***

Acute oral toxicity : LD50 Oral (Rat): 10,470 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 15,800 mg/kg

### ***Molybdenum(VI) oxide:***

Acute oral toxicity : LD50 (Rat, male and female): 4,461 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,840 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Target Organs: Mucous membranes  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No adverse effect has been observed in acute toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity

### ***silicon:***

Acute oral toxicity : LD50 Oral (Rat): 3,160 mg/kg

### ***manganese:***

Acute oral toxicity : LD50 Oral (Rat): 9 g/kg

### ***2-butoxyethanol:***

Acute oral toxicity : LD50 Oral (Rat, male and female): 1,200 mg/kg  
Method: OECD Test Guideline 401  
GLP: no

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### ***ethyl acetate:***

Acute oral toxicity : LD50 Oral (Rat): 6,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	<b>Page 9 of 17</b>

Acute dermal toxicity : LD50 Dermal (Rabbit): > 18,000 mg/kg

***Silica, amorphous:***

Acute oral toxicity : LD50 Oral (Rat): 3,160 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

**Components:**

***ethanol:***

Species: Rabbit  
Exposure time: 24 h  
Method: OECD Test Guideline 404  
Result: No skin irritation

***Molybdenum(VI) oxide:***

Species: Rabbit  
Exposure time: 4 h  
Assessment: No skin irritation  
Method: OECD Test Guideline 404  
Result: No skin irritation  
GLP: yes

***2-butoxyethanol:***

Species: Rabbit  
Exposure time: 72 h  
Method: OECD Test Guideline 404  
Result: Irritating to skin.  
GLP: yes

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:**

***ethanol:***

Species: Rabbit  
Result: Eye irritation  
Method: OECD Test Guideline 405

***Molybdenum(VI) oxide:***

Species: Rabbit  
Result: Irritating to eyes.  
Assessment: Irritating to eyes.

***silicon:***

Species: Rabbit  
Result: Mild eye irritation  
Method: Draize Test

***2-butoxyethanol:***

Result: Eye irritation

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 10 of 17

***ethyl acetate:***

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT Specific Target Organ Toxicity - single exposure**

Not classified based on available information.

**Components:**

***Molybdenum(VI) oxide:***

Assessment: May cause respiratory irritation.

**STOT Specific Target Organ Toxicity - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

**Components:**

***ethanol:***

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 9,268 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 11 of 17

### ***Molybdenum(VI) oxide:***

Toxicity to fish : (Oncorhynchus mykiss (rainbow trout)): 100 mg/l  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

(Pimephales promelas (fathead minnow)): 370 mg/l  
Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 100 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

(Daphnia magna (Water flea)): 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

### ***2-butoxyethanol:***

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,490 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l  
Exposure time: 48 h

### ***ethyl acetate:***

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 560 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (algae): 3,300 mg/l  
Exposure time: 48 h

## **Persistence and degradability**

### **Components:**

#### ***ethanol:***

Biodegradability : Remarks: No data available

#### ***Molybdenum(VI) oxide:***

Biodegradability : Remarks: No data available

#### ***mica:***

Biodegradability : Remarks: No data available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 12 of 17

***silicon:***

Biodegradability : Remarks: No data available

***manganese:***

Biodegradability : Remarks: No data available

***2-butoxyethanol:***

Biodegradability : Remarks: No data available

***ethyl acetate:***

Biodegradability : Remarks: No data available

***Silica, amorphous:***

Biodegradability : Remarks: No data available

## Bioaccumulative potential

**Components:**

***ethanol:***

Bioaccumulation : Remarks: No data available

Partition coefficient: n-  
octanol/water : log Pow: -0.349 (24 °C)

***Molybdenum(VI) oxide:***

Bioaccumulation : Remarks: No data available

***mica:***

Bioaccumulation : Remarks: No data available

***silicon:***

Bioaccumulation : Remarks: No data available

***manganese:***

Bioaccumulation : Remarks: No data available

***2-butoxyethanol:***

Bioaccumulation : Remarks: No data available

Partition coefficient: n-  
octanol/water : log Pow: 0.77 (20 °C)  
pH: 7

***ethyl acetate:***

Bioaccumulation : Remarks: No data available

Partition coefficient: n-  
octanol/water : log Pow: 0.73 (20 °C)

***Silica, amorphous:***

Bioaccumulation : Remarks: No data available

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 13 of 17

## Mobility in soil

### Components:

#### ***ethanol:***

Distribution among environmental compartments : Remarks: No data available

#### ***Molybdenum(VI) oxide:***

Distribution among environmental compartments : Remarks: No data available

#### ***mica:***

Distribution among environmental compartments : Remarks: No data available

#### ***silicon:***

Distribution among environmental compartments : Remarks: No data available

#### ***manganese:***

Distribution among environmental compartments : Remarks: No data available

#### ***2-butoxyethanol:***

Distribution among environmental compartments : Remarks: No data available

#### ***ethyl acetate:***

Distribution among environmental compartments : Remarks: No data available

#### ***Silica, amorphous:***

Distribution among environmental compartments : Remarks: No data available

## Other adverse effects

### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 14 of 17

Waste from residues : Dispose of wastes in an approved waste disposal facility.

## SECTION 14. TRANSPORT INFORMATION

### IATA-DGR

UN number : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(ethanol, ethyl acetate)  
Class : 3  
Packing group : II  
Labels : 3  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(ethanol, ethyl acetate)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUIDS, N.O.S.  
(ethanol, ethyl acetate)  
Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : TSCA\_12b - Not relevant

**TSCA list** : TSCA 5a - Not relevant

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 15 of 17

## EPCRA - Emergency Planning and Community Right-to-Know Act

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethyl acetate	141-78-6	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

- SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard
- SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313** : This product contains components that are reportable under the regulation.
- Chromium III CompoundsCobalt,  
inorganic compounds
- Molybdenum trioxide
- Manganese
- Certain Glycol Ethers

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product contains components that are reportable under the regulation.

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product contains components that are reportable under the regulation.

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains components that are reportable under the regulation.

### Massachusetts Right To Know

This product contains components that are reportable under the regulation.

### Pennsylvania Right To Know

This product contains components that are reportable under the regulation.

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 16 of 17

## New Jersey Right To Know

This product contains components that are reportable under the regulation.

## California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

- EINECS (European Union) : On the inventory, or in compliance with the inventory
- SWISS (Switzerland) : On the inventory, or in compliance with the inventory
- TSCA (United States) : On TSCA Inventory
- DSL/NDSL (Canada) : This product contains one or several components listed in the Canadian NDSL.
- AICS (Australia) : Not in compliance with the inventory
- NZioC (New Zealand) : Not in compliance with the inventory
- ENCS (Japan) : On the inventory, or in compliance with the inventory
- ISHL (Japan) : Not in compliance with the inventory
- KECI (Korea) : Not in compliance with the inventory
- PICCS (Philippines) : Not in compliance with the inventory
- IECSC (China) : On the inventory, or in compliance with the inventory
- TCSI (Taiwan) : Not in compliance with the inventory
- CICR (Turkey) : Not in compliance with the inventory
- INSQ (Mexico) : Not in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 06/04/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>1436333</b>		<b>GSLA_ULTRA Black Paste 50g</b>	
Product specification	<b>RS_FP_606158</b>	Revision Date	<b>06/04/2020</b>
Version	<b>2.1</b>	Print Date	<b>06/04/2020</b>
Material number	<b>1436333</b>	Page	Page 17 of 17

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN