

## TPM series (90W~180W , 1mV/0.1mA, with USB interface)

### Introduction

TPM series are high precision programmable DC power supply with **single output, output power rated from 90W to 180W with various model numbers**. A remarkable feature of the TPM series is high resolution 1mV/0.1mA. Delay Time and Auto Run facilitate automatic test in different applications. USB/RS-232 interface, SCPI command sets make remote control easier. The smart cooling fan ensures low noise. Over load, over voltage, over current, over temperature and reverse polarity protections protect the TPM series and their load from unexpected conditions. High stability and high accuracy further make TPM series an ideal option for various applications requiring high resolution and accurate control.

### Features

- ✓ 1CH output with 2 selectable output ranges (TPM-3003/3005)
- ✓ High resolution 1mV/0.1mA
- ✓ 24-bit ADC and 16-bit DAC, high accuracy
- ✓ Over load, over voltage, over current, over temperature and reverse polarity protections
- ✓ Constant voltage and constant current operations, auto CV and CC switch
- ✓ 122x32 backlit LCD display for full output details
- ✓ High speed rotary dial and keypad input
- ✓ Built-in beeper alarm
- ✓ Panel lock and output ON/OFF function
- ✓ 100 sets save & recall for voltage and current setups
- ✓ Delay time setup (99999s) and AUTO running program for easy AUTO test
- ✓ Standard USB interface, support SCPI commands, support Labview
- ✓ Optional RS-232 interface

### Product photo



TPM-3003



TPM-6003E

# Programmable Linear DC Power Supply



## Specifications

Constant voltage operation			
Line regulation	≤0.01%+3mV		
Load regulation	≤0.01%+3mV (I≤3A); ≤0.02%+5mV (I>3A)		
Ripple & Noise (5Hz~1MHz)	≤1mVrms (I≤3A); ≤2mVrms (I>3A)		
Recovery time	≤100us (50% load change, minimum load 0.5A)		
Constant current operation			
Line regulation	≤0.2%+3mA		
Load regulation	≤0.2%+3mA (I≤3A); ≤0.2%+5mA (I>3A)		
Ripple & Noise	≤3mA rms (I≤3A); ≤6mA rms (I>3A)		
Display			
Voltmeter	5 digits LCD display		
Ammeter	5 digits LCD display		
Setting accuracy (25±5°C)	Voltage: ±(0.03% reading+10mV) Current: ±(0.2% reading+10mA)		
Reading accuracy (25±5°C)	Voltage: ±(0.02% reading+5mV) Current: ±(0.02% reading+5mA)		
General			
Protection	Over load, over voltage, over current, over temperature and reverse polarity protections		
Panel lock	Provided		
Interface	USB interface, support SCPI commands, support Labview Optional RS-232 interface		
Memory	100 sets		
Insulation	Between base and output terminal: ≥20MΩ/500VDC Between base and AC power cord: ≥30MΩ/500VDC		
Operating environment	Indoor use Relative humidity: ≤80%	Altitude: ≤2000m Installation category: II	Ambient temperature: 0~40°C Pollution degree: 2
Storage environment	-10°C~70°C, ≤70%RH		
Power source	AC110V/220V±10% selectable, 50/60Hz		
Accessories	Power cord x1, Operation manual x1, USB cable x1, Software CD x1, Test lead x1		

## Selection guide

Model	TPM-3003		TPM-3005		TPM-3003E	TPM-3005E	TPM-6003E
Output voltage	0~36V	0~15V	0~36V	0~15V	0~30V	0~30V	0~60V
Output current	0~3A	0~6A	0~5A	0~10A	0~3A	0~5A	0~3A
O.V.P. range	0.1~38V		0.1~38V		0.1~34V	0.1~34V	0.1~64V
O.C.P. range	0.1~6.5A		0.1~11A		0.1~3.5A	0.1~5.5A	0.1~3.5A
Resolution	1mV/0.1mA		1mV/1mA		1mV/0.1mA		
Dimension (WxHxD)	130x160x310mm						
Weight	5.5kg		6.2kg		4.5kg	5.5kg	5.5kg

Specifications are subject to change without prior notice.

TWINTEX · [www.twintex.com.tw](http://www.twintex.com.tw)

Taipei, Taiwan: Tel: +886-02-2915 0101 · Fax: +886-02-2916 0101  
Shenzhen, China: Tel.: +86-755-2812 9890 · Fax: +86-755-2814 9802