Botron B496203 Technical Data Sheet



Overview:

Botron's New B496203 Intelligent DC-Ionizer 3 Fan Overhead Ion blower is internet ready and monitored with a built-in LED screen. Built-in LED lights and an advanced DC type design. Easy to hang with bolt on brackets. Low energy, only 34W. Easy to remove fan grill for easy service of extended life emitters. Fast static decay and excellent ion balance. Comes with Auto Ion Balance and an Abnormal HV monitoring system.


PERFORMANCE

Ion balance +/- 5vDecay time at $12" +/- 1000V \sim +/- 100V < 1.0$ seconds

*All results are based according to EOS/ESD-STM 3.1-2000.

*Results may vary based on test conditions.

Power supply Type Coverage Air volume Noise level Temperature Humidity Ozone Indicator Controls Mounting Emitter Dimensions Weight	110/220 DC 1', 1 sec - 2', 5 sec - 3', 9 sec 100 - 232 cfm 35dB at 3.2' 68-104F (0 - 40 C) 20% - 70% RH < 0.007 ppm LED Screen On/Off switch, Light Brackets Tungsten Alloy 6.3"H x 37"W x 3.4"D 13.2 lbs



- DC Technology
- Variable Speed Control
- Internet Ready
- Monitored Software



APPLICATIONS

As with all of Botron's ionization units, the B496203 is designed neutralize electrostatic charge in personal bench top environments, sensitive materials assembly, packaging, clean room and laboratories. The unit can be mounted but is not limited to the underside of shelving, ceilings and walls.

INSTALLATION

- 1. Remove contents from package.
- 2. Mount the ionizer in desired position.
- 3. Make sure there are no obstructions between the target area and ionizer.
- 4. Install power cord securely.
- 5. Turn switch on.
- 6. Adjust air flow accordingly.

OPERATION

Power on unit and adjust air flow for maximum neutralization.

Aim unit at the area or items to be neutralized.

PART NUMBERS

B496201 Intelligent Benchtop Ionizer B496202 Intelligent 2 Fan Overhead Ionizer B496203 Intelligent 3 Fan Overhead Ionizer