**Windows**   Follow the steps below to set up your new GR251U microchip reader. If you have any questions, feel free to contact us.

Step 1:

- Connect the communication cable to your computer's USB port and wait till the drivers are installed.

- Make sure you have administrator access on the computer you are installing the drivers.

- You can verify if the drivers are installed properly under 'Device Manager'

- To access device manager Hit Star ➡ Type 'Device Manager'.

Step 2:

- Open Device manager following the previous step and select 'Ports' and make note of the COM number next to Prolific-USB-Serial Port.

Step 3:

- Download the software from Microchips Australia website here https://microchips.com.au/pages/gr250-support

- Unzip the file and run the software installation file and follow the steps to complete the installation.


Step 4:

- Run the software installation file and follow the steps to install the program.

- Once installed open the 'GR25X Download Tool.

Need more help? | **Call** 03 9706 3165   **or**   **Email** info@microchips.com.au

Windows | Follow the steps below to set up your new GR251U microchip reader. If you have any questions, feel free to contact us.


Step 5:

- From the 'COM Port' drop down list, select the COM number you made note of under device manager and click 'Connect'.

- Allow up to 30 seconds for the software to make a connection with the reader.

Step 6:

- After connection is established, you will see the following screen.

Step 7:

- To download data from the reader, Select 'Download Data' button.

- All the saved transponder codes will appear on the box below.

Windows | Follow the steps below to set up your new GR251U microchip reader. If you have any questions, feel free to contact us.


Step 8:

- To save this data to a file, select 'Store in File' button and 'OK' on the next screen.

- Choose where you want to save the file and give the file a name and save file.

  You can open the saved .csv file using Microsoft excel.

Step 9:

- After you have saved the file, you can choose to clear the memory by selecting 'Clear Reader Memory'.

Step 10:

- Make sure you disconnect the software before removing the communication cable.