SC450 How To

Prepare for use

1



Unplug battery charger.

2



Wrap cord accordingly.

3



Lower recovery tank lid.

4



Inspect ball float cage.

5



Fill solution tank with water (do not exceed 130°F).

6



Inspect squeegee blade and install squeegee.

7



Inspect brush or pad.

8



Install brush or padholder under the deck.

9



Turn on brush/pad-holder switch.

10



Press handle button to engage brush. Repeat this step if necessary.

11



Choose solution flow for the type of work to be performed.

12



Lower squeegee lever.

SC450 How To

Store the Machine

2

5

8



Empty recovery tank and solution tank.



Wash recovery tank and vacuum grid with clean water.



Inspect and clean, cover gasket, vacuum grid and automatic shut-off float.



Inspect hoses; replace if kinked or damaged.



Remove, rinse and inspect squeegee. Replace if needed.



Remove, clean and inspect brush or pad. Rinse with warm water. Hang to dry. Replace if needed.



4



Lift recovery tank lid.



Charge batteries.

9

6



Plug machine up to charge for next use.



SC450 How To Weekly Maintenance 2 Check each battery Perform a squeegee cell's water level (does Inspect and clean blade check. not apply to gel solution filter. batteries). Yearly Maintenance Yearly Maintenance Six Month Maintenance Brush/pad-holder motor 5 Vacuum system motor Perform a screw and 4 6 nut tightening check carbon brush check or carbon brush check or replacement replacement

