



Model	T260	T290	T300	T3
Cleaning Path and Type	20" disk	20" disk	20" disk 24" disk 20" orbital	20" disk
Propel Option	Pad Assist	Pad Assist Traction Drive	Pad Assist Traction Drive	Pad Assist Traction Drive
Battery Configurations	135AH AGM	130AH Lead Acid 140AH AGM	130AH Lead Acid 150AH Lead Acid 140AH AGM 90AH Lithium Ion	130AH Lead Acid 155AH Lead Acid 140AH AGM
Charger	Offboard	Onboard	Offboard Onboard	Offboard Onboard
Solution/Recovery Tank Size	10.5 / 11.5 Gallons	10.5 / 13 Gallons	11 / 14 Gallons	10.5 / 15 Gallons
Solution Flow Rates	Variable up to .4 GPM	N/A	Low: .15 GPM Medium: .35 GPM High: .5 GPM	Variable up to .4 GPM
Down Pressure	45lbs	40lbs	51lbs 90lbs (Optional)	50lbs 90lbs
Brush/Pad Speed	150 RPMs	155 RPMs	230 RPMs	230 RPMs
Sound Level (DBA)	72	74	64.9 57.8 (Optional)	68.5
Dimensions (L X W X H)	51.2 x 20.4 x 43.3 Squeegee Width 30.4"	48.4 x 20.3 x 37.8 Squeegee width 32"	54 x 22 x 43.10 Squeegee Width 30"	50.25 in X 22 in X 43 Squeegee Width 30"
Weight (standard batteries)	312lbs	346lbs (Pad Assist) 357lbs (Traction Drive)	376lbs (Pad Assist) 400lbs (Traction Drive)	343lbs (Pad Assist) 391lbs (Traction Drive)
Vac Motor HP	.4 HP	.65 HP	.6 HP	.5 HP
Brush Motor HP	.55 HP	.73 HP	1 HP	1 HP