Vantage 14 How To

Prepare for use

1



Unplug battery charger.

2



Wrap cord accordingly.

3



Inspect brushes or pads then install.

4



Inspect then install squeegee blade.

5



Inspect ball float cage.

6



Lower recovery tank lid.

7



Fill solution tank. (temperature should not exceed 130°F).

8



Install brush or padholder.

9



Make sure brush is properly installed under the deck.

10



Press the push-button and the brush lever to engage the brush/padholder then release.

11



Choose desired program for the type of work to be performed.

12



Press the solution flow control switch.

Vantage 14 How To

Store the Machine

1



Empty recovery tank and solution tank.

2



Rinse and wash recovery tank with clean water.

3



Inspect and wash, vacuum grid and automatic shut-off float.

4



Remove, rinse and inspect squeegee. Replace if needed.

5



Remove, clean and inspect brush or pad. Rinse with warm water. Hang to dry (Replace if needed).

6



Lift recovery tank lid.

7



Charge batteries.

8



Wipe exterior of machine with a damp cloth.

9



Leave recovery tank open for ventilation.



Vantage 14 How To

Daily, Weekly and Occasional Maintenance

1



Clean brush daily.

2



Clean squeegee daily by removing debris.

3



Check each battery cell's water level (does not apply to gel batteries).
Charge batteries daily.

4



Clean tank and vacuum grid daily.

5



Perform squeegee blade check and/or replacement weekly.

Every 6 Months

6

Screw and nut tightening check. Perform this task after the first 8 hours of operation.

7



Brush deck rubber pad check and/or replacement

8



Brush deck end-ofstroke cable check and/or replacement yearly.

9

Brush deck rubber flange check and/or

replacement yearly.

