



# INDUSTRY'S MOST COMPLETE AIR MOVER LINE

The world's lightest and quietest air movers and dryers...



**Mini Mighty Series**  
138 W - 1/4 HP  
600 CFM - 925 CFM



**400 Series**  
1/4 HP - 1/3 HP  
1,600 CFM - 2,000 CFM

**600 Series**  
1/3 HP - 1/2 HP  
2,400 CFM - 2,800 CFM

**800 Series**  
3/4 HP - 1 HP  
3,200 CFM - 3,600 CFM



**XPOWER Air Movers & Dryers are leading the industry in innovation**

- Fully integrated motor and housing design
- Lightest and quietest air mover in the industry
- Powerful and energy efficient 138 Watts to 1 HP motor
- Compact, durable and rugged plastic housing models
- Multiple angle positions for different drying and ventilating applications
- International safety certifications



**XPOWER MANUFACTURE, INC**  
240 CLARY AVENUE, SAN GABRIEL, CA 91776  
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

**WWW.XPOWER.COM**

# SPECIFICATIONS

Air Mover Series	MINI MIGHTY SERIES				400 SERIES	
Model No.	80A	100A	130A	230AT	400	430
Voltz/Hertz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz
Motor	138 W	173 W	1/5 HP	1/4 HP	1/4 HP	1/3 HP
Power	1.2A	1.5 A	2.0 A	2.3 A	3.0 A	3.8 A
Rated Airflow	600 CFM	600 CFM	700 CFM	925 CFM	1600 CFM	2000 CFM
Speeds	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed
Cord Length	10 ft	10 ft	10 ft	10 ft	20 ft	20 ft
Operating Positions	4	4	4	4	4	4
Stackable	Yes	Yes	Yes	Yes	Yes	Yes
3 Hour Timer	No	No	No	Yes	No	X-430TF
Daisy Chain	Yes	Yes	Yes	Yes	X-400A	No
Filter Kit	No	No	No	No	OPTIONAL	X-430TF
Unit Weight	7.9 Lbs.	9.5 Lbs.	9.3 lbs	9.9 Lbs.	15 - 17.2 Lbs.	15 - 17 Lbs.
Unit Dimensions (LxWxH)	11.5" x 9.3" x 12.3"	10.7" x 12.4" x 13.3"	10.7" x 12.4" x 13.3"	10.7" x 12.4" x 13.3"	13.9" x 14.8" x 14.6"	13.9" x 14.8" x 14.6"
Housing	PP	PP	PP	PP	PP & ABS	ABS
Safety Certifications	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL
Dual Thermal Protection	Yes	Yes	Yes	Yes	Yes	Yes
Pallet Quantity	84 Units	72 Units	72 Units	72 Units	45 Units	45 Units

Air Mover Series	600 SERIES		800 SERIES	
Model No.	600	630	800	830
Voltz/Hertz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz
Motor	1/5 & 1/3 HP	1/2 HP	3/4 HP	1 HP
Power	1.5-3.8 A	5.0 A	7.5 A	8.5 A
Rated Airflow	2400 CFM	2800 CFM	3200 CFM	3600 CFM
Speeds	3 Speed	3 Speed	3 Speed	3 Speed
Cord Length	25 Ft	20 Ft	20 - 25 Ft	20 - 25 Ft
Operating Positions	4	4	4	4
Stackable	Yes	Yes	Yes	Yes
3 Hour Timer	No	No	X-800TF	No
Daisy Chain	X-600A (GFCI)	No	No	No
Filter Kit	Optional	Optional	X-800TF	Optional
Carpet Clamp	Optional	Optional	Optional	Optional
Telescopic Handle w/ Wheels	No	No	P-800H (3 Position)	P-830H & X-830H (3 Position)
Unit Weight	21.5 Lbs.	18.7 - 21.9 Lbs.	23 - 27.6 Lbs.	24 - 28.5 Lbs.
Unit Dimensions (LxWxH)	15.9"x15.7"x16.3"	15.9"x15.7"x16.3"	15.9"x18.7"x18.7"	15.9"x18.7"x18.7"
Housing	PP & ABS	PP	PP & ABS	PP & ABS
Safety Certifications	ETL / CETL	ETL / CETL	ETL / CETL	ETL / CETL
Dual Thermal Protection	Yes	Yes	Yes	Yes
Pallet Quantity	36 Units	24 - 36 Units	16 Units	16 Units

## ACCESSORIES:

### Filter Kit

400 Series - **400FK**  
600 Series - **600FK**  
800 Series - **800FK**



### 600/800 Series - **CCK**



Carpet Clamp Kit

### Telescopic Handle

600 Series - **600HK**  
800 Series - **800HK**



## INDUSTRIES WE SERVE



WATER DAMAGE



FIRE & SMOKE DAMAGE



MOLD REMOVAL



RESTAURANT

