

# SPEED SCRUB® 350 | STAND-ON SCRUBBER



## Product Specifications

Feature	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel
Cleaning Tool Attachment	Insta-Click™ Standard	
Machine Speed Top Scrub and Forward Transport Top Reverse Transport	3.6 mph (5.8 km/hr) 1.1 mph (1.8 km/hr)	
Scrubbing Coverage Rate Per Hour Theoretical Max Conventional - Practical ec-H2O NanoClean® - Practical	31,680 ft2 (2,946 m2) 24,588 ft2 (2,287 m2) 25,284 ft2 (2,351 m2)	38,016 ft2 (3,535 m2) 30,052 ft2 (2,795 m2) 30,903 ft2 (2,874 m2)
<b>Control Panel</b>		
Pro-Membrane™	Standard	
LCD Pro-Panel® Touch Screen	Optional	
<b>Brush/Pad Drive System</b>		
Cleaning Path	20 in / 500 mm	24 in / 600 mm
Pad/Brush RPM	215 rpm	275 rpm
Pad/Brush Down Pressure	62 & 90 lbs (28 & 41 kg)	64 & 91 lbs (29 & 41 kg)
Scrub Motor	24 VDC, 0.87 HP / 0.65 kW	
<b>Solution and Recovery Systems</b>		
Solution Tank Capacity	14.1 gal (53 L)	
Recovery Tank Capacity	18.4 gal (70 L)	
Drive Motor	24 VDC, 0.64 HP / 0.48 kW	
Vacuum Motor	24 VDC, 0.62 hp / 0.46 kW	
Vacuum Water Lift	42 in (1,067 mm)	
<b>Cleaning Technology</b>		
Conventional	Standard	
ec-H2O NanoClean® Technology	Optional	
Conventional Water Flow	0.15 / 0.35 / 0.50 gpm 0.57 / 1.32 / 1.89 lpm	
ec-H2O NanoClean® Technology Water Flow	0.12 / 0.25 / 0.35 gpm 0.45 / 0.95 / 1.32 lpm	

Feature	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel
<b>Battery System</b>		
System Voltage / Battery Count	24 Volts / 4	
Batteries	Wet 210 AH Wet 240 AH (Provides longest run time) Sealed AGM 220AH	
Battery Run Time (Up to Hours)	3.1	4.0
On-Board Charger	Yes	Yes
Off-Board Charger	Yes	Yes
<b>Decibel Ratings At Operator Ear</b>		
Standard - dBA	63.7	64.5
Quiet-Mode™ - dBA	59.7	61.3
<b>Machine Dimensions and Weights</b>		
Overall Width with Squeegee	30.1" / 765 mm	31.2" / 793 mm
Length X Width X Height	55 X 26.5 X 49 Inches 1,397 X 673 X 1,245 mm	
Weight (less batteries)	490 lbs / 222 kg	495 lbs / 225 kg
Weight (with batteries)	725 lbs / 329 kg	730 lbs / 331 kg
<b>Product Backing</b>		
Warranty	10 years Rotomold - 3 years Parts 2 years Labor - 6 months of Trip	

Specifications are subject to change without notice.

